

GENERAL NOTES:

1.

The Contractor shall comply with all applicable safety regulations. All construction shall be completed following current City Standard Specifications and Special Provisions.
2.

Contractor will be required to provide notice to utility companies a minimum of seventy-two (72) hours prior to any excavation, as follows:  
  
Kansas One-Call                      687-2470  
  
The Contractor must notify the following in case of an emergency:  
  
AT&T                                      1-800-246-8464  
City of Wichita Water & Sewer Dept.    1-316-219-8921  
City of Wichita Stormwater            1-316-268-4090  
City of Wichita Traffic                1-316-268-4034  
Cox Communications                1-888-249-3530  
Evergy                                  1-800-544-4857  
Kansas Gas Service                  1-888-482-4950  
Southern Star Central Gas            1-800-324-9696
3.

Utility service lines, poles, etc. are to be adjusted as necessary by others prior to construction unless the plans specifically call for their adjustment by the Contractor or unless the plans specifically identify a utility to be adjusted by its owner during construction. Existing utilities and their location, as shown on the plans, represent the best information obtainable for design. The Contractor will be required to work around existing utilities within the Right-of-Way which do not conflict with proposed construction.
4.

Rubble from the removal of miscellaneous structures and excess excavation which is to be wasted shall be disposed of on sites to be provided by the Contractor. These sites shall be approved by the Engineer as to suitability, appearance and site location. Locations, in the opinion of the Engineer, that will leave an unsightly appearance will not be approved. All disposal sites must be approved by the Kansas Department of Health and Environment. Material either stockpiled or disposed of in a flood plain would require a Kansas State Board of Agriculture permit. Any material dumped in waters of the United States or wetlands is subject to U.S. Corps. of Engineers permitting regulations. Any material buried or stockpiled beyond approved construction limits would require additional archaeological investigations unless buried in a previously approved borrow location.
5.

Trees and shrubs in public Right-of-Way which are in direct conflict with proposed new construction shall be removed by the Contractor with the Engineer's approval. Trees and shrubs which are not in direct conflict with proposed new construction shall be saved and protected from damage.
6.

The Contractor shall give all property owners and/or tenants of developed property abutting the construction of this project a minimum of ten (10) days notice prior to start of construction.
7.

The Contractor shall be responsible for preserving property irons. The Contractor will be required to re-establish any property irons which are damaged or destroyed by his construction operations. Such irons shall be re-established by a licensed land surveyor in accordance with state laws.
8.

The Water Distribution Division shall field locate water valves one time during construction when requested by the Contractor. It shall be the Contractor's responsibility to preserve such field locations during the construction process. Water valves, valve boxes or fire hydrants damaged during construction shall be repaired by the Contractor at his own expense. Valve boxes and water meters within the project limits shall be adjusted to match field grades.
9.

The Contractor shall protect from damage and support existing utilities during construction as approved by the utility owner and Engineer at the Contractor's expense.
10.

If traffic is impacted by construction, a traffic control plan must be submitted and approved by the City Traffic Engineer, at traffic@wichita.gov before construction can begin. The Contractor shall be responsible for all traffic control measures to facilitate construction. All construction zone markings and signage shall conform to the latest version of the Manual on Uniform Traffic Control Devices (MUTCD) as published by the US Dept. of Transportation, Federal Highway Administration. All costs associated with construction markings and signage shall be the Contractors responsibility.
10.

All elevations shown are NAVD 88.
11.

All existing pavement and curb and gutter within the construction limits shall be saw cut, full depth, to the lines shown on the plans, or to the nearest joint, and removed, unless otherwise noted. If removal limits are within three feet of a joint, remove to the joint.
12.

All traffic control devices in the work zone (including markings and signs) and their installation and maintenance shall comply with the latest edition of the Manual on Uniform Traffic Control Devices (MUTCD). All traffic control devices in the traveled way or clear zone shall be crashworthy (NCHRP Report 350 or MASH compliant).

13.

All construction equipment, including vehicles, materials, and debris, shall be stored outside of the clear zone. Where this cannot be achieved the contractor shall place appropriate signs, abject identifiers, and/or barricades in compliance with the MUTCD.
14.

Except when required for safety, traffic control shall not block any lanes or sidewalks when work is not being performed.
15.

No shrink or swell factors have been applied to the earthwork quantities shown on this project. All earthwork quantities are based on raw surface volume comparisons.
16.

Contractor shall limit the extent of trench openings over nights and weekends to less than 50 feet.
17.


Subdivision Benchmark - (1 flat survey marker No. 8134-08 3" top diameter) in top of curb adjacent to each Fire Hydrant. Cost shall be incidental to L.F. Concrete C&G, Comb. Type 2 (3 5/8").
18.

All street ROW and Reserves shall be permanent seeding, all other areas may be temporary seeding. All seeding per City of Wichita Specifications.
19.

Excess dirt generated from installation of underground utilities is to remain on iste and be stockpiled on Reserve 'B'.
20.

All required testing is the contractor's responsibility.
21.

All coordinates listed are modified NAD83 Kansas State Plane Zone South unless otherwise noted. To convert listed coordinates to NAD83 Kansas State Plane Zone South coordinates, multiply the northing and easting by the project scale factor of 0.999884699. Elevation datum is NAVD88 Geoid 12B unless otherwise noted.



Benchmarks

BENCHMARK #1:  
CHISELED SQUARE ON THE TOP OF SIDEWALK, 44 FEET EAST OF THE CENTERLINE OF WEBB RD AND 1,986 FEET NORTH OF THE CENTERLINE OF PAWNEE.  
ELEVATION = 1377.19 (NAVD88, G12B)

BENCHMARK #2:  
CHISELED SQUARE ON THE TOP OF SIDEWALK, 42 FEET EAST OF THE CENTERLINE OF WEBB RD AND 1,744 FEET NORTH OF THE CENTERLINE OF PAWNEE.  
ELEVATION = 1377.96 (NAVD88, G12B)

PAVING IMPROVEMENTS

to serve


CHALET RIDGE

CITY OF WICHITA, KANSAS

Gary Janzen, P.E. City Engineer

Project Number 472-2019-085590

O.C.A. NO. 766485



PROJECT LOCATION

Vicinity Map

STORM SEWER 4

STORM SEWER 5

STORM SEWER 2

STORM SEWER 1

BENCHMARK #1

BENCHMARK #2

STORM SEWER 3

IMPROVEMENT DISTRICT

Sheet Index

Sheet	Title
1	TITLESHEET
2	SITE CLEARING PLAN
3	CURB & GUTTER DETAILS
4	VALLEY GUTTER DETAILS
5	ASPHALT PAVING DETAILS
6	SIGN DETAILS
7	WHEELCHAIR RAMP DETAILS
8	ANNABELLE
9	ANNABELLE
10	ANNABELLE CIR
11	ANNABELLE CIR
12	THATCHER CIR
13	THATCHER
14	THATCHER CT
15	THATCHER CT
16	EMERGENCY ACCESS
17	INTERSECTION GRADING
18	INTERSECTION GRADING
19	CUL-DE-SAC & HAMMERHEAD GRADING
20	PEDESTRIAN WALK PLAN
21	BACKYARD INLET DETAILS
22	TYPE 1A INLET DETAILS
23	TYPE 1 INLET DETAILS
24	PAVEMENT UNDERDRAIN DETAILS
25	STORM SEWER 1
26	STORM SEWER 1
27	STORM SEWER 1
28	STORM SEWERS 2 & 3
29	STORM SEWER 4
30	STORM SEWER 5
31	FOUR-CORNER GRADING PLAN
32	TYPICAL GRADING SECTIONS
33	GRADING PLAN
34	BUILDING COMPACTION PLAN
35	PAVING COORDINATE MAP
36	LOT GRADING COORDINATE MAP
37	POND GRADING COORDINATE MAP
38	POINT TABLES
39	POINT TABLES
40	POINT TABLES
41	EROSION CONTROL PLAN
42	BACK OF CURB PROTECTION & CONSTRUCTION ENTRANCE
43	SILT FENCE DETAILS
44	STRAW BALE DETAILS
45	STREET IMPROVEMENT PLAN
46	SUBDIVISION DEVELOPMENT PROCESS
47	FINAL PLAT

EARTHWORK QUANTITIES

Description	Cu. Yds.
Cut	17,350
Fill	16,700
Net (Cut)	650

APPROVED AS NOTED  
BY WICHITA PUBLIC WORKS ENGINEERING  
AND STORMWATER DIVISION

Engineering \_\_\_\_\_

Stormwater \_\_\_\_\_

February 2020

PLANS PREPARED BY



GARVER  
8535 E. 21st Street N.  
Suite 130  
Wichita, KS 67206  
(316) 264-8008  
www.GarverUSA.com  
Project No. 19T41021