



SCALE 1" = 50'

EROSION CONTROL ITEMS TO BE COMPLETED WITH SANITARY SEWER LINE CONSTRUCTION		
STABILIZED CONSTR ENTRANCE	1	EA
INLET SEDIMENT BARRIER	4	EA
OUTLET PROTECTION	1	LF
CURLEX	39180	SF

- ① LINEAR SEDIMENT BARRIER
- ② INLET SEDIMENT BARRIER
- ③ OUTLET PROTECTION

NOTES:

BMP'S INDICATED ON THIS PLAN ARE A GUIDE. CONTRACTOR SHALL ADD PERIMETER PROTECTION AS NECESSARY TO PREVENT OFF-SITE SILT TRANSPORT. CONTRACTOR IS ALSO RESPONSIBLE FOR MAINTAINING EXISTING BMP'S ONSITE.

CURLEX WILL BE INSTALLED FROM CURB TO RIGHT OF WAY OR THE EDGE OF SIDEWALK AFTER PAVING INSTALLATION IS COMPLETE.

INSTALL CURLEX SEE NOTE THIS SHEET

<p>Fawn Grove Phase 4 Paving Erosion Control Plan WICHITA, KANSAS</p>			
	<p>Ruggles & Bohm, P.A. Engineering, Surveying, Land Planning</p>		<p>DESIGN E.JG DRAWN RLS REVIEW UTILITY</p>
	<p>924 North Main Wichita, Kansas 67203 www.rbkansas.com</p>		<p>(316) 264-8008 (316) 264-4621 fax E-mail: info@rbkansas.com</p>
<p>DRAWING FILE {NPDES}</p>	<p>PROJECT NUMBER 472-84576</p>	<p>DATE June 18, 2007</p>	<p>SHEET 14 of 32</p>