BM 98.80 R.R. Spike N.W. Side Wood Street Lite Pole on S.E. Cor. Richmond & Southgate

NOTE: CORRUGATED METAL PIPE SHALL CONFORM TO THE APPLICABLE SECTIONS OF SECTIONS R-6 AND R-8 OF THE 1966 STANDARD SPECIFICATIONS OF THE KANSAS HIGHWAY COMMISSION. CORRUGATED METAL PIPE FURNISHED FOR THIS PROJECT SHALL BE TYPE I WITH TYPE "B" BITUMINOUS COATING.

SCALE: Hor. 1"=20'
Ver. 1"=5'

MERIDIAN AVE.
(Existing Pav't.)

Existing Ditch

15' bottom

Iron Sta. 0+70

27.5'

Sta. 0+00

SUNNYBROOK LANE (Future Pav't)

Start Project Sta. 0+57.20

Future double 7'x2' RCB
Flowline level @ 94.24

Constr. Std. 4' dia. Type B Manhole
Sta. 3+60. Use wide flange
M.H. ring 59

Bell Pole

Iron Sta. 4+11.70

27.5'

Install ~~23"x14" RCEP~~ or 25"x16" CMPA

Constr. Std. 2'x5' Inlet
Top 98.30

Constr. Std. 2'x5' Inlet
Top 98.30
73.5
Install 71' of 15" RCP or ~~15" CMP~~

31' B/B

Flo. 96.05

Flo. 94.85

Proposed Pav't
RICHMOND AVE.

7.5'

7.5'

31' B/B

Start Project
Sta. 0+57.20

EXISTING GROUND

Sta. 3+60
Std. 4' dia. Type B M.H.

Elev. top M.H. 98.2

FUTURE TOP OF CURB(+0.12574 %±)

Sta. 4+57.20
Std. 2'x5' Inlet

100
95
90

94.25 94.29 94.34 94.39 94.44 94.49 94.54 94.55 94.59 94.64 94.69 94.74 94.79 94.84 94.85

600' of 23"x14" RCEP @ +0.10% or
600' of 25"x16" CMPA @ +0.10%

DONALD E. SCHREIBER
LICENSED
6311
KANSAS
PROFESSIONAL ENGINEER

INCIDENTAL
DRAINAGE IN CONNECTION WITH RICHMOND AVE. FROM S.L. SOUTHGATE TO N.L. BLOCK 4, BUILDERS 14th ADDITION.

CITY OF WICHITA, KANSAS

R.W. LINN, CITY ENGINEER

DATE: Dec. 1973

PROJECT NO. DAKD 569056

SHEET 1 OF 1

Final Meas.
S.W.S. #2 JAK

1 2 3 4 5 6