B.M. 1528.3 SE Cor Conc. Pav. Hd. # 2268 N. Volutsia.
B.M. 1685.9 20# Spike W.S. P.P. E.L. Chautauqua, NL 22nd

N

STREET

+10.6 P.P. 1.5'S.L.
+19.5 2"Tree 8'S.L.
+14.3 2"Tree 5.2'S.L.

+39.3 10'D-0.8'R, Gen. 29.2'E.
+30.3 30"Elm +7'S.L.
+80 10'D-0.5'R, Gen. 25.2'E.
+39.6 10'D-0.5'R, Gen. 27.1'E.
+74.8 P.P. 16'S.L.
+83.2 E.10'D-0.5'R, Gen. 29.2'E.
+39.5 E.10'D-0.5'R, Gen. 27.6'E.
+83.6 E.10'D-0.5'R, Gen. 30.2'E.
+57.1 E.10'D-0.5'R, Gen. 30.2'E.
+57.8 P.P. 2.4'S.L.
+21.6 Cy. Mon. 0.4'E.

Note
Use an extra 5' rein. bar between each standard transverse bar over sewer ditch. Make the base 7" thick over sewer ditch.

-1600' @ 1/4% Wk. 0.8'
+2,654' @ 1/4% Wk. 0.8'

P I
160.50
200' V.C.

P I
El. 167.20
30' V.C.

0+00 | 7+50 | 1+00 | 7+50 | 2+00 | 7+50 | 3+00 | 7+50 | 4+00 | 7+50 | 5+00 | 7+50 | 6+02.45

6.50	6.8		5.70	5.9		4.90	4.9		4.10	3.8		3.30	2.6		2.50	1.1		1.96	1.7		1.93	0.1		2.89	1.0		3.58	1.2		4.88	3.6		6.21	5.5		7.40	7.5
166.10			165.50	5.1		164.50			163.70			162.90			162.10	P.C.		161.77	161.56		161.83			161.53	6.76		162.09	162.66		163.15	P.T.		164.48			165.81			166.80	N.T.00	
5.60	6.6		4.80	5.1		4.00	4.3		3.20	3.2		2.60	1.9		1.60	1.6		1.06	1.0		1.03	0.7		1.59	1.0		2.65	1.2	18"CSP	3.98	3.4		5.31	5.4		6.50	6.8	
5.67	6.6	No	5.13	5.1		4.36	4.3		3.53	3.0		2.75	2.2		1.97	1.8		1.43	1.5		1.61	1.1		1.96	1.5		3.01	1.9		4.39	4.1		5.68	5.8	No	6.57	6.7	
5.75	6.6	Crown	5.29	5.3		4.51	4.4		3.76	3.6		2.98	2.4		2.15	2.2	CHAUTAUQUA	1.82	1.7		1.60	1.4		2.15	1.9		3.19	2.0		4.50	4.7		5.81	6.0	Crown	6.65	6.7	
5.82	6.3		5.26	5.3		4.64	4.3		3.68	3.3		2.89	2.7		2.11	2.0		1.39	1.8		1.57	1.0		2.12	1.7		3.15	2.0		4.95	5.5		5.76	5.9		6.72	6.1	
5.90	5.8		5.43	5.8		4.86	5.0		3.89	4.0		2.91	2.8		2.06	2.1		1.63	1.6		1.32	1.1		2.05	1.2		3.08	1.5		4.36	3.8		5.48	6.1		6.80	7.0	
166.40			165.63			164.86			164.09			163.31			162.54	P.C.		162.22	162.03		161.37			162.02	162.22		162.55	162.58		163.38	P.T.		164.36			166.13			167.11	N.T.30	
7.20	7.2		6.63	6.8		5.66	5.6		4.88	4.7		4.11	3.9		3.36	3.0		2.83	2.3		2.02	1.8		2.32	1.4		4.38	4.0		5.46	5.1		6.95	6.1		8.10	7.6	

Note's Drive | Mata's Drive | Mata's Drive | Mata's Drive | Mata's Drive | Mata's Drive

P I
200' V.C.
161.00

P I
El. 167.50
30' V.C.

-1543' @ 1/4% Wk. 0.8' | +2,575' @ 1/4% Wk. 0.8'

22ND

23RD

STREET

+37.9 Sanitary Manh. 33.2'E.
+48.8 DI C&W-32.5'E.
+33.9 MH 63'E.

E.J. Kendrick W.C.
E.E. Smith
Chief Clerk
Utilities Engineer

B. E. SMITH LICENSED 436 KANSAS PROFESSIONAL ENGINEER

CHAUTAUQUA

NL 22ND TO SL 23RD

26 - 2 - 30 A.C.

CITY OF WICHITA

B E SMITH CITY ENGINEER

SEPT 1953 PROJ. NO. C13-67