


Channel Properties											Classifications	
Bottom	Left	Right	Manning	Discharge	Critical	Uniform	Channel	Profile				
Width	Slope	Side Slope	n	Depth	Depth	Depth	Depth	Depth				
ft	ft	ft		ft	ft	ft	ft	ft				
30	0.0074	2	0.015	180	0.91	2.90	mid	M1				

Starting Point				
Station	Bottom	Flow	Depth	Direction
ft	Elevation	Depth	ft	ft
230	48.8	1.85	0.1	0.10

Depth	Area	Velocity	Specific	Wetted	Hydraulic	Ave	Delta	X	Bottom	Water
ft	ft ²	ft/s	Energy	Perimeter	Radius	Friction	ft	ft	Elevation	Surface
						Slope				Elevation
1.85	47.90	2.54	1.85	48.26	1.86	0.0175	0.0001	48.26	48.80	51.71
1.90	48.30	2.47	1.84	48.66	1.85	0.0175	0.0001	48.30	48.80	51.71
2.00	49.12	2.35	2.00	49.52	1.84	0.0175	0.0001	49.12	48.80	51.71
2.10	49.94	2.25	2.10	50.34	1.84	0.0175	0.0001	49.94	48.80	51.71
2.20	50.76	2.15	2.20	51.16	1.84	0.0175	0.0001	50.76	48.80	51.71
2.30	51.58	2.05	2.30	51.98	1.84	0.0175	0.0001	51.58	48.80	51.71
2.40	52.40	1.95	2.40	52.80	1.84	0.0175	0.0001	52.40	48.80	51.71
2.50	53.22	1.85	2.50	53.62	1.84	0.0175	0.0001	53.22	48.80	51.71
2.60	54.04	1.75	2.60	54.44	1.84	0.0175	0.0001	54.04	48.80	51.71
2.70	54.86	1.65	2.70	55.26	1.84	0.0175	0.0001	54.86	48.80	51.71
2.80	55.68	1.55	2.80	56.08	1.84	0.0175	0.0001	55.68	48.80	51.71
2.90	56.50	1.45	2.90	56.90	1.84	0.0175	0.0001	56.50	48.80	51.71
3.00	57.32	1.35	3.00	57.72	1.84	0.0175	0.0001	57.32	48.80	51.71
3.10	58.14	1.25	3.10	58.54	1.84	0.0175	0.0001	58.14	48.80	51.71
3.20	58.96	1.15	3.20	59.36	1.84	0.0175	0.0001	58.96	48.80	51.71
3.30	59.78	1.05	3.30	60.18	1.84	0.0175	0.0001	59.78	48.80	51.71
3.40	60.60	0.95	3.40	61.00	1.84	0.0175	0.0001	60.60	48.80	51.71
3.50	61.42	0.85	3.50	61.82	1.84	0.0175	0.0001	61.42	48.80	51.71
3.60	62.24	0.75	3.60	62.64	1.84	0.0175	0.0001	62.24	48.80	51.71
3.70	63.06	0.65	3.70	63.46	1.84	0.0175	0.0001	63.06	48.80	51.71
3.80	63.88	0.55	3.80	64.28	1.84	0.0175	0.0001	63.88	48.80	51.71
3.90	64.70	0.45	3.90	65.10	1.84	0.0175	0.0001	64.70	48.80	51.71
4.00	65.52	0.35	4.00	65.92	1.84	0.0175	0.0001	65.52	48.80	51.71
4.10	66.34	0.25	4.10	66.74	1.84	0.0175	0.0001	66.34	48.80	51.71
4.20	67.16	0.15	4.20	67.56	1.84	0.0175	0.0001	67.16	48.80	51.71
4.30	67.98	0.05	4.30	68.38	1.84	0.0175	0.0001	67.98	48.80	51.71
4.40	68.80	0.05	4.40	69.20	1.84	0.0175	0.0001	68.80	48.80	51.71
4.50	69.62	0.05	4.50	70.02	1.84	0.0175	0.0001	69.62	48.80	51.71
4.60	70.44	0.05	4.60	70.84	1.84	0.0175	0.0001	70.44	48.80	51.71
4.70	71.26	0.05	4.70	71.66	1.84	0.0175	0.0001	71.26	48.80	51.71
4.80	72.08	0.05	4.80	72.48	1.84	0.0175	0.0001	72.08	48.80	51.71
4.90	72.90	0.05	4.90	73.30	1.84	0.0175	0.0001	72.90	48.80	51.71
5.00	73.72	0.05	5.00	74.12	1.84	0.0175	0.0001	73.72	48.80	51.71
5.10	74.54	0.05	5.10	74.94	1.84	0.0175	0.0001	74.54	48.80	51.71
5.20	75.36	0.05	5.20	75.76	1.84	0.0175	0.0001	75.36	48.80	51.71
5.30	76.18	0.05	5.30	76.58	1.84	0.0175	0.0001	76.18	48.80	51.71
5.40	77.00	0.05	5.40	77.40	1.84	0.0175	0.0001	77.00	48.80	51.71
5.50	77.82	0.05	5.50	78.22	1.84	0.0175	0.0001	77.82	48.80	51.71
5.60	78.64	0.05	5.60	79.04	1.84	0.0175	0.0001	78.64	48.80	51.71
5.70	79.46	0.05	5.70	79.86	1.84	0.0175	0.0001	79.46	48.80	51.71
5.80	80.28	0.05	5.80	80.68	1.84	0.0175	0.0001	80.28	48.80	51.71
5.90	81.10	0.05	5.90	81.50	1.84	0.0175	0.0001	81.10	48.80	51.71
6.00	81.92	0.05	6.00	82.32	1.84	0.0175	0.0001	81.92	48.80	51.71
6.10	82.74	0.05	6.10	83.14	1.84	0.0175	0.0001	82.74	48.80	51.71
6.20	83.56	0.05	6.20	83.96	1.84	0.0175	0.0001	83.56	48.80	51.71
6.30	84.38	0.05	6.30	84.78	1.84	0.0175	0.0001	84.38	48.80	51.71
6.40	85.20	0.05	6.40	85.60	1.84	0.0175	0.0001	85.20	48.80	51.71
6.50	86.02	0.05	6.50	86.42	1.84	0.0175	0.0001	86.02	48.80	51.71
6.60	86.84	0.05	6.60	87.24	1.84	0.0175	0.0001	86.84	48.80	51.71
6.70	87.66	0.05	6.70	88.06	1.84	0.0175	0.0001	87.66	48.80	51.71
6.80	88.48	0.05	6.80	88.88	1.84	0.0175	0.0001	88.48	48.80	51.71
6.90	89.30	0.05	6.90	89.70	1.84	0.0175	0.0001	89.30	48.80	51.71
7.00	90.12	0.05	7.00	90.52	1.84	0.0175	0.0001	90.12	48.80	51.71
7.10	90.94	0.05	7.10	91.34	1.84	0.0175	0.0001	90.94	48.80	51.71
7.20	91.76	0.05	7.20	92.16	1.84	0.0175	0.0001	91.76	48.80	51.71
7.30	92.58	0.05	7.30	92.98	1.84	0.0175	0.0001	92.58	48.80	51.71
7.40	93.40	0.05	7.40	93.80	1.84	0.0175	0.0001	93.40	48.80	51.71
7.50	94.22	0.05	7.50	94.62	1.84	0.0175	0.0001	94.22	48.80	51.71
7.60	95.04	0.05	7.60	95.44	1.84	0.0175	0.0001	95.04	48.80	51.71
7.70	95.86	0.05	7.70	96.26	1.84	0.0175	0.0001	95.86	48.80	51.71
7.80	96.68	0.05	7.80	97.08	1.84	0.0175	0.0001	96.68	48.80	51.71
7.90	97.50	0.05	7.90	97.90	1.84	0.0175	0.0001	97.50	48.80	51.71
8.00	98.32	0.05	8.00	98.72	1.84	0.0175	0.0001	98.32	48.80	51.71
8.10	99.14	0.05	8.10	99.54	1.84	0.0175	0.0001	99.14	48.80	51.71
8.20	99.96	0.05	8.20	100.36	1.84	0.0175	0.0001	99.96	48.80	51.71
8.30	100.78	0.05	8.30	101.18	1.84	0.0175	0.0001	100.78	48.80	51.71
8.40	101.60	0.05	8.40	102.00	1.84	0.0175	0.0001	101.60	48.80	51.71
8.50	102.42	0.05	8.50	102.82	1.84	0.0175	0.0001	102.42	48.80	51.71
8.60	103.24	0.05	8.60	103.64	1.84	0.0175	0.0001	103.24	48.80	51.71
8.70	104.06	0.05	8.70	104.46	1.84	0.0175	0.0001	104.06	48.80	51.71
8.80	104.88	0.05	8.80	105.28	1.84	0.0175	0.0001	104.88	48.80	51.71
8.90	105.70	0.05	8.90	106.10	1.84	0.0175	0.0001	105.70	48.80	51.71
9.00	106.52	0.05	9.00	106.92	1.84	0.0175	0.0001	106.52	48.80	51.71
9.10	107.34	0.05	9.10	107.74	1.84	0.0175	0.0001	107.34	48.80	51.71
9.20	108.16	0.05	9.20	108.56	1.84	0.0175	0.0001	108.16	48.80	51.71
9.30	108.98	0.05	9.30	109.38	1.84	0.0175	0.0001	108.98	48.80	51.71
9.40	109.80	0.05	9.40	110.20	1.84	0.0175	0.0001	109.80	48.80	51.71
9.50	110.62	0.05	9.50	111.02	1.84	0.0175	0.0001	110.62	48.80	51.71
9.60	111.44	0.05	9.60	111.84	1.84	0.0175	0.0001	111.44	48.80	51.71
9.70	112.26	0.05	9.70	112.66	1.84	0.0175	0.0001	112.26	48.80	51.71
9.80	113.08	0.05	9.80	113.48	1.84	0.0175	0.0001	113.08	48.80	51.71
9.90	113.90	0.05	9.90	114.30	1.84	0.0175	0.0001	113.90	48.80	51.71
10.00	114.72	0.05	10.00	115.12	1.84	0.0175	0.0001	114.72	48.80	51.71



Wednesday, March 16, 1997

Channel Properties										Classifications	
Bottom Width	Bottom Slope	Left Side Slope	Right Side Slope	Manning Discharge	Discharge	Critical Depth	Uniform Depth	Channel Profile	Classification	Profile	
30	0.0074	2	2	0.015	180	0.91	2.90	mid	M1		

Starting Point				
Station	Bottom Elevation	Flow Depth	Flow Rate	Flow Direction
	ft	ft	cfs	ft
0	41	3	20	20.5

Depth	Area	Velocity	Specific Energy	Wetted Perimeter	Hydraulic Radius	Ave Friction Slope	Delta h	X	Bottom Elevation	Water Surface Elevation
2.00	48.80	1.85	1.85	48.26	1.86	0.0001	48.26	41.74	41.74	44.61
2.10	49.62	1.75	2.10	49.08	1.85	0.0001	49.08	41.74	41.74	44.61
2.20	50.44	1.65	2.20	49.90	1.84	0.0001	49.90	41.74	41.74	44.61
2.30	51.26	1.55	2.30	50.72	1.84	0.0001	50.72	41.74	41.74	44.61
2.40	52.08	1.45	2.40	51.54	1.84	0.0001	51.54	41.74	41.74	44.61
2.50	52.90	1.35	2.50	52.36	1.84	0.0001	52.36	41.74	41.74	44.61
2.60	53.72	1.25	2.60	53.18	1.84	0.0001	53.18	41.74	41.74	44.61
2.70	54.54	1.15	2.70	54.00	1.84	0.0001	54.00	41.74	41.74	44.61
2.80	55.36	1.05	2.80	54.82	1.84	0.0001	54.82	41.74	41.74	44.61
2.90	56.18	0.95	2.90	55.64	1.84	0.0001	55.64	41.74	41.74	44.61
3.00	57.00	0.85	3.00	56.46	1.84	0.0001	56.46	41.74	41.74	44.61
3.10	57.82	0.75	3.10	57.28	1.84	0.0001	57.28	41.74	41.74	44.61
3.20	58.64	0.65	3.20	58.10	1.84	0.0001	58.10	41.74	41.74	44.61
3.30	59.46	0.55	3.30	58.92	1.84	0.0001	58.92	41.74	41.74	44.61
3.40	60.28	0.45	3.40	59.74	1.84	0.0001	59.74	41.74	41.74	44.61
3.50	61.10	0.35	3.50	60.56	1.84	0.0001	60.56	41.74	41.74	44.61
3.60	61.92	0.25	3.60	61.38	1.84	0.0001	61.38	41.74	41.74	44.61
3.70	62.74	0.15	3.70	62.20	1.84	0.0001	62.20	41.74	41.74	44.61
3.80	63.56	0.05	3.80	63.02	1.84	0.0001	63.02	41.74	41.74	44.61
3.90	64.38	0.05	3.90	63.84	1.84	0.0001	63.84	41.74	41.74	44.61
4.00	65.20	0.05	4.00	64.66	1.84	0.0001	64.66	41.74	41.74	44.61
4.10	66.02	0.05	4.10	65.48	1.84	0.0001	65.48	41.74	41.74	44.61
4.20	66.84	0.05	4.20	66.30	1.84	0.0001	66.30	41.74	41.74	44.61
4.30	67.66	0.05	4.30	67.12	1.84	0.0001	67.12	41.74	41.74	44.61
4.40	68.48	0.05	4.40	67.94	1.84	0.0001	67.94	41.74	41.74	44.61
4.50	69.30	0.05	4.50	68.76	1.84	0.0001	68.76	41.74	41.74	44.61
4.60	70.12	0.05	4.60	69.58	1.84	0.0001	69.58	41.74	41.74	44.61
4.70	70.94	0.05	4.70	70.40	1.84	0.0001	70.40	41.74	41.74	44.61
4.80	71.76	0.05	4.80	71.22	1.84	0.0001	71.22	41.74	41.74	44.61
4.90	72.58	0.05	4.90	72.04	1.84	0.0001	72.04	41.74	41.74	44.61
5.00	73.40	0.05	5.00	72.86	1.84	0.0001	72.86	41.74	41.74	44.61
5.10	74.22	0.05	5.10	73.68	1.84	0.0001	73.68	41.74	41.74	44.61
5.20	75.04	0.05	5.20	74.50	1.84	0.0001	74.50	41.74	41.74	44.61
5.30	75.86	0.05	5.30	75.32	1.84	0.0001	75.32	41.74	41.74	44.61
5.40	76.68	0.05	5.40	76.14	1.84	0.0001	76.14	41.74	41.74	44.61
5.50	77.50	0.05	5.50	76.96	1.84	0.0001	76.96	41.74	41.74	44.61
5.60	78.32	0.05	5.60	77.78	1.84	0.0001	77.78	41.74	41.74	44.61
5.70	79.14	0.05	5.70	78.60	1.84	0.0001	78.60	41.74	41.74	44.61
5.80	79.96	0.05	5.80	79.42	1.84	0.0001	79.42	41.74	41.74	44.61
5.90	80.78	0.05	5.90	80.24	1.84	0.0001	80.24	41.74	41.74	44.61
6.00	81.60	0.05	6.00	81.06	1.84	0.0001	81.06	41.74	41.74	44.61
6.10	82.42	0.05	6.10	81.88	1.84	0.0001	81.88	41.74	41.74	44.61
6.20	83.24	0.05	6.20	82.70	1.84	0.0001	82.70	41.74	41.74	44.61
6.30	84.06	0.05	6.30	83.52	1.84	0.0001	83.52	41.74	41.74	44.61
6.40	84.88	0.05	6.40	84.34	1.84	0.0001	84.34	41.74	41.74	44.61
6.50	85.70	0.05	6.50	85.16	1.84	0.0001	85.16	41.74	41.74	44.61
6.60	86.52	0.05	6.60	85.98	1.84	0.0001	85.98	41.74	41.74	44.61
6.70	87.34	0.05	6.70	86.80	1.84	0.0001	86.80	41.74	41.74	44.61
6.80	88.16	0.05	6.80	87.62	1.84	0.0001	87.62	41.74	41.74	44.61
6.90	88.98	0.05	6.90	88.44	1.84	0.0001	88.44	41.74	41.74	44.61
7.00	89.80	0.05	7.00	89.26	1.84	0.0001	89.26	41.74	41.74	44.61
7.10	90.62	0.05	7.10	90.08	1.84	0.0001	90.08	41.74	41.74	44.61
7.20	91.44	0.05	7.20	90.90	1.84	0.0001	90.90	41.74	41.74	44.61
7.30	92.26	0.05	7.30	91.72	1.84	0.0001	91.72	41.74	41.74	44.61
7.40	93.08	0.05	7.40	92.54	1.84	0.0001	92.54	41.74	41.74	44.61
7.50	93.90	0.05	7.50	93.36	1.84	0.0001	93.36	41.74	41.74	44.61
7.60	94.72	0.05	7.60	94.18	1.84	0.0001	94.18	41.74	41.74	44.61
7.70	95.54	0.05	7.70	95.00	1.84	0.0001	95.00	41.74	41.74	44.61
7.80	96.36	0.05	7.80	95.82	1.84	0.0001	95.82	41.74	41.74	44.61
7.90	97.18	0.05	7.90	96.64	1.84	0.0001	96.64	41.74	41.74	44.61
8.00	98.00	0.05	8.00	97.46	1.84	0.0001	97.46	41.74	41.74	44.61
8.10	98.82	0.05	8.10	98.28	1.84	0.0001	98.28	41.74	41.74	44.61
8.20	99.64	0.05	8.20	99.10	1.84	0.0001	99.10	41.74	41.74	44.61
8.30	100.46	0.05	8.30	99.92	1.84	0.0001	99.92	41.74	41.74	44.61
8.40	101.28	0.05	8.40	100.74	1.84	0.0001	100.74	41.74	41.74	44.61
8.50	102.10	0.05	8.50	101.56	1.84	0.0001	101.56	41.74	41.74	44.61
8.60	102.92	0.05	8.60	102.38	1.84	0.0001	102.38	41.74	41.74	44.61
8.70	103.74	0.05	8.70	103.20	1.84	0.0001	103.20	41.74	41.74	44.61
8.80	104.56	0.05	8.80	104.02	1.84	0.0001	104.02	41.74	41.74	44.61
8.90	105.38	0.05	8.90	104.84	1.84	0.0001	104.84	41.74	41.74	44.61
9.00	106.20	0.05	9.00	105.66	1.84	0.0001	105.66	41.74	41.74	44.61
9.10	107.02	0.05	9.10	106.48	1.84	0.0001	106.48	41.74	41.74	44.61
9.20	107.84	0.05	9.20	107.30	1.84	0.0001	107.30	41.74	41.74	44.61
9.30	108.66	0.05	9.30	108.12	1.84	0.0001	108.12	41.74	41.74	44.61
9.40	109.48	0.05	9.40	108.94	1.84	0.0001	108.94	41.74	41.74	44.61
9.50	110.30	0.05	9.50	109.76	1.84	0.0001	109.76	41.74	41.74	44.61
9.60	111.12	0.05	9.60	110.58	1.84	0.0001	110.58	41.74	41.74	44.61
9.70	111.94	0.05	9.70	111.40	1.84	0.0001	111.40	41.74	41.74	44.61
9.80	112.76	0.05	9.80	112.22	1.84	0.0001	112.22	41.74	41.74	44.61
9.90	113.58	0.05	9.90	113.04	1.84	0.0001	113.04	41.74	41.74	44.61
10.00	114.40	0.05	10.00	113.86	1.84	0.0001	113.86	41.74	41.74	44.61


DRAINAGE PLAN

BRIDGEFIELD ADDITION

WICHITA, SEDGWICK COUNTY, KANSAS





OWNER:
SCOTT DEVELOPERS, LLC
ATTN: DON & PAT SCOTT
21 SCOTTSDALE
WICHITA, KS 67230

BENCHMARK:
CUT ON TRAFFIC SIGNAL POLE
SE CORNER 12TH AND CENTRAL
ELEV. = 1368.50 M.S.L.




Drainage Area	Area (acres)	Cs	Cm	Ts (min)	Tc (hr)	Qp (cfs)	Qm (cfs)	Qb (cfs)
1	3.2	0.42	0.72	15	3.83	7.37	5.1	17.0
2	1.9	0.42	0.72	15	3.83	7.37	3.1	10.1
3	1.1	0.42	0.72	15	3.83	7.37	1.8	5.8
4	0.8	0.42	0.72	15	3.83	7.37	1.2	4.2
5	4.2	0.42	0.72	15	3.83	7.37	6.8	22.3
6	0.9	0.42	0.72	15	3.83	7.37	1.4	4.8
7	4.9	0.42	0.72	15	3.83	7.37	7.9	26.0
8	8.2	0.42	0.72	15	3.83	7.37	10.0	32.9
9	0.7	0.42	0.72	15	3.83	7.37	3.7	1.1
10	5.1	0.42	0.72	15	3.83	7.37	8.2	27.1
11	2.2	0.42	0.72	15	3.83	7.37	3.5	11.7
12	1.2	0.42	0.72	15	3.83	7.37	1.9	6.4
13	1.3	0.42	0.72	15	3.83	7.37	2.1	6.9
14	1.2	0.42	0.72	15	3.83	7.37	1.9	6.4
15	0.6	0.42	0.72	15	3.83	7.37	1.0	3.2
16	0.5	0.42	0.72	15	3.83	7.37	0.8	2.7
17	7.0	0.42	0.72	15	3.83	7.37	11.3	37.1
18	0.9	0.42	0.72	15	3.83	7.37	1.4	4.8


LOT	BLOCK	M.S.L.	CITY DATUM
10/13	D	1355.0	167.6
9/14	D	1353.0	165.6
4/15	D	1351.0	163.6
3/16	D	1350.0	162.6
12/17	D	1348.0	160.6
18/19	D	1346.0	158.6
2/1	D	1345.0	157.6
1/2	B	1343.0	155.6
1	C	1341.0	153.6
6/2	C	1340.0	152.6




Note: Elevations shown on this Drainage Plan are in Mean Sea Level.
To Convert MSL to City Datum subtract 1197.4' from MSL.
The "Drainage Plan" being submitted herein is intended to serve as a guide for the design of streets and storm water sewer improvements. Modifications to structures, pipes, etc. may be necessary during the final design in order to obtain the most economical design and construction possible.



BENCHMARK:
"T" CUT ON TRAFFIC SIGNAL POLE
SE CORNER 127TH AND CENTRAL
ELEV. = 1368.50 M.S.L.



TYPICAL VIEW OUT
NO SCALE



TYPICAL WALK OUT
NO SCALE

NOTE:
Proposed top of foundation are shown on plans. Contractor to set finish floor elevation.
All street elevations shown on plans are for top of curb (full height).
View-out elevations are denoted as XXX V.O.
Walk-out elevations are denoted as XXX W.O.
Lots 1 & 2, Block B, shall have setbacks of 30' and 25' respectively in order to have viewouts.
Lot 3, Block D, shall have an extra deep foundation, the depth shall be determined when a layout is selected.

MINIMUM BUILDING PAD ELEVATIONS FOR LOWEST OPENING TO THE STRUCTURES			
LOT	BLOCK	M.S.L.	CITY DATUM
10,13	D	1358.0	170.5
9,14	D	1356.0	168.5
4,15	D	1354.0	166.6
3,16	D	1353.0	165.6
1,2,17	D	1351.0	163.6
18,19	D	1349.0	161.6
21	D	1348.0	160.6
17	B	1346.0	158.6
1	C	1346.0	158.6
5	C	1344.0	156.6
6,7	C	1343.0	155.6



APPROVED
DRAINAGE PLAN

BRIDGEFIELD ADDITION
GRADING PLAN
WICHITA, KS


BAUGHMAN COMPANY P.A.
ENGINEERING, SURVEYING, & PLANNING
316-222-7271 • 315 ELLIS • WICHITA, KANSAS 67201

PROJECT NUMBER
City of Wichita


DESIGN: SLP/JAB DRAWN: JAB APPROVED: DATE: 8/21/97 SCALE: 1" = 60' SHEET: 2 OF 2



BENCHMARK:
 CUT ON TRAFFIC SIGNAL POLE
 SE CORNER 12TH AND CENTRAL
 ELEV. = 1368.50 M.S.L.



TYPICAL VIEW OUT
 NO SCALE



TYPICAL WALK OUT
 NO SCALE

NOTE:
 Proposed top of foundation are shown on plans. Contractor to set finish floor elevation.
 All street elevations shown on plans are for top of curb (full height).
 View-out elevations are denoted as XX.X V.O.
 Walk-out elevations are denoted as XX.X W.O.

MINIMUM BUILDING PAD ELEVATIONS FOR LOWEST OPENING TO THE STRUCTURES			
LOT	BLOCK	ELEVATION	
		M.S.L.	CITY DATUM
10,13	D	1358.0	170.6
9,14	D	1356.0	168.6
4,15	D	1354.0	166.6
3,16	D	1353.0	165.6
12,17	D	1351.0	163.6
18,19	D	1349.0	161.6
21	D	1348.0	160.6
17	B	1346.0	158.6
1	C	1346.0	158.6
5	C	1344.0	156.6
6,7	C	1343.0	155.6

BRIDGEFIELD

GRADING PLAN

WICHITA, KS

BAUGHMAN COMPANY P.A.

ENGINEERING, SURVEYING, & PLANNING

315-262-2271 • 315 ELLIS • WICHITA, KANSAS 67211

PROJECT NUMBER

DATE 5/4/97

SCALE 1" = 60'

DESIGN: SLP/JAB

DRAWN: JAB

APPROVED: [Signature]

DATE: 5/4/97

SCALE: 1" = 60'

SHEET 2 OF 2