



STA. 0+97, 0' LT.  
INSTALL E.O.R. MARKERS

CONSTRUCT VALLEY GUTTER PAVEMENT.  
7" REINFORCED CONCRETE W/ 5"  
CRUSHED ROCK BASE AND MONOLITHIC  
EDGE CURB (3 5/8")

STA. 2+66, 29' LT.  
INSTALL SNS  
"Cherry Creek  
Cherry Creek Ct \_\_\_\_"

CONSTRUCT COMBINED ROLL  
TYPE CURB AND GUTTER  
(3 5/8") BOTH SIDES

PLACE CURLEX AND HAY BALE  
EROSION CONTROL AS INDICATED  
ON EROSION CONTROL PLAN.

CONSTRUCT 5" ASPHALT  
CONCRETE PAVEMENT W/ 5"  
CRUSHED ROCK BASE

CONSTRUCT 4' SIDEWALK  
(AE) (4") AS INDICATED.

P.V.I.  
ELEV. 1347.01  
No V.C.

<b>TARA CREEK ADDITION, PAVING IMPROVEMENTS CHERRY CREEK WICHITA, KANSAS</b>			
	<b>Ruggles &amp; Bohm, P.A.</b> Engineering, Surveying, Land Planning		DESIGN: CMB DRAWN: RA REVIEW: RA
	924 North Main Wichita, Kansas 67203 www.rbkansas.com		(316) 264-8008 (316) 264-4621 fax E-mail: info@rbkansas.com
DRAWING FILE: Cherry Creek 1	PROJECT NUMBER:	DATE: Nov. 19, 2007	SHEET: 4 OF 23