



Shield Size	Digits	Digit Series	A	A/2	B	C	D	E	F	G	H	I	J
30" x 24"	235	C	30"	15"	24"	2"	2 1/2"	1 1/2"	2 1/2"	10"	6"	9 1/2"	10"
45" x 36"	235	C	45"	22 1/2"	36"	3"	3 3/4"	3/4"	3 3/4"	15"	9"	14 1/8"	15"
24" x 24"			24"	12"	24"	2"	2 1/2"	1/2"	2 1/2"	12"	4"	9 1/2"	7 1/4"
36" x 36"			36"	18"	36"	3"	3 3/4"	3/4"	3 3/4"	18"	6"	14 1/8"	
60" x 48"	135	D	60"	30"	48"	4"	5"	1"	5"	20"	12"	19"	20"
60" x 48"	235	C	60"	30"	48"	4"	5"	1"	5"	20"	12"	19"	20"

Note:  
 Color Specifications (Reverse Screen Processing)  
 Sign face shall be covered with enclosed lens silver-reflective sheating.  
 Background for digits shall be transparent blue process ink.  
 Background for Interstate shall be transparent red process ink.

See flat sign detail sheets for aluminum alloys and thicknesses required.  
 The type of adhesive for reflective sheating may be solvent activated, heat activated or pressure sensitive.

3					
2					
1					
NO.	DATE	REVISIONS	BY	APP'D	
KANSAS DEPARTMENT OF TRANSPORTATION					
Design Details For					
2 3/3 Digit Interstate Route Marker					
(For Guide Signs)					
SHEET NO. 41 OF 143	SCALE	APP'D	QUANTITIES	TRACES	
DESIGNED BY	DETAILED BY	QUAN. CK.	TRACES		
DESIGN CK.	DETAIL CK.				