

DRIVEWAY CONCRETE PAVEMENT (6" UNIFORM)(AE) FOR ENTRANCES				
Station	Side	L (ft.)	W (ft.)	Quant. ft <sup>2</sup>
51+77.24	Lt.	5.6	22.0	321.80
52+10.96	Rt.	13.6	20.0	298.85
52+81.36	Lt.	22.5	24.0	556.35
53+29.00	Rt.	17.0	20.0	359.09
TOTAL				1,536.09

5" CRUSHED ROCK BASE ON FABRIC REINFORCEMENT			
Station	Side	Quant. (Sq. Ft.)	Quant. (Sq. Yds.)
50+10.23 to 53+90.56	℄	12,564.95	1,396.11
TOTAL			1,397

5" A.C. PAVEMENT WITH 3" BIT. BASE				
Station to Station	L (ft.)	W (ft.)	Quant. (Sq. Ft.)	Quant. (Sq. Yds.)
50+10.23 to 53+90.56	380.33	26	10,210.50	1,134.50
TOTAL				1,135

COMBINED ROLL TYPE CURB & GUTTER		
Station to Station	Side	Lin. Ft.
50+15.73 to 53+73.50	Lt.	59.11
50+14.30 to 53+73.50	Rt.	60.63
TOTAL		119.74

COMBINED CURB & GUTTER		
Station to Station	Side	Lin. Ft.
50+73.50 to 53+35.60	Lt.	262.10
50+73.50 to 53+43.00	Rt.	269.50
TOTAL		531.60

REMOVAL OF EXISTING STRUCTURES ■		
Station	Side	Description
52+10.96	Rt.	12"x24.5' RCP
53+29.00	Rt.	12"x29' RCP
53+58.30	℄	30"x18' MAC

■ FOR INFORMATION ONLY

REMOVAL OF EXISTING ASPHALT SURFACE		
Station to Station	Side	Quant. (Sq. Ft.)
53+35.38 to 53+90.56	℄	1,381.59
TOTAL		1,382

SLOPE DRAIN (SPECIAL) 6" CONCRETE GRADE 3.0 (AE)		
Station to Station	Side	Quant. (Sq. Ft.)
53+35.60 to 53+61.44	Lt.	146.3
53+43.00 to 53+65.24	Rt.	122.7
TOTAL		269.0

BACK OF CURB PROTECTION (EXCELSIOR BLANKET)		
Station to Station	Side	Quant. (Sq. Ft.)
50+10.93 to 51+66.14	Lt.	909.65
50+09.51 to 52+00.96	Rt.	1,040.84
51+88.34 to 52+69.36	Lt.	421.80
52+20.96 to 53+19.00	Rt.	503.85
52+93.36 to 53+60.44	Lt.	381.34
53+39.07 to 53+67.06	Rt.	169.86
53+37.61 to 53+88.68	Lt.	779.71
53+44.60 to 53+94.44	Rt.	727.41
TOTAL		4,934.46

RECAPITULATION OF QUANTITIES		
Item	Quant.	
Site Clearing & Restoration	1	L.S.
SWS Pipe Removed	72	L.F.
Removal of Exist. Asph. Surface	1,382	S.F.
Removal of Exist. Concrete	942	S.F.
Common Excavation	789	C.Y.
Embankment	67	C.Y.
5" Asphaltic Concrete Pavement (3" Bit. Base)	1,135	S.Y.
5" Crushed Rock Base on Fabric Reinforcement	1,397	S.Y.
Combined Roll Type Curb & Gutter	120	L.F.
Combined Curb & Gutter	532	L.F.
6" Uniform (AE) Concrete Pavement for Driveways	1,537	S.F.
6" Concrete Grade 3.0 (AE) for Slope Drains	269	S.F.
4" Concrete Sidewalk	176	S.F.
3.0 S.F. RCPHE	46	L.F.
3.0 S.F. End Section (Type 1)	2	EA.
Back of Curb Protection (Excelsior Blanket)	4,935	S.F.
Seeding	1	L.S.

4" CONCRETE SIDEWALK (4' WIDE)		
Station to Station	Side	Quant. (Sq. Ft.)
51+62.24 to 51+66.24	Lt.	16.00
51+88.24 to 51+92.24	Lt.	15.84
51+96.96 to 52+00.96	Rt.	15.82
52+20.96 to 52+24.96	Rt.	15.78
52+57.36 to 52+69.36	Lt.	48.00
52+93.37 to 53+05.37	Lt.	48.00
53+15.00 to 53+19.00	Rt.	16.00
TOTAL		175.44

REMOVAL OF EXISTING CONCRETE		
Station	Side	Quant. (Sq. Ft.)
52+10.96	Rt.	191.61
52+81.36	Lt.	504.09
53+29.00	Rt.	246.00
TOTAL		941.70

EARTHWORK					
Station to Station	Excavation		Contractor Furnished		Embankment cu yd
	Common	Rock	cu yd	V.M.F.	
	cu yd	V.M.F.	cu yd	V.M.F.	95% density
50+10.23 to 53+90.56	789				67
TOTAL		789			67

REVISED

SEAL:



**Cook, Flatt & Strobel**  
ENGINEERS, P.A.  
**CFS**

CFS PROJECT NO:  
08-509

CITY OF WICHITA, KANSAS

**AGNES STREET**

WEST 36TH ST. NORTH TO WEST 37TH ST. NORTH

DATE: Aug. 2008 DESIGNED BY: KKH DRAWN BY: BMG CHECKED BY: JWB

SHEET TITLE:

**SUMMARY  
OF  
QUANTITIES**

PROJECT NUMBER  
472-84610

**OFFICE  
CHECK**

SHEET NUMBER:

**6 of 17**