

FHWA REGION NO.	STATE	PROJECT NUMBER	FISCAL YEAR	SHEET NUMBER	TOTAL SHEETS
7	KANSAS	87N-0385-01	2006	2	43

- Underground utility service lines and overhead utility pole lines are to be adjusted by utility companies if necessary prior to construction unless the plans specifically call for their adjustment by the Contractor. Existing utilities and their location, as shown on the plans, represent the best information obtainable for design. The Contractor will be required to work around existing utilities within the right-of-way which do not conflict with proposed construction.
- Rubble from the removal of miscellaneous structures and excess excavation which is to be wasted shall be disposed of on sites to be provided by the Contractor. These sites shall be approved by the Engineer as to suitability, appearance and site location. Locations that, in the opinion of the Engineer, will leave an unsightly appearance will not be approved.
- All disposal sites must be approved by the Kansas Department of Health and Environment. Material either stockpiled or disposed of in a flood plain would require a Kansas State Board of Agricultural permit. Any material dumped in waters of the United States or wetlands is subject to U.S Corps of Engineers permitting regulations. Any material buried or stockpiled beyond approved construction limits would require additional archaeological investigations unless buried in a previously approved borrow location.
- The Contractor shall give all property owners and/or tenants of developed property abutting the construction of this project a minimum of ten (10) days notice prior to start of construction and again 48 hours prior to any work actually starting.
- The Contractor shall be responsible for preserving shown property irons. The Contractor will be required to reestablish any shown property irons which are disturbed by his construction operations. Such irons shall be reestablished by a licensed Land Surveyor in accordance with state laws.
- Contractor is required to provide a minimum notice of forty-eight (48) hours to utility companies prior to starting any excavation as follows:  
  

Kansas One-Call	687-2470
-----------------	----------


The Contractor must notify the following before construction and in case of an emergency.

Cox Communications	262-0661
Kansas Gas Service	1-888-482-4950
Westar	383-8600
Aquila Net (UtiliCorp United)	1-800-303-0357
Southwestern Bell Telephone Company	1-800-870-8390
City of Wichita Water Department	262-6000
City of Wichita Sewer Maintenance	268-4071
- Provide a full depth saw cut at locations where proposed construction abuts an existing surface course or pavement for which partial removal of that surface or pavement is required. Sawed joints to facilitate removal within three (3) feet of the existing joint will not be permitted and for such instances the limits of removal shall extend to the existing joint. Such saw cuts will not be paid for directly and this cost shall be considered as subsidiary to the removal of the surface or pavement.
- All salvageable drainage pipes, manhole rings and covers, inlet grates, street signs, traffic poles and any other salvageable items shall be transported to the appropriate City yards for stockpile. Delivery of the items shall be paid through bid item "Transportation of Salvageable Materials".
- Connection of proposed storm sewer inlet to existing storm sewer and the removal of the existing structure shall be Subsidiary to new inlet structures.

- Contractor shall maintain two-way traffic during the project for the entire length of the project. Traffic control shall be bid as lump sum per the bid item "Traffic Control".
- Manhole adjustments shall conform to City of Wichita Standard Specifications and shall be considered subsidiary to other items of work.
- Pavement shall be sawed, removed and replaced as necessary for storm sewer construction, inlet removal, and manhole adjustment, except in areas indicated on plans where pavement is to be removed and reconstructed. All such work shall be incidental to the bid item for reinforced concrete pavement.
- All areas disturbed by construction shall be restored with sod to match existing turf type. The estimated quantity of sod is 1000 sq. yds. Restoration of disturbed areas shall include, but not limited to, top soil preparation and sodding. All sodding work shall be in accordance with City Standard Specifications and the City Administrative Regulation No. AR78, which governs cleanup and restoration or replacement following construction. The "Recapitulation of Quantities" shows the estimated Square Yards of sodding, with a bid item for the same. When the weather/season prevents the installation of sod, the Contractor shall be responsible for the installing Erosion Control Blanket (Curlax I, or approved equal) at the back of curb (8' wide minimum). All costs for erosion mat installation shall be SUBSIDIARY to "Site Clearing and Restoration".
- DELETED
- PAVEMENT MARKINGS - All pavement markings shall be thermoplastic. Pavement markings shall be installed per manufacturer's recommendations and shall meet KDOT's Special Provision to the Standard Specifications 90P-294. Full traffic may not be restored (and substantial project completion achieved) until all pavement markings are in place. Should construction timing be such that restoration of traffic becomes necessary during temperatures prohibiting the installation of thermoplastic markings, the contractor shall install and maintain temporary markings until such time that thermoplastic markings may be properly installed. Except for the material requirement, temporary pavement markings shall be placed equivalent, in every manner (i.e. dimension, frequency, spacing, etc.), to the permanent marking layout. The cost for temporary pavement markings will not be paid for directly, but shall be considered subsidiary to the bid items for "Pavement Markings".
- The joints in existing and new concrete pavements to be overlaid shall be cleaned and re-sealed with Crafcro 34201 joint sealant or approved equivalent in conformance with the City of Wichita Standard Specifications. The installed sealant should be recessed 1/8" below the concrete surface. Contractor shall be careful to avoid contact of the sealant with the concrete surface. If such contact occurs, the sealant shall be completely removed. Spreading-out excess sealant across the pavement surface (to squeegee) will not be allowed.

UTILITY CONTRACTOR LIST

- Westar  
1900 East Central  
P.O. Box 208  
Wichita, KS 67202  
316-261-6251  
Contact: Jim Horton
- Kansas Gas Service  
1021 East 26th Street North  
P.O. Box 208  
Wichita, KS 67202  
316-832-3126  
Contact: Jim Coe
- Aquila Net (UtiliCorp United)  
1611 S. Hoover  
Wichita, KS 67209  
316-941-1608  
Contact: Calvin Briggs
- Cox Communications  
701 East Douglas  
Wichita, KS 67202  
316-262-4270  
Contact: Marc Henderson
- Southwestern Bell Telephone Co.  
154 North Broadway  
Wichita, KS 67202  
316-268-2759  
Contact: Jim Toben
- Stormwater Utility  
City of Wichita  
City Hall - 7th Floor  
455 North Main  
Wichita, KS 67202  
316-268-4545  
Contact: Scott Lindebak
- Dept. of Water & Sewer  
City of Wichita  
City Hall - 8th Floor  
455 North Main  
Wichita, KS 67202  
316-268-4555  
Contacts: LaDonna Lawrenz (Sewer)  
Bill Perkins (Water)
- Traffic Engineering  
City of Wichita  
City Hall - 7th Floor  
455 North Main  
Wichita, KS 67202  
316-268-4446  
Contact: Julianne Kallman
- Sedgwick County Emergency  
Management Agency  
535 N. Main, Suite B10  
Wichita, KS 67203-3702  
316-383-7546  
Contact: Jack Kegley

Pawnee and McLean Improvements GENERAL NOTES WICHITA, KANSAS			
	<b>Ruggles &amp; Bohm, P.A.</b> Engineering, Surveying, Land Planning	DESIGN: PDC DRAWN: PDC REVIEW: 6/25/06 UTILITY:	SHEET <b>2</b> OF <b>43</b>
	924 North Main Wichita, Kansas 67203 www.rbkansas.com	(316) 264-8008 (316) 264-4621 fax E-mail: info@rbkansas.com	DRAWING FILE: General Notes PROJECT NUMBER: 472-84007 DATE: July 23, 2005