



WICHITA, KANSAS

ADDENDUM NO. 2
TO THE PROPOSAL FB060164

2010 Contract Maintenance Concrete Repairs, Ph 2
(north of 63rd Street South, east of 135th Street West)

472-84930

TO BE BID: August 27, 2010

The following changes and additions shall be made to the plans and proposal.

- 1. In Bid Proposal Item #8, "Work on Project", paragraph 9 should read as follows:

Concrete Pavement Repair shall be reinforced with 6 X 12, W4 X W4 welded wire mesh for residential and collectors. Material for sealing joints in the new pavement shall be Crafco Road Saver #205 or pre-approved equal. Where existing reinforced steel cannot be saved, **No. 4 rebars 2'0" long on 30" centers with a minimum of 2 bars in any patch side shall be drilled and epoxyed into existing concrete.** The Epoxy shall be Simpson SET High Strength or equivalent. **Hammering rebars into concrete is not allowed. The cost of all the necessary work to complete the repair work such as full depth saw cut, removal and replacement is subsidiary to that particular repair bid items.** Monolithic edge curb required shall match existing curb as closely as possible. All costs for removal and construction of monolithic edge curb will be included in the price bid for that item. **All concrete pavement repairs, regardless of location, require full-depth saw cuts. All saw cutting, removal & other work to complete the concrete repair work will be considered subsidiary to concrete base repair bid item.**

Each bidder is required to acknowledge receipt of this Addendum by his signature affixed hereto and to file same with and attached to his bid. Any Bid Proposal that is returned without all addenda signed and included in the Proposal shall be considered an invalid Proposal.

August 25, 2010

Jim Armour, P.E.
City Engineer

Date _____

Signature of Bidder

BIDDER: _____
(print or type name of firm)

ADDRESS: _____

AUTHORIZED AGENT: _____
