

| SCHEDULE OF INLETS AND MANHOLES | | | | | | | | | | | | | | | | | | |
|---------------------------------|-----------|----------------|-------------|---------------|--------------|------------|--------------|---------|--------------|----------------------|-------|-----|-----|--------|-----|-----|--------|-------|
| STATION | SIDE | STRUCTURE TYPE | | | | SEWER DATA | | | ELEV. TOP | STORM SEWER LIN. FT. | | | | | | | | |
| | | MAN-HOLE | GRATE INLET | TYPE 12 INLET | TYPE 1 INLET | MISC. | OUTFLOW PIPE | | | 18" | 24" | 30" | 36" | 42" | 48" | 54" | 60" | |
| | | | | | | | SIZE | ELEV. | | | | | | | | | | GRADE |
| MAINLINE | | | | | | | | | | | | | | | | | | |
| 1 | 659+90.19 | Rt. | | | | 48" HW | 48" | 1314.00 | | | | | | | | | O.F. | |
| 2 | 658+81.89 | Rt. | | 1S | | Stack | 48" | 1314.20 | 0.18% | 1325.03 | | | | | | | 110.27 | |
| 3 | 658+81.89 | Lt. | 1 | | | | 48" | 1314.30 | 0.15% | 1326.29 | | | | | | | 74.91 | |
| 4 | 658+81.89 | Lt. | | 1 | | | 18" | 1314.47 | 0.32% | 1325.14 | 54.69 | | | | | | | |
| 5 | 657+77.31 | Lt. | 1 | | | | 48" | 1314.50 | 0.15% | 1326.07 | | | | | | | 104.55 | |
| 6 | 657+77.31 | Lt. | | 1 | | | 18" | 1321.42 | 0.32% | 1324.92 | 54.72 | | | | | | | |
| 7 | 657+77.31 | Rt. | | 1 | | | 18" | 1321.28 | 0.32% | 1324.78 | 74.89 | | | | | | | |
| 8 | 657+36.88 | Lt. | 1 | | | | 42" | 1315.10 | 0.22% | 1326.06 | | | | 40.38 | | | | |
| 9 | 657+36.89 | Lt. | | 1 | | | 18" | 1321.40 | 0.32% | 1324.90 | 54.59 | | | | | | | |
| 10 | 657+36.88 | Rt. | | 1 | | | 18" | 1321.26 | 0.32% | 1324.76 | 75.01 | | | | | | | |
| 11 | 656+52.19 | Lt. | 1 | | | | 42" | 1315.20 | 0.22% | 1326.13 | | | | 84.68 | | | | |
| 12 | 656+52.19 | Lt. | | 1 | | | 18" | 1321.49 | 0.32% | 1324.99 | 54.63 | | | | | | | |
| 13 | 656+52.19 | Rt. | | 1 | | | 18" | 1320.77 | 0.32% | 1324.27 | 75.05 | | | | | | | |
| 14 | 654+50.74 | Lt. | 1 | | | | 42" | 1315.60 | 0.17% | 1326.97 | | | | 201.45 | | | | |
| 15 | 654+50.74 | Lt. | | 1 | | | 18" | 1322.33 | 0.32% | 1325.83 | 54.62 | | | | | | | |
| 16 | 654+50.96 | Rt. | | 1 | | | 18" | 1321.50 | 0.32% | 1325.00 | 90.07 | | | | | | | |
| 17 | 652+27.40 | Lt. | 1 | | | | 36" | 1316.80 | 0.30% | 1328.97 | | | | 223.34 | | | | |
| 18 | 652+27.40 | Lt. | | 1 | | | 18" | 1324.32 | 0.32% | 1327.82 | 54.62 | | | | | | | |
| 19 | 650+77.39 | Lt. | 1 | | | | 36" | 1317.20 | 0.27% | 1330.94 | | | | 150.00 | | | | |
| 20 | 650+77.39 | Lt. | | 1 | | | 18" | 1326.29 | 0.32% | 1329.79 | 54.62 | | | | | | | |
| 21 | 648+52.92 | Lt. | 1 | | | | 36" | 1317.70 | 0.22% | 1334.31 | | | | 224.47 | | | | |
| 22 | 648+52.92 | Lt. | | 1 | | | 18" | 1329.66 | 0.32% | 1333.16 | 54.62 | | | | | | | |
| 23 | 646+03.52 | Lt. | 1 | | | | 36" | 1318.20 | 0.19% | 1338.05 | | | | 249.40 | | | | |
| 24 | 646+03.52 | Lt. | | 1 | | | 18" | 1333.40 | 0.32% | 1336.90 | 54.62 | | | | | | | |
| 25 | 644+02.92 | Lt. | 1 | | | | 36" | 1318.50 | 0.14% | 1341.06 | | | | 200.60 | | | | |
| 26 | 644+02.92 | Lt. | | 1 | | | 18" | 1336.41 | 0.32% | 1339.91 | 54.62 | | | | | | | |
| 27 | 643+02.96 | Lt. | 1 | | | | 36" | 1318.60 | 0.10% | 1342.56 | | | | 99.97 | | | | |
| 28 | 643+02.96 | Lt. | | 1 | | | 18" | 1337.91 | 0.32% | 1341.41 | 54.62 | | | | | | | |
| 29 | 640+78.52 | Lt. | 1 | | | | 30" | 1328.29 | 4.10% | 1345.93 | | | | 224.43 | | | | |
| 30 | 640+78.52 | Lt. | | 1 | | | 18" | 1341.28 | 0.32% | 1344.78 | 54.62 | | | | | | | |
| 31 | 639+52.92 | Lt. | 1 | | | | 30" | 1333.71 | 4.31% | 1347.81 | | | | 125.60 | | | | |
| 32 | 639+52.92 | Lt. | | 1 | | | 18" | 1343.16 | 0.32% | 1346.66 | 54.59 | | | | | | | |
| 33 | 638+02.93 | Lt. | 1 | | | | 30" | 1340.18 | 4.31% | 1350.06 | | | | 150.00 | | | | |
| 34 | 638+02.93 | Lt. | | 1 | | | 18" | 1345.41 | 0.32% | 1348.91 | 54.59 | | | | | | | |
| 35 | 636+52.92 | Lt. | 1 | | | | 30" | 1346.66 | 4.32% | 1352.31 | | | | 150.00 | | | | |
| 36 | 636+52.92 | Lt. | | 1 | | | 18" | 1347.66 | 0.32% | 1351.16 | 54.66 | | | | | | | |
| 37 | 635+02.92 | Lt. | 1 | | | | 24" | 1349.41 | 1.50% | 1354.56 | | | | 150.00 | | | | |
| 38 | 635+02.92 | Lt. | | 1 | | | 18" | 1349.91 | 0.32% | 1353.41 | 54.66 | | | | | | | |
| 39 | 633+52.40 | Lt. | 1 | | | | 24" | 1351.67 | 1.50% | 1356.82 | | | | 150.52 | | | | |
| 40 | 633+52.40 | Lt. | | 1 | | | 18" | 1352.17 | 0.32% | 1355.67 | 54.62 | | | | | | | |
| 41 | 632+02.40 | Lt. | 1 | | | | 24" | 1353.92 | 1.50% | 1359.07 | | | | 150.00 | | | | |
| 42 | 632+02.40 | Lt. | | 1 | | | 18" | 1354.42 | 0.32% | 1357.92 | 54.62 | | | | | | | |
| 43 | 660+89.70 | Rt. | | | | 42" HW | 42" | 1314.00 | | | | | | | | | O.F. | |
| 44 | 661+50.52 | Rt. | | 1 | | | 42" | 1318.71 | 7.58% | 1326.71 | | | | 62.13 | | | | |
| 45 | 661+50.52 | Rt. | 1 | | | | 42" | 1318.79 | 0.12% | 1327.98 | | | | 62.70 | | | | |
| 46 | 661+50.52 | Lt. | | 1 | | | 18" | 1323.34 | 0.32% | 1326.84 | 66.90 | | | | | | | |
| 47 | 662+49.92 | Rt. | 1 | | | | 42" | 1319.98 | 1.19% | 1329.02 | | | | 99.43 | | | | |
| 48 | 662+49.90 | Lt. | | 1 | | | 18" | 1324.39 | 0.32% | 1327.89 | 66.92 | | | | | | | |
| 49 | 662+49.93 | Rt. | | 1 | | | 18" | 1324.23 | 0.32% | 1327.73 | 62.70 | | | | | | | |
| 50 | 663+49.88 | Rt. | 1 | | | | 42" | 1321.18 | 1.20% | 1330.22 | | | | 100.00 | | | | |
| 51 | 663+50.52 | Lt. | | 1 | | | 18" | 1325.64 | 0.32% | 1329.14 | 66.23 | | | | | | | |
| 52 | 663+49.30 | Rt. | | 1 | | | 18" | 1325.48 | 0.32% | 1328.98 | 59.46 | | | | | | | |
| 53 | 664+49.87 | Rt. | 1 | | | | 42" | 1322.38 | 1.20% | 1331.41 | | | | 100.00 | | | | |
| 54 | 664+51.04 | Lt. | | 1 | | | 18" | 1326.85 | 0.32% | 1330.35 | 66.62 | | | | | | | |
| 55 | 664+49.22 | Rt. | | 1 | | | 18" | 1326.76 | 0.32% | 1330.26 | 53.33 | | | | | | | |
| 56 | 665+49.91 | Rt. | 1 | | | | 36" | 1324.08 | 1.20% | 1332.61 | | | | 100.00 | | | | |
| 57 | 665+49.66 | Rt. | | 1 | | | 18" | 1327.97 | 0.32% | 1331.47 | 54.57 | | | | | | | |
| 58 | 666+49.94 | Rt. | 1 | | | | 36" | 1325.28 | 1.20% | 1333.81 | | | | 100.00 | | | | |
| 59 | 666+49.94 | Rt. | | 1 | | | 18" | 1329.16 | 0.32% | 1332.66 | 54.55 | | | | | | | |
| 60 | 667+62.51 | Rt. | 1 | | | | 36" | 1326.53 | 1.11% | 1335.16 | | | | 100.00 | | | | |
| 61 | 667+60.62 | Lt. | | 1 | | | 18" | 1330.01 | 0.32% | 1333.51 | 94.06 | | | | | | | |
| 62 | 667+62.89 | Rt. | | 1 | | | 18" | 1330.52 | 0.32% | 1334.02 | 54.57 | | | | | | | |
| 63 | 668+62.55 | Rt. | 1 | | | | 36" | 1327.73 | 1.20% | 1336.36 | | | | 100.00 | | | | |
| 64 | 668+60.02 | Lt. | | 1 | | | 18" | 1331.26 | 0.32% | 1334.76 | 90.98 | | | | | | | |
| 65 | 668+63.32 | Rt. | | 1 | | | 18" | 1331.72 | 0.32% | 1335.22 | 54.56 | | | | | | | |
| 66 | 669+62.58 | Rt. | 1 | | | | 36" | 1328.93 | 1.20% | 1337.57 | | | | 100.00 | | | | |
| 67 | 669+64.24 | Lt. | | 1 | | | 18" | 1332.49 | 0.32% | 1335.99 | 89.97 | | | | | | | |
| 68 | 669+62.59 | Rt. | | 1 | | | 18" | 1332.91 | 0.32% | 1336.41 | 55.00 | | | | | | | |
| 69 | 670+62.62 | Rt. | 1 | | | | 36" | 1330.13 | 1.20% | 1338.77 | | | | 100.00 | | | | |
| 70 | 670+63.73 | Lt. | | 1 | | | 18" | 1333.72 | 0.32% | 1337.22 | 88.42 | | | | | | | |
| 71 | 670+62.61 | Rt. | | 1 | | | 18" | 1334.11 | 0.32% | 1337.61 | 54.54 | | | | | | | |
| 72 | 671+62.66 | Rt. | 1 | | | | 30" | 1331.83 | 1.20% | 1339.97 | | | | 100.00 | | | | |
| 73 | 671+63.25 | Lt. | | 1 | | | 18" | 1334.94 | 0.32% | 1338.44 | 87.44 | | | | | | | |
| 74 | 671+62.66 | Rt. | | 1 | | | 18" | 1335.31 | 0.32% | 1338.81 | 54.54 | | | | | | | |
| 75 | 672+53.43 | Rt. | 1 | | | | 30" | 1332.92 | 1.20% | 1341.06 | | | | 90.74 | | | | |

| SCHEDULE OF INLETS AND MANHOLES | | | | | | | | | | | | | | | | | | |
|---------------------------------|-----------|----------------|-------------|---------------|--------------|------------|--------------|---------|--------------|----------------------|-------|-----|-----|-----|-----|-----|-----|-------|
| STATION | SIDE | STRUCTURE TYPE | | | | SEWER DATA | | | ELEV. TOP | STORM SEWER LIN. FT. | | | | | | | | |
| | | MAN-HOLE | GRATE INLET | TYPE 12 INLET | TYPE 1 INLET | MISC. | OUTFLOW PIPE | | | 18" | 24" | 30" | 36" | 42" | 48" | 54" | 60" | |
| | | | | | | | SIZE | ELEV. | | | | | | | | | | GRADE |
| MAINLINE | | | | | | | | | | | | | | | | | | |
| 76 | 672+53.43 | Lt. | | 1 | | | 18" | 1336.02 | 0.32% | 1339.52 | 87.07 | | | | | | | |
| 77 | 672+53.43 | Rt. | | 1 | | | 18" | 1336.40 | 0.32% | 1339.90 | 54.54 | | | | | | | |
| 78 | 673+53.44 | Rt. | 1 | | | | | | | | | | | | | | | |