

**BENCHMARK**  
 1 Top of curb, north return, Northwest corner of 43rd and Hydraulic.  
 Elev. = 82.33  
 Small Railroad Spike in West face of Power Pole, East of 44th and Hydraulic.  
 Elev. = 82.84  
 Railroad Spike in Light Pole, Southwest corner of 45th and Victoria.  
 Elev. = 84.74

SCALE: 1" = 60'  
 • = IRON

- NOTES:**
1. PAVING CONTRACTOR SHALL MAKE SURE ALL EROSION CONTROL IS IN PLACE BEFORE PROJECT IS ACCEPTED. THIS PLAN REPRESENTS THE MINIMUM STANDARD. ANY ADDITIONAL EROSION CONTROL MEASURES SHALL BE INSTALLED BY THE PAVING CONTRACTOR AS NEEDED. ALL COST ASSOCIATED WITH EROSION CONTROL BMP'S SHALL BE INCIDENTAL TO BID ITEM "EROSION CONTROL BMP'S".
  2. This Plan is *Not* To Be Used As A Comprehensive Grading Plan. All Spot Elevations Are Proposed & Subject To Change.
  3. Each Lot Area Disturbed By Construction Shall Be the Responsibility of Each Individual Homeowner. Owner Responsible to Follow All SWPP Plans & Guidelines For The Area.
  4. Install 8" Wide Dimple/Excelsior Blanket, or Approved Equal, on Prepared Surface Back of Curb. Edge of Blanket Will Be At Back of Curb.
  5. All Seeding Shall Be Done During Spring or Fall Planting Seasons. Fall Seeding Shall Be September 1 thru Mid October. Spring Seeding Shall Be From March 15 thru Mid May.

All areas disturbed during construction within Reserves and Street R/W's shall be seeded, mulched, and fertilized as follows unless otherwise noted (Permanent Seeding):





Seed: Kansas Premium Fescue Blend: 8 lbs./1000 sq. ft.  
 Mulch: Prairie Hay: 2 tons/acre  
 Fertilizer: 12-24-12: 800 lbs./acre

All other areas disturbed during construction shall be seeded and mulched as follows (Temporary Seeding):



Seed: Rye Grass: 5 lbs./1000 Sq. Ft.  
 Mulch: Prairie Hay: 2 tons/acre

All costs associated with seeding, mulching, and fertilizing shall be included in bid item "Project Seeding." All seeding operations shall conform to City of Wichita Standard Specifications.

**EROSION CONTROL PLAN LEGEND**  
 (Installation Details Found in the SWPP Plans)

-  - DROP INLET PROTECTION
-  - CURB INLET PROTECTION
-  - STRAW BALE BARRIERS
-  - SILT FENCING

NO SCALE

		Hidden Glen Addition Erosion Control Plan Street Paving	
		<small>Baughman Company, P.A., 21510 W. 10th St., Suite 100, Overland Park, KS 66213        (913) 641-1100   FAX (913) 641-1101   WWW.BAUGHMANPAVING.COM</small>	
<b>PROJECT NUMBER</b> 472-83825	<b>DATE</b> MM/SS 07/04	<b>APPROVED</b> 	<b>DATE</b> 07/04
<b>REVISIONS</b>	<b>NOTED</b> Noted	<b>REVISION</b>	<b>DATE</b>
		9B of 19	

