



- LEGEND**
- Channelizing Device at 60' Spacing unless otherwise Noted.
 - × Tubular Marker at 20' Spacing
 - ▲ Traffic Control Sign
 - ||||| Type III Barricades
 - ◇ 18"x18" Fluorescent Red-Orange Flags
 - Red Type "B" High Intensity Warning Light
 - ▨ Temporary Pavement for Detours
 - Direction of Traffic

Note: Signs and barricades are shown diagrammatically only. Contractor will be responsible to install the required number of posts to support the installation.

Note: Utilities are not shown on Traffic Control Plans. The Contractor is responsible for verification as to type and location of underground utilities as may be necessary to avoid damage thereto. The Contractor is responsible for repairing any damage to underground utilities.

① Place channelizing devices as necessary during construction to restrict access to work area.

Construct Temporary Pavement See Sh. No. 118 for Typical Section

Plotted By: svb Date: 8/5/2013 11:59:56 AM
 FILE: I:\2008\0820\Traffic Control\08207-TC Stage IB 95.dgn

No.	Revision	By	Date
37TH STREET NORTH			
TRAFFIC CONTROL PLAN			
STAGE IB - STA. 95+00 TO STA. 107+00			
GARY JANZEN, P.E.-CITY ENGINEER			
CITY OF WICHITA PROJECT NO. 472-84692			
<small>PROFESSIONAL ENGINEERING CONSULTANTS, P.A. 303 SOUTH TOPEKA WICHITA, KS 67202 316-262-2691 www.pec1.com</small>			
Designed by	JPS	Job No.	08207
Drawn by	SVB	Date	August, 2013
			Sht. 121 of 193