

CURB AND GUTTER (MEASURED QTY.)				
LOCATION	STATION TO STATION	SIDE	TYPE 1 (L.F.)	TYPE 3 (L.F.)
Hillside	48+07.00	Lt.	11.30	9.10
Hillside	48+07.00	Rt.	9.71	9.00
Hillside	48+70.30	Lt.	8.00	
Hillside	48+70.30	Rt.	8.00	
Hillside	51+21.15	Rt.	10.00	
Hillside	51+22.50	Lt.	8.00	
Hillside	51+95.00	Lt.	9.60	9.00
Hillside	51+95.00	Rt.	12.70	9.00
Oliver	44+64.00	CLN		374.38
Oliver	47+99.00	Lt.	9.56	9.00
Oliver	47+99.00	Rt.	9.37	
Oliver	48+70.00	Rt.	8.00	
Oliver	48+70.20	Lt.	8.00	
Oliver	51+21.00	Rt.	8.00	
Oliver	51+21.50	Lt.	8.00	
Oliver	51+95.00	Lt.	9.52	9.00
Oliver	51+95.00	Rt.	10.18	9.00
Totals			147.94	437.48

4" SIDEWALK PAVEMENT (MEASURED QTY.)				
LOCATION	STATION TO STATION	SIDE	WIDTH (FT.)	QUANTITY (S.F.)
Hillside	48+07.00	Lt.	6	45.89
Hillside	48+07.00	Rt.	6	6.89
Hillside	51+87.90	Lt.	4	149.82
Hillside	51+95.00	Rt.	6	28.91
Oliver	47+99.00	Lt.	6	97.51
Oliver	47+99.00	Rt.	6	84.45
Oliver	51+95.00	Lt.	6	42.82
Oliver	51+95.00	Rt.	6	66.03
Totals				522.32

WHEELCHAIR RAMPS				
LOCATION	STATION	SIDE	WIDTH (FT.)	QUANTITY (EACH)
Hillside	48+07.00	Lt.	6	1
Hillside	48+07.00	Rt.	6	1
Hillside	48+12.50	Lt.	4	1
Hillside	48+17.00	Rt.	4	1
Hillside	48+66.00	Rt.	5	1
Hillside	48+67.00	Lt.	5	1
Hillside	51+32.50	Rt.	5	1
Hillside	51+34.00	Lt.	5	1
Hillside	51+85.00	Lt.	4	1
Hillside	51+86.00	Rt.	4	1
Hillside	51+95.00	Lt.	6	1
Hillside	51+95.00	Rt.	6	1
Oliver	47+99.00	Lt.	6	1
Oliver	47+99.00	Rt.	6	1
Oliver	48+14.00	Lt.	5	1
Oliver	48+14.50	Rt.	5	1
Oliver	48+70.00	Rt.	5	1
Oliver	48+70.50	Lt.	5	1
Oliver	51+28.50	Rt.	5	1
Oliver	51+29.50	Lt.	5	1
Oliver	51+84.00	Lt.	4	1
Oliver	51+87.00	Rt.	4	1
Oliver	51+95.00	Lt.	6	1
Oliver	51+95.00	Rt.	6	1
Totals				24

2" A.C. PAVEMENT (BM-2, PG 70-28)			
LOCATION	STATION TO STATION	QUANTITY (S.Y.)	
Oliver	44+64.00	47+56.78	277.05
Totals			277.05

5" A.C. PAVEMENT (BM-2, PG 64-22)			
LOCATION	STATION TO STATION	QUANTITY (S.Y.)	
Oliver	45+49.48	47+56.78	247.76
Totals			247.76

CONCRETE PAVEMENT 5" (REINF.) (PVMT. BASE)			
LOCATION	STATION TO STATION	QUANTITY (S.Y.)	
Oliver	44+64.00	45+49.48	29.29
Totals			29.29

CONCRETE PAVEMENT (9") (REINFORCED)			
LOCATION	STATION TO STATION	QUANTITY (S.Y.)	
Oliver	47+56.78	48+35.88	101.50
Totals			101.50

3" CONCRETE PAVEMENT				
LOCATION	STATION	LENGTH (FT.)	WIDTH (FT.)	QUANTITY (S.Y.)
Hillside	48+74.30	8	76	67.56
Hillside	51+26.80	8	76	67.56
Oliver	48+74.10	8	76	67.56
Oliver	51+25.25	8	76	67.56
Totals				270.22

REINFORCED CRUSHED ROCK BASE				
LOCATION	STATION TO STATION	8" RCRB QUANTITY (S.Y.)	6" RCRB QUANTITY (S.Y.)	
Oliver	44+64.00	47+56.78	366.58	
Oliver	47+56.78	48+35.88		126.29
Totals			366.58	126.29

8' MEDIAN CROSSWALK		
LOCATION	STATION	QUANTITY (S.F.)
Hillside	48+07.00	243.45
Hillside	51+95.00	248.94
Oliver	47+99.00	135.36
Oliver	51+95.00	245.07
Totals		872.82

RESETTING PAVING BRICK (MEDIAN)			
LOCATION	STATION TO STATION	QUANTITY (S.F.)	
Oliver	44+64.00	47+94.50	330.75
Oliver	48+03.50	48+35.88	32.98
Totals			363.73

REMOVAL OF EXISTING STRUCTURES *			
LOCATION	STATION	SIDE	ITEM
Hillside	48+16	Lt.	Stop Sign
Hillside	48+69	Lt.	Stop Sign
Hillside	51+30	Rt.	Stop Sign
Hillside	51+82	Rt.	Stop Sign
Oliver	48+17	Lt.	Stop Sign
Oliver	48+31	CLN	Sign
Oliver	48+69	Lt.	Stop Sign
Oliver	51+30	Rt.	Stop Sign
Oliver	51+79	Rt.	Stop Sign


* For Information Only.

SEEDING *	
LOCATION	QUANTITY (S.Y.)
Hillside	32.82
Oliver	29.03
Totals	61.85

Seed shall be a mix of Ryegrass applied at a rate of 50 lbs. per acre and Buffalo Grass applied at a rate of 200 lbs. per acre.

* Quantity shown For Information Only. The Contractor will be required to seed all non-paved areas disturbed by construction.

Plotted By: svb Date: 7/16/2014 11:21:44 AM
 FILE: U:\Wichita\Civil\2013\13675\000\Trans\Road\IGN Project\Quantities\13675-Summary Quantities l.dgn

No.	Revision	By	Date
CITY OF WICHITA			
SUMMARY OF QUANTITIES			
GARY JANZEN, P.E.-CITY ENGINEER CITY OF WICHITA PROJECT NO. 472-85174			
 PROFESSIONAL ENGINEERING CONSULTANTS, P.A. 303 SOUTH TOPEKA WICHITA, KS 67202 316-262-2691 www.pec1.com			
Designed by	JPS	Job No.	13675
Drawn by	SVB	Date	May, 2014
			Sht. 10 of 28