

CONCRETE PAVEMENT (8")(RES. DRIVE)			
Station	Offset	Area (sf)	Area (sf)
11+87.01	Lt.	319.38	35.49
10+47.90	Rt.	362.73	40.30
11+69.90	Rt.	335.14	37.24
12+29.04	Rt.	478.40	53.16
13+30.11	Rt.	261.52	29.06
	Total	1757.17	195.25

CONCRETE PAVEMENT (6")(RES. DRIVE)			
Station	Offset	Area (sf)	Area (sy)
12+95.13	Lt.	218.14	24.24
13+67.05	Lt.	333.81	37.09
14+31.14	Lt.	333.81	37.09
14+95.47	Lt.	304.90	33.88
15+70.02	Lt.	304.90	33.88
16+45.78	Lt.	290.47	32.27
16+84.16	Lt.	290.47	32.27
17+80.68	Lt.	333.81	37.09
18+41.69	Lt.	333.81	37.09
19+15.56	Lt.	333.81	37.09
19+53.72	Lt.	218.14	24.24
20+27.33	Lt.	304.90	33.88
21+23.81	Lt.	218.14	24.24
14+33.41	Rt.	319.39	35.49
16+31.05	Rt.	363.69	40.41
16+88.51	Rt.	189.22	21.02
17+45.72	Rt.	333.81	37.09
17+92.86	Rt.	247.06	27.45
18+63.68	Rt.	304.90	33.88
19+39.02	Rt.	218.14	24.24
19+94.48	Rt.	218.14	24.24
	Total	6013.46	668.17

5" ASPHALT PAVEMENT (3" BASE)				
Sta. to Sta.	Length (lf)	Width (lf)	Depth (in.)	Area (S.Y.)
10+30.00	21+75.87	1145.87	26.00	3310.3
21+75.87	22+22.61	46.74	Varies	151.4
	Total			3461.7

COMBINED CURB and GUTTER			
Sta. to Sta.	Side	Length (L.F.)	
10+30.00	21+75.87	Rt.	1145.9
21+75.87	21+90.65	Rt.	19.8
10+30.00	22+33.84	Lt.	1203.8
	Total		2369.5

CRUSHED STONE SUBGRADE (5")				
Sta. to Sta.	Length (LF)	Width (LF)	Area (SY)	
10+30.00	21+75.87	1145.87	33.00	4201.5
21+75.87	22+22.61	46.74	Varies	184.2
	Total			4385.7

MAILBOX RELOCATION		
Station	Offset	Side
12+82.62	12.04	Lt.
13+53.15	11.71	Lt.
14+11.52	12.44	Rt.
14+82.12	11.61	Lt.
15+61.90	11.15	Lt.
16+06.28	18.05	Rt.
16+60.07	13.44	Rt.
17+03.38	11.70	Lt.
17+12.80	15.38	Rt.
17+60.15	14.17	Rt.
18+27.12	12.03	Lt.
18+28.54	13.54	Rt.
18+74.17	12.32	Rt.
19+02.19	13.43	Lt.
19+02.29	12.57	Rt.
19+56.41	13.39	Rt.
19+75.72	9.99	Lt.
20+14.89	13.18	Rt.
20+20.42	28.51	Lt.
20+40.92	10.90	Lt.
21+12.86	11.36	Lt.
	Total	21

EARTHWORK				
Sta. to Sta.	Common Excavation (CY)	Embankment (CY)	Contractor Furnished Excavation (CY)	
10+20.00	22+40.00	2374	61	
	Totals	2374	61	

BID ITEMS		
Item	Quantity	UM
Paving Items		
Construction Traffic Control	1	L.S.
Clearing and Site Preparation	1	L.S.
Crushed Stone Subgrade (5 inch)	4386	Sq. Yd.
5" Asphalt Pavement (3" Base)	3462	Sq. Yd.
Combined Curb & Gutter	2370	L.F.
Common Excavation	2374	Cu. Yd.
Inlet Hookup	2	EA
Wheelchair Ramp	2	EA
Mailbox Relocation	21	EA
Seeding (TRWPC)	1	L.S.
Water Meter Adjustment	20	EA
Water Valve Adjustment	3	EA
Irrigation Sleeve/Sprinkler System Repairs	1	LS
Drainage Items		
Type I-A Inlet (Top Only)	2	EA
Measured Quantity Items Pavement		
Concrete Pavement (6 inch)(Res. Drive)	669	S.Y.
Concrete Pavement (8 inch)(Res. Drive)	196	S.Y.

INLET HOOKUP		
Station	Offset	Side
21+75.82	15.00	Rt.
22+37.47	15.00	Lt.
	Total	2

WHEELCHAIR RAMP		
Station	Offset	Side
21+87.97	30.5	Rt.
22+50.11	20.3	Lt.
	Total	2

TYPE 1-A INLET (TOP ONLY)				
Station	Offset	Side	Existing Top Elev.	Proposed Top Elev.
21+75.82	15.00	Rt.	118.43	119.76
22+37.47	15.00	Lt.	119.31	119.31

CITY OF WICHITA		JOANN STREET CENTRAL TO ZOO BOULEVARD	
SUMMARY OF QUANTITIES			
WICHITA, KANSAS		DESIGNED: J.R.L.	DRAWN: M.P.M.
TRAN SYSTEMS 248 North Waco, Suite 420 Wichita, Kansas 67202		CHECKED: B. A. L.	DATE: 7/2003
SCALE: 1" = 20'		SHEET NO.: 10	