

STATE	PROJECT NO.	YEAR	SHEET NO.	TOTAL SHEETS
KANSAS	87 TE-0396-01	2014	2	68

**GENERAL NOTES:**

The contractor shall erect and maintain traffic control devices in accordance with the Manual on Uniform Traffic Control Devices subject to the Engineer's approval.

Utility service lines, poles, valve boxes, gas meters and etcetera are to be adjusted as necessary by others prior to construction unless the plans specifically call for their adjustment by the Contractor or unless the plans specifically identify a utility to be adjusted by its owner during construction. Existing utilities and their location, as shown on the plans, represent the best information obtainable for design. The Contractor will be required to work around existing utilities within the right-of-way which do not conflict with proposed construction.

The Contractor will be required to provide a minimum advance notice of forty-eight (48) hours to utility companies prior to excavation or working adjacent to utilities.

The following numbers are provided:

Kansas One-Call.....	687-2470
Cox Communications.....	262-4270
Kansas Gas Service.....	831-5615, Emergency 1-888-482-4950
Westar Energy.....	261-6251
Aquila Networks.....	942-8811
AT&T.....	268-2245
City of Wichita Water Department.....	268-4940
City of Wichita Sewer Maintenance.....	268-4924

A saw cut the full depth of the existing pavement thickness shall be provided at locations where proposed construction abuts an existing surface course of pavement where the existing pavement is to be removed. Sawed Joint to facilitate removal within six (6) feet of existing joints will not be permitted and for such instances the limits of sidewalk removal shall extend to the existing joint. Such saw cuts will not be paid for directly and this cost shall be considered INCIDENTAL to the removal of the surface or surface or pavement.

All project waste including any trees, milled asphalt, rubble from miscellaneous structures, abandoned pipes, excess excavation and etc. shall be disposed of on sites to be provided by the Contractor. These sites shall be approved by the engineer as to suitability, appearance and site location. Locations that, in the opinion of the engineer, will leave an unsightly appearance will not be approved. All disposal sites must be approved by the Kansas Department of Health and Environment. Material either stockpiled or disposed of in a flood plain would require a Kansas State Board of Agriculture permit. Any material dumped in waters of the United States or wetlands is subject to U.S. Corps. of Engineers permitting regulations. Any material buried or stockpiled beyond approved construction limits would require additional archaeological investigations unless buried in a previously approved borrow location.

Trees and shrubs in public right-of-way which are in direct conflict with proposed new construction shall be removed and disposed of by the Contractor with the engineer's approval. Trees and shrubs which are not in direct conflict with proposed new construction shall be saved and protected from damage. Trees larger than 15" dia. as measured 24" above the ground level shall be bid as "Large Tree Removal", trees less than 15" shall be bid as "Small Tree Removal".

The Contractor shall be responsible for preserving shown property irons. The Contractor will be required to re-establish any shown property irons or quarter section corners which are damaged or destroyed by his construction operations. Such irons shall be re-established by a licensed land surveyor in accordance with state laws. This work will not be paid for directly, but shall be considered SUBSIDIARY to other pay items of work in the contract.

The Water Department shall field locate water valves one time during construction when requested by the Contractor. It shall be the Contractor's responsibility to preserve such field locations during the construction process. Water valves, water boxes or fire hydrants damaged during construction shall be repaired by the Contractor at his own expense.

Where water valves are shown to be adjusted, the work shall include only the adjustment of the water box to the finished grade as shown or as directed by the Engineer. At locations where available adjustment is insufficient to match design grade, the Contractor shall notify the Wichita Water Department at 268-4908 and obtain or coordinate placement of a new valve box capable of meeting final grade.

Construction of temporary pavement required for business access during construction shall be INCLUDED in the lump sum bid item "TRAFFIC CONTROL" and shall include all grading, fill, compaction, soil scarification, removal, disposal and etc. necessary for business access.

The Contractor shall give all property owners and/or tenants of developed property abutting the project limits a minimum of 10 days advance notice prior to the start of construction.

The Contractor shall comply with all applicable safety regulations.

The Contractor is made aware that he will be working in close proximity of existing utilities. Any conflicts with such utilities shall be reported to the Engineer. The Contractor shall coordinate the construction of this project with the relocation of any existing utilities by the utility companies.

Areas over-excavated in pavement removal shall be filled to subgrade elevation and compacted to 95% Std. Density. This work shall be considered SUBSIDIARY to other items of the contract.

Only existing private drains shown to be reconnected shall be reconnected to the proposed storm sewer system. The Contractor shall notify immediately the Project Engineer and/or the Project Inspector if he discovers any private drain connection not shown on the storm sewer plans.

Prior to bidding the project, each bidder shall visit the site and satisfy himself of surface and subsurface conditions. Each bidder shall also fully inform himself as to the extent of Site Clearing and Site Restoration to be performed.

The lump sum Bid Item "Site Clearing" shall INCLUDE all costs for the removal of signs, foundations, light pole bases, abandoned water meters, manholes, pole bases, fences, traffic service boxes, planter boxes, trees, shrubs, stumps, traffic signal appurtenances, sprinkler heads, irrigation control devices, drain pipes (<10"), aprons, flumes, valve boxes, pavement markings, guard posts, wheel chair ramps, concrete barriers, monitoring wells, abandoned pipes, parking blocks, and any other item(s) slated for removal for which a pay item is not provided for in the proposal.

The Contractor shall be responsible for implementing erosion control methods during construction to prevent unnecessary silt/sediment discharge through downstream properties and/or storm sewer systems. The Contractor shall install and maintain erosion controls per plan approved by the Engineer.

The Contractor shall be aware that some gas lines within the project corridor may be abandoned in place as new lines are installed. The Contractor shall be responsible for contacting the appropriate owners to determine the status of said lines.

ℓ Elevations shown on plans are to the ℓ of gutter, unless specified otherwise. No allowance is made for drops at inlet.

All pavement markings shall be epoxy. Pavement markings shall be installed per manufacture's recommendations. Full traffic may not be restored (and substantial project completion achieved) until all pavement markings are in place. Should construction timing be such that restoration of traffic becomes necessary during temperatures prohibiting the installation of epoxy markings, the contractor shall install and maintain temporary markings until such time that epoxy markings may be properly installed. Except for the material requirement, temporary pavement markings shall be placed equivalent, in every manner (i.e. dimension, frequency, spacing, etc.), to the permanent marking layout. The cost for temporary pavement markings will not be paid for directly, but shall be considered subsidiary to the bid item for "Pavement Markings".

Inlet Length and Width Callouts are to the inside face of structure unless shown otherwise.

The contractor shall avoid tearing or ripping all tree roots; especially those over 4" in diameter. A clean-cut root will callous over better so it is preferred that the use of a saw grinder or axe be used on roots needing removal. If more than 1/3 of the tree roots are removed or damaged, or if more than 1/3 of the ground area is removed or excavated, then please contact Forestry for inspection. If it is apparent that work around the tree has taken place in recent years and more work involving the removal of roots is necessary, then ask for inspection by forestry staff. If removal of roots larger than 4" diameter is necessary, ask for a forestry inspection. Notification should be done prior to root removal, however in the event that the root is removed prior to inspection, leave the root on site, and leave the hole open for the forestry staff to view.

Salvaged Traffic Lights, Signal Controllers, Signs and Posts.  
All Traffic Signal Lights, Signal Controllers, Signs and Posts shall be removed in Salvageable condition and are to become property of the City of Wichita and delivered to 1825 S. McLean. Transporting, materials, labor and equipment necessary to complete this work shall be SUBSIDIARY to the bid item "Site Clearing".

Parking Meters.  
The Contractor shall notify the City of Wichita 48 hours in advance of working in the location where parking meters are located so that a City Crew may make a determination on the removal of the parking meter (by others). In areas where parking meters are to remain, proposed striping shall be adjusted to match existing meters.

Where existing sign posts are removed the Contractor shall backfill the foundation hole and repair areas that are disturbed during construction. In areas where sign posts are removed in sidewalk or other paved areas, the existing hole shall be grouted and finished flushed with the adjacent ground. This work shall be considered SUBSIDIARY to the "Site Restoration" Bid Item.

All Earthwork associated with Sidewalk, Ramp, or Bikepath Construction is SUBSIDIARY to the item being Constructed.

**RECAPITULATION OF ROAD QUANTITIES**

ITEM	QUANTITY	UNIT
Mobilization	1	LSUM
Site Clearing	1	LSUM
Site Restoration	1	LSUM
Concrete &/or Asphalt Pavement Removed	36	SY
Sidewalk Removed	136	SY
Concrete C & G Removed & Replaced	148	LF
Concrete Sidewalk (4")	2130	SF
Bicycle Ramp w/ Detectable Warnings	7	EA
Wheelchair Ramp w/ Detectable Warnings	3	EA
Concrete Pavement	36	SY
Traffic Control	1	LSUM
Signing	1	LSUM
BMP, Erosion Control	1	LSUM
Seeding, Mulching/Fertilizing	1	LSUM

For Pavement Marking Quantities See Sheet No. 57  
For Signing Quantities (Information Only) See Sheet No. 58

DATE	
BY	
REFERENCES NOTED	
REFERENCES CHECKED	

Drawn By : ROAD  
Plotted : 8/19/2014  
File : G:\M13\0014\Road\C-GEN-M01-101.dgn



**Utility Notes:**

Visual indications of utilities are as shown. Underground locations shown, as furnished by their lessors, are approximate and should be verified in the field at the time of construction. For actual field locations of underground utilities, call 1-800-344-7233. Verification of utilities is the Contractor's responsibility.

CITY OF WICHITA, KANSAS

GENERAL NOTES