Sta 0+00

Sta 0+49.99

-1.328%

45°00'00"

45°34'23"

-1.143%

FOSSIL RIM ESTATES

16

17

18

14

13

12

Valve Box
Elev. = 184.90

Iron @ BL Sta 0+40.73

Sta 1+72.45, 14.25' Rt.
Install subdivision benchmark (Flat Survey Marker No. 8134-08 3" top diameter) in top of curb. Cost shall be incidental to L.F. Curb & Gutter.

Transition from 1/2 crown to full crown in 22.45'

Iron @ BL Sta 1+78.51

Sta 1+72.45

Sta 2+10.03
= ℄ Pepper Ridge

34' F-F
64' R/W

PEPPER RIDGE CT.

PEPPER RIDGE

Proposed Pvm't

Ex. 8" W

Valve Box
Elev. = 182.80

Iron @ BL Sta 1+77.54

Ex. 8" SS

Construct 5" A.C. Pavement W/ 5" Reinf. Rock Base.

Construct Std. Comb. Roll Type Curb & Gutter (3-5/8")

NOTE: ROLL TYPE CURB & G
BE CONSTRUCTED ON
PAVEMENT SHOWN ON
TOP OF CURB ELEVATI
GIVEN FOR FULL HEIGH