


Pole Locations		
Pole No.	Station	Offset
* 1	18+84.26	85.14' Lt.
* 2	17+22.85	61.97' Lt.
* 3	17+34.69	103.39' Rt.
* 4	18+86.24	100.19' Rt.
* 5	19+15.12	61.65' Rt.
* 6	17+50.29	108.62' Lt.
* 7	18+66.08	175.05' Rt.


* Maintain Pole From Previous Phase

SCALE
PLAN: Lat. & Long. 20' 0 20' 40'



NOTE:
--- INDICATES NON-CONFLICTING PHASES THAT SHALL TIME CONCURRENTLY.

PHASES 4 & 8 SHALL RUN EXCLUSIVE (SPLIT PHASE).



TYPICAL SIGNAL INDICATIONS

NOTES

- The power source location is a proposed Westar distribution pole (plan location is approximate only). Overhead lines shall be run from the distribution pole to pole 5. The contractor shall contact the power company to coordinate service lines and cable installation.
- Contractor shall maintain, operate and modify the temporary signal, including timings, the position of signal heads, and radar detectors, starting in Phase 3 and continuing through all subsequent construction phases until the permanent traffic signal is completed and in operation. All work necessary for the proper operation of the temporary traffic signal, whether specifically mentioned or not, shall be SUBSIDIARY to the bid item "Traffic Signalization, Temporary".
- The temporary pavement markings, signs and channelizers shown on this sheet are for informational purposes only.
- The position of signal heads, and signs have been shown in an approximate manner only for the work during Phase 3. The contractor shall reposition these items as required to accommodate work during the remaining phases. Signal heads shall have a minimum separation of 8 feet, a desired separation of 11 feet, and shall typically be centered over the receiving driving lane.
- Radar detection is to be mounted per manufacturer recommendations. Radar detection zones shall typically be centered in traffic lanes, but the contractor shall arrange with the system manufacturer to have a representative on site to assist with final location of detection zones and radar detector mounting, cable termination at the controller, fine tuning, and system set-up programming. Additionally, the contractor shall work with the manufacturer's representative to procure any and all specialty equipment needed to ensure the radar detection units operate correctly.
- Radar Sensors shall be Wavetronix SmartSensor Matrix for stop line detection & SmartSensor Advance for advance detection, or approved equal. At completion of the project all radar sensors shall be removed in salvagable condition and become the property of the City of Wichita. Equipment shall be delivered to 1825 S. McLean Blvd.
- All equipment for the temporary traffic signal shall be removed by the contractor following construction of Phase 6. This equipment shall become the property of the owner and stockpiled on site.
- All signal heads shall be wired with the specified conductors and 12 AWG wire.
- Temporary Pole Mounted Cabinet shall be used for all phases of construction.
- Luminaire shall be LED equivalent of 150 Watt.

LEGEND	
	PHASE 3
	TEMPORARY PAVEMENT
	TRAFFIC MOVEMENT
	CHANNELIZER
	LUMINAIRE
	TRAFFIC SIGNAL POLE WITH DOWN GUY
	TRAFFIC SIGNAL HEAD WITH BACKPLATE
	RADAR VEHICLE DETECTION
	TRAFFIC SIGNAL CABINET
	TEMPORARY POLE MOUNTED CABINET
	JUNCTION BOX
	SIGN ON SIGNAL SPAN WIRE
	HEAD NUMBER
	SECONDARY SERVICE POINT
	TYPE III BARRICADES
	TUBULAR MARKER

Tran Systems
245 NORTH WACO
SUITE 222
WICHITA, KANSAS 67202
PHONE: 316-303-3000
FAX: 316-462-5629

CONSULTANTS:

143RD STREET IMPROVEMENTS
WICHITA, KANSAS
CITY OF WICHITA

REVISIONS:	MARK	DATE	DESCRIPTION

PROJ NO: 87 N-0614-01
SCALE: 1" = 20'
DATE: 5/26/2017
DESIGNED BY: TAU
DRAWN BY: TAU
CHECKED BY: SGE

SHEET TITLE:
TEMPORARY SIGNAL PLAN LAYOUT PHASE 3

SHEET NO.
125
SHEET 125 OF 236

taummed 5/26/2017 11:15:43 AM c:\tran\systems\proj\14ummed\0228400C-CPP-M01-302.dgn