



- ▬ Type 3 barricades
- X Length to the nearest whole mile
- Channelizing device
- ▭ Ahead, 1500 ft, or 1 mile
- ▭ Ahead, 1000 ft, 1500 ft, or 1/2 mile
- ⊕ Right or left
- ⊗ Speed to be determined by the Engineer
- Type "A" low intensity warning light

* For speeds greater than 45 mph use freeway / expressway size signs.

One flagger should be stationed within each multi-lane roadway activity area where work is in a closed lane adjacent to traffic and not separated by a concrete safety barrier system.

3				
2				
1				
NO.	DATE	REVISIONS	BY	APP'D
KANSAS DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL CROSSOVER ON UNDIVIDED ROADWAY				
TE748				
DESIGNED	B.A.H.	QUANTITIES	TRACED	Kristina Eriksen
DESIGN CK.	DETAIL CK.	QUAN. CK.	TRACE CK.	

Saved: 07-19-2017 4:07:35 PM by: CP
 Plot Scale: 1:1 07-25-2017 10:46:35 AM by: CP
 U:\Vchila-Civil\2015\15956\000\Multi-Trans\Drawings\15956-000-796-Standard TE748

KDOT Graphics Certified