

General Notes:

1. Trees and shrubs in public right-of-way which are in direct conflict with proposed new construction shall be removed and disposed of by the contractor with the engineer's approval. Trees and shrubs which are not in conflict with proposed new construction and not shown to be removed shall be saved and protected from damage.

2. Utility service lines, poles, valve boxes, meters, et cetera are to be adjusted as necessary by others prior to construction unless the plans specifically call for their adjustment by the contractor. Existing utilities and their location, as shown on the plans, represent the best information obtainable for design. location information has been obtained from the various utility companies and is either from company record drawings or company provided field locations. The plan locations shown are not guaranteed. Additional existing utilities may also be encountered. the contractor will be required to work around existing utilities within the right-of-way which do not conflict with proposed construction. Three (3) working days prior to construction of each phase of the project, the contractor will be required to field verify the location and elevations of existing utilities. Any discrepancies shall be immediately brought to the attention of the engineer.

3. All manhole rings and covers, inlet grates and frames and storm drainage culverts from structures to be removed shall be carefully removed and stockpiled at locations within the right-of-way, as directed by the engineer for removal by city's own forces and funds. This work shall be considered subsidiary to "REMOVAL OF EXISTING STRUCTURES".

4. Pavement to be removed shall be paid for according to city standard specifications. A full depth saw cut of the existing total pavement thickness shall be provided at locations where proposed construction abuts an existing surface course or pavement for which partial removal of that surface or pavement is required. Removal limits shown within one (1) meter of existing joints shall extend to the existing joint. Such saw cuts will not be paid for directly and this cost shall be considered as subsidiary to the removal of the surface or pavement.

5. Rubble from the removal of miscellaneous structures and excess excavation and pavement removal, which is to be wasted, and excavation shown to be wasted shall be disposed of on sites to be provided by the contractor. These sites shall be approved by the engineer as to suitability, appearance, and site location. Locations that, in the opinion of the engineer, will leave an unsightly appearance will not be approved.

6. All disposal sites must be approved by the Kansas Department Of Health And Environment. Material either stockpiled or disposed of in a flood plain would require a Kansas State Board Of Agriculture Permit. Any material dumped in waters of the United States or wetlands is subject to U.S. Corps Of Engineers permitting regulations.

7. Any Material Buried Or Stockpiled Beyond Approved Construction Limits Will Require Additional Archeological Investigations Unless Buried In A Previously Approved Borrow Location.

8. Properties within the project may have underground irrigation systems (lawn sprinklers) which conflict with new construction. Contractor shall remove such components as needed during construction of the project. The irrigation system shall be reinstalled in like kind before project completion. Any irrigation system modifications required because of project improvements shall be coordinated with the property owner. Portions of underground irrigation systems not in conflict with new construction shall be protected from damage and shall remain in place. All work related to underground irrigations/sprinklers shall be considered as subsidiary to the contract pay item "Relocate/Reconstruct Private Sprinkler System". (Non-participating)

9. Unless otherwise noted on the plans, all labor, materials, and equipment necessary to make connections to existing pipe or existing small structures shall not be paid for directly; but shall be subsidiary to the new pipe placement.

10. The sequencing shown is intended as a guide for major items only. Parts of the work shown for specific sequence may be accomplished in other stages. Major items not constructed within the sequence shown and/or variations to the sequence shown shall be pre-approved by the engineer. The contractor shall be responsible for the coordination of all items of construction. Regardless of sequencing used, traffic handling shall be essentially in accordance with plans and/or as pre-approved by the engineer.

11. When portland cement concrete pavement is to be used as a base with an asphalt overlay, saw joints shall be 3 mm wide. Do Not Seal Joints With Sealant. No white pigment curing compound.

12. Power poles, fire hydrants, utility pedestals, etc. in direct conflict with construction to be relocated by others prior to construction.

13. Unless otherwise noted on the plans the contractor shall remove the existing traffic signals, poles, controller, pull boxes, etc. These items shall remain the property of the city. Items shall be delivered to the City at 1801 S. McLain city yard.

14. All ADA curb ramps are Type I unless otherwise noted.

15. The contractor shall place flowable fill backfill around all storm sewer pipe placed beneath street or driveway.

16. All curb inlet tops shall have a 2% slope toward the front (throat) of the inlet.

17. All paving brick on project to be removed shall be salvaged to City of Wichita and delivered to the city's west maintenance yard. Salvaged brick delivered to the city yard is to be relatively free of asphalt and other foreign material. All work related to delivery of salvaged paving brick shall be considered to be subsidiary to the contract pay item "Transporting of salvaged materials". (This is a non-participating bid item)

18. The Contractor shall coordinate with the City for signal timing during construction.

19. Compaction of earthwork in cut sections shall be subsidiary to excavation. Any destroyed property items shall be replaced.

20. Widened gutter section of combined curb & gutter at intersections will not be payed for directly, and this cost shall be considered as subsidiary to the other contract pay items of work.

21. The bid item "Transporting of Salvaged Materials" shall include, but not be limited to: Salvaged traffic signals & poles, signs, and monument.

22. Traffic control shall be in conformance with the Manual On Uniform Traffic Control Devices, latest edition.

23. All work shall be in conformance with The City Of Wichita, Kansas Standard Specifications For The Construction Of Public Projects, latest edition and the Kansas Department of Transportation Metric Criteria and Controls, latest edition.

INDEX OF SHEETS

1	Title Sheet
2	General Notes
3 - 6	Summary of Quantity Sheets
7 - 14	Typical Sections - Rock Road
15 - 19	Typical Sections - N. 21st St.
20 - 43	Phasing
44 - 77	Temporary Traffic Control Plans
78 - 82	Plan Sheets - N. Rock Road
83 - 89	Plan Sheets - N. 21 Street
90 - 91	Intersection - Rock Road & N. 21st Street
92 - 93	Geometrics - N. Rock Road & N. 21st Street
94	Standard Drive Entrances
95	Valley Gutter Detail, Wheelchair Ramp Detail
96	Miscellaneous Details
97	Gravity Retaining Wall - N. Rock Road
98	Gravity Retaining Wall - N. 21st Street
99 - 103	Pipe Profiles - N. 21st St.
104 - 110	Curb Inlet Detail Sheets
111	Reinforced Concrete Manhole Detail
112	Precast Concrete Manhole Detail
113	Manhole Frame & Cover Detail
114	Inlet & Manhole Adjustment Details
115 - 126	Traffic Signal Plans
127 - 128	Permanent Pavement Marking and Signage - Rock Rd.
129 - 131	Permanent Pavement Marking and Signage - N. 21st St.
132	Pavement Marking Summary
133 - 134	Signage Details & Summary
135 - 138	Soil Erosion BMP
139 - 146	Rock Road Cross Sections
147 - 158	N. 21st St. Cross Sections

CONTROL POINTS

#	NORTH	EAST	ELEV. *	DESC.	STATION
1.	15090.573	11983.854	64.027	3/4" REBAR	0+438.002, 16.058 LT.
2.	15263.728	12019.193	65.247	CHISELED X	0+611.363, 18.362 RT
3.	15443.109	12018.898	66.062	3/4" REBAR	0+790.738, 16.913 RT
4.	15751.189	11989.641	66.193	3/4" REBAR	1+098.750, 13.370 LT
5.	15993.834	11988.715	65.713	3/4" REBAR	1+341.396, 13.792 LT
6.	15665.002	11586.033	66.855	3/4" REBAR	49+582.796, 11.841 LT
7.	15665.030	11185.065	63.778	3/4" REBAR	49+181.816, 11.191 LT

*City of Wichita Datum

UTILITIES:

Utilities located by the following:

Electricity -	KGE 1900 E. Central Wichita, KS 67201 (316) 261-6251	Telephone -	Southwestern Bell Telephone 154 N. Broadway Wichita, KS 67202 (316) 268-2245
Gas -	Kansas Gas Service 1021 E. 26th Street N. Wichita, KS 67219 (316) 832-3122	Water & Sewer -	City of Wichita Utilities Director 455 N. Main St., 8th Floor Wichita, KS 67201 (316) 268-4555
Gas -	Peoples Natural Gas 1611 South Hoover Wichita, KS 67209 (316) 941-1608	Cable Television -	Cox Communications 701 E. Douglas Wichita, KS 67201 (316) 262-4270

ROCK ROAD

GENERAL NOTES

HWS
Consulting Group Inc.

Omaha Office
10844 Old Mill Rd. Ste. 1
Omaha, NE 68154
Phone: (402) 333-5792
Fax: (402) 333-2248

Designed By:	BWE	Checked By:	RJK
Drawn By:	HS	Date:	04-04-01
		Job No.	55-70-2003