

INLET & MANHOLE DATA

ROUTING SEQUENCE		LOCATIONS OF INSTALLATIONS			CONSTRUCT OR INSTALL										DIMENSIONS				ELEVATIONS		INFLOW CONDUITS				OUTFLOW CONDUITS		FOR INFORMATION ONLY					REMARKS		
					INLET (TY.12) (CURB)	INLET (TY.12) (SPEC)	INLET (TY.22) (CURB)	INLET (TY.1A) (CURB)	DROP INLET (DOUBLE)	M.H. (STD.) (TY.B)	END SECT. *	G & F A (TYPE)	L & F A (TYPE)	L. (FT.)	W. (FT.)	H. (FT.)	HT. (FT.)	TOP	FLOOR	SIZE DIRECTION	FLOWLINE (ELEV.)	SIZE DIRECTION	FLOWLINE (ELEV.)	SIZE DIRECTION	FLOWLINE (ELEV.)	SIZE DIRECTION	FLOWLINE (ELEV.)	NO STEP	CAST IRON (LBS.)	STRUC. STEEL (LBS.)	REINF. STEEL (LBS.)		CLASS 'A' CONC. (MISC.) (CU. YD.)	CL. III EXC. (CU. YD.)
18	19	66+00	WEBB	25.5' LT.			1							222.00	214.00																			
19	21	66+00	WEBB	25.5' RT.			1							202.00	213.50	15"-W.	214.00																	
20	21	61+50	WEBB	25.5' LT.			1							217.09	208.09																			
21	23	61+50	WEBB	25.5' RT.			1							217.09	207.09	15"-W.	208.25	15"-N.	208.25															
22	23	56+50	WEBB	25.5' LT.			1							210.55	206.05																			
23	26	56+50	WEBB	36.5' RT.			1							210.20		15"-W.	206.00	21"-N.	205.20															
24	25	51+21.61	WEBB	107.99' LT.				1						204.00		4'-0"	2'-0"																	
25	26	51+23.50	WEBB	42.5' LT.			1							203.92	197.92	24"-W.	198.35																	
26	27	51+23.50	WEBB	42.5' RT.			1							203.92		38"x24"-W.	197.85	24"-N.	198.10															
27	28	51+13.5	WEBB	44.5' RT.						1				203.92		4'x3'-N.	197.84																	
28	30	11+13.5	21ST. ST. N.	44.5' RT.						1				205.10		4'x3'-NW.	197.74																	
30	33	12+78.5	21ST. ST. N.	42.5' RT.			1							204.40		30"-N.	197.88	7'x3'-W.	197.59															
32	33	16+08.5	21ST. ST. N.	25.5' RT.			1							203.58	198.58	11'-4"	5'-4"																	
33	33	16+08.5	21ST. ST. N.	36.5' LT.										203.24		11'-4"	4'-4"																	
47		19+00.00	21ST. ST. N.	42' LT.				1						201.0		4'-0"	2'-0"																	
48	35	20+42.00	21ST. ST. N.	30' RT.							1																							
49	35	20+58.00	21ST. ST. N.	30.56' RT.							1																							
50	35	20+58.00	21ST. ST. N.	40' LT.							1																							
-	35	20+50.00	21ST. ST. N.	40' LT.							1			202.0																				
TOTALS								10	2		3	3																						

CONDUIT DATA

ROUTING SEQUENCE		LOCATIONS OF INSTALLATIONS			CONSTRUCT OR INSTALL			CONDUIT FLOW LINES		SEWER EXCAVATION		STORM SEWERS (LIN. FT.)										END SECTIONS (EACH)		AASHTO CONC. CLASS	METAL PIPE GAGE	REMARKS																	
												REINF. CONC.					REINF. CONC.	CORR. METAL	15"	18"	48"																						
FROM	TO	STATION	ROUTE IDENTIFICATION	DISTANCE RT./LT.	TYPE OF CONDUIT	LENGTH (FEET)	INFLOW (ELEV.)	OUTFLOW (ELEV.)	ROCK (CU. YDS.)	COMMON (CU. YDS.)	15"	21"	24"	30"	54"	1.5Sq.Ft.	5.0Sq.Ft.	4'x3'	7'x3'	9'x3'	15"	18"	48"																				
18	19	66+00.00	WEBB	25.5' LT.	15" RCP	56	214.25	214.00			56																																
19	21	66+00.00	WEBB	25.5' RT.	15" RCP	450	213.90	208.25			450																																
20	21	61+50.00	WEBB	25.5' LT.	15" RCP	56	208.50	208.25			56																																
21	23	61+50.00	WEBB	25.5' RT.	21" RCP	500	207.75	205.20			500																																
22	23	56+50.00	WEBB	25.5' LT.	15" RCP	67	206.30	206.00			67																																
23	26	56+50.00	WEBB	36.5' RT.	24" RCP	525	204.95	198.10			525																																
24	25	51+21.61	WEBB	107.99' LT.	1.5Sq.Ft. RCPHE	60	198.50	198.35			60																																
25	26	51+23.50	WEBB	42.5' LT.	5.0Sq.Ft. RCPHE	91	198.25	197.85			91																																
26	27	51+23.50	WEBB	42.5' RT.	4'x3' RCB	12	197.85	197.84			12																																
27	28	51+13.5	WEBB	44.5' RT.	4'x3' RCB	97	197.84	197.74			97																																
28	30	11+13.5	21ST. ST. N.	44.5' LT.	4'x3' RCB	160	197.74	197.59			160																																
29	30	12+78.5	21ST. ST. N.	70.5' LT.	30" RCP	24	197.95	197.88			24																																
30	33	12+78.5	21ST. ST. N.	42.5' LT.	7'x3' RCB	330	197.59	197.25			330																																
31	33	16+08.5	21ST. ST. N.	59.0' LT.	30" RCP	6	197.59	197.54			6																																
32	33	16+08.5	21ST. ST. N.	25.5' RT.	15" RCP	67	198.79	198.50			67																																
33	34	16+08.5	21ST. ST. N.	36.5' LT.	9'x3' RCB	440	197.25	196.81			440																																
48	35	20+42.00	21ST. ST. N.	30' RT.	15" RCP	6	196.68	196.62			6																																
49	35	20+58.00	21ST. ST. N.	30.56' RT.	15" RCP	6	196.68	196.62			6																																
50	35	20+58.00	21ST. ST. N.	40' LT.	15" RCP	6	197.5	197.0			6																																
TOTAL												714	500	525	30	60	91	269	330	440	3																						

1 10-8-90 Detailed on CADD R.J.S. J.O.B.
NO. DATE REVISIONS BY APPD.

KANSAS DEPARTMENT OF TRANSPORTATION

SCHEDULE OF INLETS AND MANHOLES

STD. NO. 653 G

FHWA APPROVAL 1-17-91
DESIGNED: [] DETAILED: []
DESIGN CK. [] DETAIL CK. []

APP'D: James O. Breaer
DESIGNED: [] DETAILED: []
DESIGN CK. [] DETAIL CK. []