

DATE	
BY	
REFERENCES NOTED	
REFERENCES CHECKED	

CONDUIT AND CABLE ROUTING TABLE																										
		CONDUIT (FT)													CABLE (FT)											
FROM	TO	CTR TO CTR DISTANCE (FT)	TRENCHED					BORED				ON STRUCTURE	POWER					COMM.		COMM.	DEVICE					
			1	2	3	4	5	6	7	8	9	1	2	3	4	5	FIBER OPTIC		⊠	1	2	3	4			
			1 IN	2 IN	3 IN	4 IN	SPARE 2 IN	2 IN	3 IN	SPARE 2 IN	2 IN RMC	3-#X/0	3-#4	3-#6	2-#X	2-#X	12 SMFO	96 SMFO	CAT 6 CABLE	CCTV	DMS	VDS*				
CCTV Site (Exist.)	SV054-01 (Exist.)	48																								
SV054-01 (Exist.)	SV054-02	440			440				440																	
SV054-02	SV054-03	1158			1158				1158																	
SV054-03	SV054-04	94									94															
SV054-04	SV054-05	1000									1000															
SV054-05	SV054-06	906									906															
SV054-06	SV054-07	1482									1482															
SV054-02	PB054-01 (Exist.)	134									134															
PB054-01 (Exist.)	CCTV Site (Exist.)	21																								
SV054-05	PB (Exist.)	36									36															
PB (Exist.)	TSS Site (Exist.)	27																								
TOTAL					1598				1598		3652				3482											

\* CONDUIT AND / OR CABLE RUN CARRIES OVER TO ADJACENT SHEETS

\*\* MAX. HEIGHT OF DETECTOR ON POLE ASSUMED AT 42 FT FOR CABLE QUANTITIES