

FHWA REGION NO	STATE	PROJECT NO	YEAR	SHEET NO	TOTAL SHEETS
7	KANSAS	87-U-1362-01	1993	101	149

WORD & SYMBOL DETAILS (WHITE)



RAILROAD CROSSING DETAIL






* The distance from the railroad crossing marking to the nearest track will vary according to the approach speed and sight distance of the vehicular traffic approaching, but probably should be not less than 50 feet.

A three-lane roadway should be marked with a centerline for two-lane approach operation on the approach to a crossing.

On multi-lane roads the transverse bands should extend across all approach lanes, and individual RXR symbols should be used in each approach lane.

Refer to Standard Alphabet for Highway Signs and Markings for RXR symbols details.

TYPICAL APPROACH TAPER DETAIL



Approach Taper Length from point A to point B is to be determined using the above equation. Point A is the location at which taper starts. Point B is the end of full width left turn channelization.

Unless otherwise specified the space between lines should be at least four times the height of the characters for low speed roads but not more than ten times the height of the characters, under any conditions.

For specific pavement marking details and dimensions see plan sheets.


PAVEMENT MARKINGS

LOCATION	Solid WHITE Edge Line	Broken WHITE Lane Line	Dotted WHITE Extension	Solid WHITE Channelization	Solid WHITE Diagonal	Solid WHITE Crosswalk	Solid WHITE Stop Line		Solid YELLOW Median	Solid YELLOW Edge Line	Solid YELLOW Double	Solid YELLOW Diagonal	Broken YELLOW	Solid YELLOW No Passing
2+23 to 21+50		770					70				5226	110		
14+66 to 18+14	348													
18+14 to 21+50	672													
6+20 to 9+30				310										
8+95 to 9+75				120										
5+50 to 9+75				425										
10+30 to 16+90				660										
10+30 to 11+10				120										
10+75 to 14+00				325										
7+50 to 9+70				220										
8+90 to 9+70				120										
							(See	Sheet	104 for	Recap	of Bid	Items)		
	1020	770		2300			70				5226	110		

WORD & SYMBOL MARKINGS

LOCATION	↱	↰	↑	↱	↰		RXR	STOP	ONLY	X-ING	SCHOOL		

TYPICAL CROSSWALKS



Type I Crosswalk lines shall be solid white lines. They shall not be less than 6" wide and should not be spaced less than 6' apart.

Type II: These lines should be solid white 24" wide placed parallel to the direction of traffic flow. The line placement is determined by lane line, center line, and wheel path in such a manner as to minimize traffic wear. The crosswalk width should be not less than 6'. The transverse crosswalk lines may be omitted.

Type III: These lines should be solid white 12" to 24" wide, spaced 12" to 24" apart placed at a 45° angle to the line of the crosswalk. The crosswalk width should be not less than 6'. The transverse crosswalk lines may be omitted.

BILL OF MATERIALS

ITEMS	TOTAL	UNITS
COLD PLASTIC MARKING (CL. A)(4")		LIN. FT.
COLD PLASTIC MARKING (CL. A)(8")		LIN. FT.
COLD PLASTIC MARKING (CL. A)(12")		LIN. FT.
COLD PLASTIC MARKING (CL. A)(18")		LIN. FT.
COLD PLASTIC MARKING (CL. A)(24")		LIN. FT.
		LIN. FT.
COLD PLASTIC MARKING (CL. B)(4")		LIN. FT.
COLD PLASTIC MARKING (CL. B)(18")		LIN. FT.
COLD PLASTIC MARKING (CL. A)(RIGHT TURN ARROW)		EACH
COLD PLASTIC MARKING (CL. A)		EACH
		EACH
COLD PLASTIC MARKING (CL. A)		EACH
		EACH
COLD PLASTIC MARKING (CL. A)		EACH
		EACH
COLD PLASTIC MARKING (CL. A)		EACH
		EACH

NO	DATE	REVISIONS	BY	APP'D
3				
2	7/7/80	RR X ng Detail	JFF	
1	7/7/80	Word & Symbol Details	JFF	

KANSAS DEPARTMENT OF TRANSPORTATION

COLD PLASTIC PAVEMENT MARKING 21ST. ST. N.

URBAN HIGHWAYS DEPARTMENT STD. NO 2.1 7/80

SHEET NO. OF	SCALE	APP'D Fred C. Tillotson
DESIGNED	DETAILED J F F	QUANTITIES	TRACED
DESIGN CK.	DETAIL CK. F. E. T.	QUAN. CK.	TRACE CK.

MKEC CAIG