



Scale: 1" = 20'

Alt. 1:
Const. 10" A.C. Pavement
(8" Bit. Base)
Alt. 2:
Const. 6" A.C. Pavement (4" Bit. Base)
On 10" Reinf. Crushed Rock.

Alt. 1:
Const. 6" Temporary A.C. Pavement
(4" Bit. Base) Over 6" Subgrade Treatment
Alt. 2:
Const. 6" Temporary A.C. Pavement
(4" Bit. Base) Over 6" Reinf. Crushed
Rock.

P.V.I.
ELEV. = 85.74
NO V.C.

P.V.I.
ELEV. = 85.74
NO V.C.

UNPLATTED

ADDITION

ADD ALTERNATE TREES & LOCATION
2 SHADEMASTER HONEYLOCUST

Const. 6' Conc.
Sidewalk

Const. Std. Comb. Curb
& Gutter (6" & 1 1/2")

1 SHADEMASTER HONEYLOCUST
2 - 2 1/2" BB

ACCESS CONTROL EXCEPT FOR 2 OPENINGS



SOUTH SENECA IMPROVEMENTS

LANDSCAPE PLAN

48TH ST. SO. TO MACARTHUR RD.

MID-KANSAS ENGINEERING CONSULTANTS PA
3500 NORTH ROCK ROAD
BUILDING #800
WICHITA, KANSAS 67226

638-6666

Design
Drawn by
Checked by
Date DEC., 1992
Job no

Sheet
10
of **12**