



1" = 150'

MINIMUM BUILDING PAD ELEVATION FOR LOWEST OPENING INTO STRUCTURES		
BLOCK	LOT NO.'S	ELEVATION (M.G.V.D.)
1	1 - 60	1357.8

SETBACK LINES PER ZONING REGULATIONS

M = Measured
 C = Calculated
 (A) = Assumed

- SURVEY MARKER LEGEND**
- 1/2" IRON PIPE
 - ⊠ RAILROAD SPIKE
 - ⊞ 5" x 5" CONCRETE MONUMENT WITH A 5/8" REBAR
 - 5/8" REBAR W/ RIBBLES & BOHM CAP (SET)

BENCH MARK: CITY OF WICHITA BRASS DISK ON THE NORTHWEST CORNER OF A.R.C.B.C., 0.75 MILES EAST OF HOOVER ON 21ST ST. NORTH ELEV = 1321.62 M.S.L.

BENCH MARK: CITY OF WICHITA BRASS DISK TOP OF HEADWALL OF R.C.B.C UNDER WEST STREET, NORTH OF 29TH ST. NORTH ON EAST SIDE OF WEST ST. ELEV = 1321.80 M.S.L.

BENCH MARK: CITY OF WICHITA BRASS DISK AT THE NORTHWEST CORNER OF HOOVER AND 21ST ST. NORTH ELEV = 1326.47 M.S.L.

BENCH MARK: CITY OF WICHITA BRASS DISK AT THE SOUTHWEST CORNER OF HOOVER AND 29TH ST. NORTH ELEV = 1330.16 M.S.L.

Sawmill Creek Addition PLAT WICHITA, KANSAS		DESIGN AML	SHEET 16 OF 16
Ruggles & Bohm, P.A. Engineering, Surveying, Land Planning		DRAWN AML	
924 North Main (316) 284-8008 Wichita, Kansas 67203 (316) 284-4621 fax www.rbkansas.com E-mail: info@rbkansas.com		REVIEW	UTILITY 16
PROJECT NUMBER POND [plat]		DATE Jan. 18, 2005	

58-01-03-03