



- Notes:
- 1 Existing zoning - 'AA'
  - 2 Date of topographical map - 31 May 1972
  - 3 Bench Mark - Standard Disc on the Northeast Corner of Bridge at the Southwest Corner of property. ELEVATION 137.17
  - 4 Minimum pad elevation:  
 'R-6' Area = 140.70  
 'LC' Area = 139.00  
 Minimum fill elevation:  
 'R-6' Area = 139.20  
 'LC' Area = 137.50

- LEGEND.
- Computer Note No.
  - Manhole
  - Inlet
  - Outlet
  - Storm Sewer Size and Location
  - Limits of Drainage Area

Drainage Plan  
 Lots 1 and 2 Block 1  
 Spring Lake Addition  
 Hold Building permits and/or development  
 for Lot 3 until ~~and~~ final drainage plan and/or  
 guarantees (if required) submitted.

1	Add storm sewer sizes, note no., elevations	KJH	3-18-80
	No.	Revision	By Date
<b>SPRING LAKE ADD.</b> <b>DRAINAGE PLAN</b> <b>WICHITA, KANSAS</b> <b>PROFESSIONAL ENGINEERING CONSULTANTS, P.A.</b> <small>ENGINEERS        WICHITA, KANSAS</small>			
Designed by	CMB/KJH	Job No.	79254
Drawn by	KJH	Date	
			Sht. 1 of 1

SW CORNER OF THE SE 1/4  
 OF SECTION 30, T 21 S, R 2 E  
 OF THE 6TH P.M.