Sta. 0+00 Sec. Cor. Stone
S.W. Cor. Sec. 28-T27S-R2E
Iron Pipe 6" Deep
40.6° N.E. to Steel Cor. Post
51.2° S.W. - 3 nails in T.P.
73.7° " " Pipe Line Marker
63.7° N.W. to 3 nails in Guy Pole
54.9° S.E. " Steel Cor. Post
30.5° W. " Hedge North

El. 1358.4
El. 1359.0
Welsh Street
30' x 30' School Flag Pole in Concrete
Merry-go-Round
Sta. 2+09 Ent. Culvert
18"x18" C.T.C.
Remove & Const.
24"x20' R.C.P.
Pasture
Hedge to be removed
Sec. 28 T27S - R2E
Sta. 9+23 Bri. #62-33-923
2'x24' C.M.P. D.A. 10 Ac. C-0.5
Remove & Const.
5'x26'x30' R.C.B.C.
R/W ℄ 40'
Sta. 14+25
2'x12'x14' M.B.C.
Remove & Const.
24'x20' R.C.P.
Yard
Guy Pole
Evergreens
Pasture
Pasture
Hedge to be removed
Sta. 24+82
24"x12"x12' M.B.C.
Remove & Const.
24"x20' R.C.P.
Field Ent. +82
Yard
Sta. 26+82
15"x12"x12' M.B.C.
Remove & Const.
24"x20' R.C.P.
Wheat
Sta. 1+08 School Yard Ent.
2'x2'x15' W.B.C.
Remove & Const.
24"x20' R.C.P.
Plowed
Yard
Orchard
Orchard
Yard
Sec. 33 T27S - R2E
Alfalfa
Yard
Sta. 6+46
2'x17' C.M.P.
Remove & Const.
24"x20' R.C.P.
Sta. 15+85
4'x2'x2'1" R.C.B.C.
D.A. 90 Ac. C-0.5
Remove & Const.
6'x2'6"x30' R.C.B.C.
Sta. 17+00
12"x12"x16' W.B.C.
Remove & Const.
15"x20' R.C.P.
Pasture
South ¼ Cor. Sec. 28
Sta. 26+50.2 Stone 6" Deep
26.8° N. to 3 nails in H.L.P.
29.0° S. " " " " "
35.3° S.E. " " " Oak Post
32.1° N.E. " " " " "
3.0' E. to line of H.L.P.'s N/S.
Hedge Grove
H.L.P. Anchor +11
H.L.P. Anchor +20
Field Ent. +82
H.L.P. Anchor +20
Sta. 26+82
15"x12"x12" W.B.C.
Remove & Const.
24"x20' R.C.P.
Wheat

B.M. #1 Step B.M. in H.L.P. 43' N.E. of Sec. Cor.
S.W. Cor. Sec. 28-T27S-R2E El. 1359.92

Exc. 358 Cu. Yds.
Emb. 286 "
Excess 20%

Exc. 1409 Cu. Yds.
Emb. 1027 "
Excess 20%

Exc. 1720 Cu. Yds.
Emb. 1356 "
Excess 20%

1360.0
1350.0
1340.0
Lt.
Rt.
1359.0
Profile of Crossroad
Line of Cent. Pts.
6.11%
200' V.C.
E. 100
200' V.C.
6.40%
200' V.C.
11.000%
200' V.C.
E. 1351.
Crown grade 1354.09
E. 1350.69
E. 1348.3
Crown grade 1351.40
E. 1347.90
E. 23.7%
400' V.C.
1360.0
1350.0
1340.0

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27

Sta. 27+47
18"x16' C.M.P.
Yard
Plowed
Shelterbelt
Sec. 28 T27S-R2E
Pasture
Sta. 39+58 Const
15"x20' R.C.P.
Sta. 43+17
4'x2'x20' R.C.B.C.
D.A. 30 Ac. C-0.5
Remove & Const.
4'x2'x30' R.C.B.C.
R/W ℄ 40'
Plowed
Const. 15"x20' R.C.P.
Yard
Evergreens
Sta. 52+33
18"x31' C.M.P.
D.A. 3 Ac. C-0.4
To remain in place
Hedge Grove
Sta. 26+50.2 ¼ Cor.
Sta. 28+28
12"x14' C.M.P.
Remove & Const.
24"x20' R.C.P.
Hedge to be removed
Sta. 34+70
4'x2'x24' R.C.B.C.
D.A. 185 Ac. C-0.5
Remove & Const.
2-5'x2'x30' R.C.B.C.
R/W ℄ 40'
Const. Summit
Hedge to be removed
Sta. 53+01.5 Sec. Cor. Stone
S.E. Cor. Sec. 28-T27S-R2E
Stone 15" Deep
4.8° S.W. to 3 nails in Cor. Fe. Post
42.9° S.E. " " " " "
81.3° N.W. " " " " "
42.2° N.E. " " " T.P.
45.0° S.W. " " " H.L.P.
Wheat
Sec. 33 T27S-R2E
Yard
Wheat

B.M. #2 Step B.M. in H.L.P. 79' S.E. of ¼ Cor.
South Side Sec. 28 El. 1343.90

B.M. #3 Step B.M. in H.L.P. 45' S.W. of Sec. Cor.
S.E. Cor. Sec. 28, T27S-R2E El. 1344.67

Exc. 1365 Cu. Yds.
Emb. 1012 "
Excess 20%

Exc. 1417 Cu. Yds.
Emb. 1134 "
Excess 20%

Exc. 2957 Cu. Yds.
Emb. 885 "
Excess 20%
* Includes 106 Cu. Yds. for approach grade East of South

1350.0
1340.0
1330.0
400' V.C.
1.38%
200' V.C.
E. 1334.25
Crown grade 1332.69
E. 1330.09
1.167%
200' V.C.
1.600%
200' V.C.
E. 1338.4
Crown grade 1341.15
E. 1338.65
1.500%
200' V.C.
1.867%
200' V.C.
Identical P.I.'s
Crown grade 1345.15
Lt.
Rt.
1.325%
1350.0
1340.0
1330.0

23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55

PLAN
SURVEYED
DRAWN
NOTE BOOK
NO.
CHECKED
ALIGNMENT CHECKED
R/W MONUMENTED
STRUCTURE NO. & PINS ON NO.
RT. OF WAY CHECKED

PROFILE
SURVEYED
DRAWN
NOTE BOOK
NO.
CHECKED
G.E. MONUMENTED
STRUCTURE NO. & PINS ON NO.

DATE
BY
Road Restored

PLATE 2-PLAN-PROFILE O.P.R. & R.E. STANDARD