



For Information Only

MINIMUM BUILDING PAD ELEVATION FOR LOWEST OPENING INTO STRUCTURES		
BLOCK	LOT NO.	ELEVATION (N.A.V.D. 88)
9	1, 2, 3, 4, 5, 6, 7, 8	1363.5

**Benchmark**

BENCHMARK:  
POINT #30  
CHISELED SQUARE ON THE TOP OF CURB ON THE SOUTH SIDE OF AUTUMN RIDGE, 98' EAST OF THE EAST LINE OF CHERYL'S HOLLOW 2ND ADDITION.  
ELEVATION = 1364.26 (NAVD88)

BENCHMARK:  
POINT #31  
CHISELED SQUARE ON THE TOP OF CURB AT THE WEST CURB RETURN AT THE NORTHWEST CORNER OF HUNTER'S VIEW AND STOUT.  
ELEVATION = 1364.76 (NAVD88)

**Legend**

- (L) : Garage Left Required
- \* : Rear yard must be graded to drain to low corner

**Cheryl's Hollow, 2nd Addition  
Four-Corner Grading**

**RUGGLES & BOHM**

ENGINEERING | SURVEYING | LANDSCAPE ARCHITECTURE | GOVERNMENT

924 NORTH MAIN WICHITA, KANSAS 67203 P (316) 264-8008 F (316) 264-4621  
WWW.RUGGLESANDBOHM.COM

DATE

DESIGN  
KWL

DRAWN  
CDJ

REVIEW

SHEET

PROJECT NUMBER <b>472-84412</b>	RB JOB NO. <b>4731E</b>	DWG. SCALE <b>40</b>	<b>22</b>
DRAWING FILE <b>10 - Four-Corner Grading Plan [Four-Corner Grading]</b>			