


# Hydraflow Plan View



# Storm Sewer Summary Report

Line No.	Line ID	Flow rate (cfs)	Line size (in)	Line length (ft)	Invert EL Dn (ft)	Invert EL Up (ft)	Line slope (%)	HGL down (ft)	HGL up (ft)	Minor loss (ft)	HGL Junct (ft)	Dns line No.
1		26.10	36 c	164.6	1250.00	1250.49	0.300	1251.88	1252.37	n/a	1252.71 i	End
2		23.85	36 c	33.1	1250.49	1250.59	0.299	1252.71	1252.75	0.40	1253.15	1
3		21.60	36 c	29.4	1250.59	1250.68	0.300	1253.27	1253.29	0.26	1253.55	2
4		14.70	24 c	144.3	1251.68	1252.11	0.300	1253.68*	1254.29*	0.48	1254.77	3
5		12.25	24 c	27.9	1252.11	1252.20	0.301	1254.88*	1254.96*	0.12	1255.08	4
6		9.80	24 c	203.6	1252.20	1252.81	0.300	1255.16*	1255.54*	0.18	1255.72	5
7		6.50	18 c	37.7	1253.31	1253.42	0.302	1255.72*	1255.87*	0.21	1256.08	6
8		3.40	15 c	342.9	1253.67	1254.79	0.325	1256.17*	1257.12*	0.12	1257.24	7
9		3.10	15 c	292.9	1253.67	1254.62	0.325	1256.19*	1256.86*	0.05	1256.91	7
10		2.00	15 c	229.6	1254.62	1255.37	0.325	1256.97*	1257.19*	0.04	1257.23	9
11		5.50	18 c	259.1	1252.18	1252.96	0.300	1253.57	1254.19	0.24	1254.43	3
12		4.60	15 c	258.4	1253.21	1254.05	0.325	1254.46*	1255.77*	0.33	1256.10	11
13		2.90	15 c	127.0	1254.05	1254.46	0.324	1256.23*	1256.49*	0.09	1256.57	12

sws2_RW	Number of lines: 13	Run Date: 04-23-2007
---------	---------------------	----------------------

NOTES: c = cir; e = ellip; b = box; Return period = 10 Yrs. ; \*Surcharged (HGL above crown). ; i - Inlet control.

# Inlet Report

Line No	Inlet ID	Q = CIA (cfs)	Q carry (cfs)	Q capt (cfs)	Q byp (cfs)	Junc type	Curb Inlet		Grate Inlet			Gutter						Inlet			Byp line No	
							Ht (in)	L (ft)	area (sqft)	L (ft)	W (ft)	So (ft/ft)	W (ft)	Sw (ft/ft)	Sx (ft/ft)	n	Depth (ft)	Spread (ft)	Depth (ft)	Spread (ft)		Depr (in)
1		2.25*	0.00	2.25	0.00	Curb	6.0	10.00	0.00	0.00	0.00	Sag	2.00	0.080	0.030	0.000	0.27	5.71	0.34	5.71	2.00	Off
2		2.25*	0.00	2.25	0.00	Curb	6.0	10.00	0.00	0.00	0.00	Sag	2.00	0.080	0.030	0.000	0.27	5.71	0.34	5.71	2.00	Off
3		1.40*	0.00	1.40	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.11	9.64	0.11	9.64	0.00	Off
4		2.45*	0.00	2.45	0.00	Curb	6.0	10.00	0.00	0.00	0.00	Sag	2.00	0.080	0.030	0.000	0.28	6.05	0.35	6.05	2.00	Off
5		2.45*	0.00	2.45	0.00	Curb	6.0	10.00	0.00	0.00	0.00	Sag	2.00	0.080	0.030	0.000	0.28	6.05	0.35	6.05	2.00	Off
6		3.30*	0.00	3.30	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.20	15.54	0.20	15.54	0.00	Off
7		0.00	0.00	0.00	0.00	MH	0.0	0.00	0.00	0.00	0.00	Sag	0.00	0.000	0.000	0.000	0.00	0.00	0.00	0.00	0.00	Off
8		3.40*	0.00	3.40	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.21	15.82	0.21	15.82	0.00	Off
9		1.10*	0.00	1.10	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.10	8.51	0.10	8.51	0.00	Off
10		2.00*	0.00	2.00	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.15	11.70	0.15	11.70	0.00	Off
11		0.90*	0.00	0.90	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.09	7.69	0.09	7.69	0.00	Off
12		1.70*	0.00	1.70	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.13	10.70	0.13	10.70	0.00	Off
13		2.90*	0.00	2.90	0.00	DrGrt	0.0	0.00	8.00	4.00	2.00	Sag	2.00	0.030	0.030	0.000	0.19	14.42	0.19	14.42	0.00	Off

sws2\_RW Number of lines: 13 Run Date: 04-23-2007

NOTES: Inlet N-Values = 0.016 ; Intensity = 88.24 / (Inlet time + 15.50) ^ 0.83; Return period = 10 Yrs. ; \* Indicates Known Q added

# Hydraulic Grade Line Computations

Line	Size (in)	Q (cfs)	Downstream								Len (ft)	Upstream								Check		JL coeff (K)	Minor loss (ft)
			Invert elev (ft)	HGL elev (ft)	Depth (ft)	Area (sqft)	Vel (ft/s)	Vel head (ft)	EGL elev (ft)	Sf (%)		Invert elev (ft)	HGL elev (ft)	Depth (ft)	Area (sqft)	Vel (ft/s)	Vel head (ft)	EGL elev (ft)	Sf (%)	Ave Sf (%)	Enrgy loss (ft)		
1	36	26.10	1250.00	1251.88	1.88	4.66	5.60	0.49	1252.37	n/a	165	1250.49	1252.37	1.87	4.64	5.63	0.49	1252.86i	n/a	n/a	-0.001	0.89	n/a
2	36	23.85	1250.49	1252.71	2.22	5.60	4.26	0.28	1252.99	0.159	33.1	1250.59	1252.75	2.16	5.44	4.39	0.30	1253.05	0.170	0.165	0.055	1.35	0.40
3	36	21.60	1250.59	1253.27	2.68	6.66	3.24	0.16	1253.43	0.093	29.4	1250.68	1253.29	2.61	6.53	3.31	0.17	1253.46	0.096	0.094	0.028	1.50	0.26
4	24	14.70	1251.68	1253.68	2.00*	3.14	4.68	0.34	1254.02	0.423	144	1252.11	1254.29	2.00	3.14	4.68	0.34	1254.63	0.422	0.423	0.610	1.41	0.48
5	24	12.25	1252.11	1254.88	2.00	3.14	3.90	0.24	1255.11	0.293	27.9	1252.20	1254.96	2.00	3.14	3.90	0.24	1255.19	0.293	0.293	0.082	0.50	0.12
6	24	9.80	1252.20	1255.16	2.00	3.14	3.12	0.15	1255.31	0.188	204	1252.81	1255.54	2.00	3.14	3.12	0.15	1255.69	0.188	0.188	0.382	1.19	0.18
7	18	6.50	1253.31	1255.72	1.50	1.77	3.68	0.21	1255.93	0.383	37.7	1253.42	1255.87	1.50	1.77	3.68	0.21	1256.08	0.383	0.383	0.145	1.00	0.21
8	15	3.40	1253.67	1256.17	1.25	1.23	2.77	0.12	1256.29	0.277	343	1254.79	1257.12	1.25	1.23	2.77	0.12	1257.24	0.277	0.277	0.951	1.00	0.12
9	15	3.10	1253.67	1256.19	1.25	1.23	2.53	0.10	1256.29	0.231	293	1254.62	1256.86	1.25	1.23	2.53	0.10	1256.96	0.230	0.231	0.675	0.50	0.05
10	15	2.00	1254.62	1256.97	1.25	1.23	1.63	0.04	1257.01	0.096	230	1255.37	1257.19	1.25	1.23	1.63	0.04	1257.23	0.096	0.096	0.220	1.00	0.04
11	18	5.50	1252.18	1253.57	1.38	1.70	3.23	0.16	1253.73	0.238	259	1252.96	1254.19	1.24	1.56	3.53	0.19	1254.39	0.272	0.255	0.660	1.24	0.24
12	15	4.60	1253.21	1254.46	1.25*	1.23	3.75	0.22	1254.68	0.508	258	1254.05	1255.77	1.25	1.23	3.75	0.22	1255.99	0.507	0.508	1.312	1.50	0.33
13	15	2.90	1254.05	1256.23	1.25	1.23	2.36	0.09	1256.32	0.202	127	1254.46	1256.49	1.25	1.23	2.36	0.09	1256.57	0.202	0.202	0.256	1.00	0.09

sws2\_RW


Number of lines: 13

Run Date: 04-23-2007

Notes: \* Normal depth assumed.

# Storm Sewer Profile

Elev. (ft)



# Storm Sewer Profile

Elev. (ft)

