



S.M. 1997 S.E. Cor. Cane porch No. 828 FARMSTEAD
 S.M. 1974 S.E. Cor. Cane porch No. 828 FARMSTEAD

SCALE 1"=40'

SHOW EXISTING
 CHAIN
 11/15/20

BILL of MATERIALS		
635	30 yds	Asphaltic Concrete Pavt
375	Lin ft	Key Joint
375	Lin ft	Comb. Curb & Gutter
1695	Lbs	Rein. Steel
835	30 yds	Pav't Removed
		Driveways (est. assumed)
		Excavation (est. assumed)
		Subgrade

CURVE DATA IS BASED ON CENTER LINE RADIUS = 100.00'
 3° 05' 15" 00" 10.2330 Sta / 11 Arc

STATION	ARC	CHORD	LENGHTS	DEFLECTION	TOTAL DEFLECTION
PC 11.00				0° 00' 00"	0° 00' 00"
11.25	25.00'	21.50'	25.00'	4° 15' 47"	4° 15' 47"
11.50				8° 31' 34"	8° 31' 34"
11.75				12° 47' 21"	12° 47' 21"
12.00				17° 03' 08"	17° 03' 08"
12.25				21° 18' 55"	21° 18' 55"
12.50				25° 34' 42"	25° 34' 42"
12.75	25.00'	21.50'	25.00'	29° 50' 29"	29° 50' 29"
PT 21.50.30	10.50'	9.95'	11.00'	34° 06' 15"	34° 06' 15"

* QUANTITY OF DAVEMENT REMOVED
 IN THE BILL OF MATERIALS IS INDICATED
 BY CROSS HATCHING.



NOTE: Any excess of suitable excavation
 is to remain as gravel for parking fill.

NOTE TO CONTRACTOR
 This project will be constructed under
 the supervision of the CITY ENGINEER
 and conforming to the SPECIFICATIONS
 of the CITY OF WICHITA. The CON-
 TRACTOR will reimburse the City of
 Wichita for all cost of Engineering, Plans,
 and Inspection.

The exact limits of combined curb & gutter
 removed to be determined by the engineer,
 consistent with existing utility locations.
 Existing base pavement is to be saved
 and matched.

Relocation of FARMSTEAD STREET
 in connection with OLDE ENGLISH
 MANOR - ADDITION.
 26'-2"-30" ASPH - CONC
 CITY OF WICHITA, KANSAS
 R.W. LINN CITY ENGINEER
 Date MAY 1972 Private Proj AAKB502008