


STORM WATER SEWER NO. 167

GENERAL NOTES

- CONTRACTOR SHALL COORDINATE WORK WITH PAVING AND SANITARY SEWER CONTRACTORS, AND CONTACT RELEVANT UTILITY COMPANIES AND OTHER AGENCIES INVOLVED WITH THE FINE ARTS OF THIS PROJECT SITE DEVELOPMENTS.
- FIELD ENGINEER SHALL TAKE NOTES ON ALL TRENCHES AND TRENCHES IN THE PROJECT AREA PRIOR TO CONSTRUCTION. FIELD ENGINEER SHALL REPLACE ALL SUCH TRENCHES AND TRENCHES DISTURBED DURING CONSTRUCTION.
- FIELD ENGINEER SHALL TAKE NOTES ON THE PLANS MAY VARY FROM PROPOSED PAVING PLANS. THE FIELD ENGINEER SHALL LOCATE CURB INLETS WITH REFERENCE TO PROPOSED PAVING PLANS OF THE PERTINENT STREETS.
- ALL CURB INLETS SHALL HAVE A MINIMUM DIAMETER SHALL HAVE HELICALLY CORRUGATIONS. ALL SUCH PIPES FOR SIZES AND CARRIER DIAMETER SHALL HAVE FULLY PAVED (FP) SMOOTH FLOW INTERIORS.
- ALL CONCRETE SHALL BE "B-SACK CONCRETE" UNLESS OTHERWISE NOTED.
- FOR EACH DOWNSTREAM FROM END SECTION, ADD FOR RIP-RAP SHALL BE PAID FOR IN ITEMS BID FOR PIPES AND/OR RIP-RAP.
- TREES TO BE REMOVED ARE MARKED WITH "X" EXCEPT THAT ANY TREE MARKED FOR REMOVAL WHICH IN THE OPINION OF THE ENGINEER CAN BE SAVED, SHALL BE SAVED.
- END SECTIONS AT PIPE OUTFALL SHALL BE CONSTRUCTED TO ALIGN WITH THE SLOPE OF BANKS IN ORDER THAT PROTRUSION IS MINIMUM. WHERE SUCH PROTRUSION CANNOT BE AVOIDED, FILL AROUND THE END-SECTION AT APPROXIMATELY 5:1 SIDE SLOPE SO IT APPEARS ENTIRELY RECESSED.
- CONTRACTOR SHALL HAVE THE OPTION TO INSTALL PRE-CAST TYPE I-A CURB INLET IN LIEU OF THE BRICK TYPE CONSTRUCTION, SEE STANDARD DETAIL PRE-CAST TYPE I-A INLET DATED AUGUST, 1973.
- CONTRACTOR SHALL AVOID UNCOVERING EXISTING WATERLINES UNLESS ABSOLUTELY NECESSARY. UNCOVERING SHALL BE DONE ONLY IN THE PRESENCE OF A WATER DEPARTMENT ENGINEER.



Scale: 1" = 160'

BENEFIT DISTRICT

THE SOUTH ONE THOUSAND TWENTY (1020) FEET OF SPECIAL ED ADDITION: AN UNPLATTED TRACT OF LAND IN THE NORTHEAST QUARTER SECTION 21, TOWNSHIP 27 SOUTH, RANGE 1 WEST MORE FULLY DESCRIBED AS BEGINNING AT THE SOUTH-EAST CORNER OF SPECIAL ED ADDITION; THENCE NORTH ALONG THE EAST LINE OF SAID ADDITION A DISTANCE OF ONE THOUSAND TWENTY (1020) FEET; THENCE SOUTHEASTERLY TO A POINT ON THE NORTH LINE OF SECOND STREET SAID POINT BEING FIVE HUNDRED SIXTY-FIVE (565) FEET EAST OF THE SOUTHEAST CORNER OF SPECIAL ED ADDITION; THENCE WEST ALONG NORTH LINE OF SECOND STREET TO POINT OF BEGINNING; ALL LOTS AND BLOCKS IN GLENEAGLES 2ND ADDITION.

INDEX	
1	COVER SHEET
2-9	PLAN-PROFILE SHEETS
10	CURB INLET STANDARD SHEET



DEAN SELLERS ACTING CITY ENGINEER


CITY OF WICHITA, KANSAS

Proj. NO. 468-76-245-80801-000-000-001



DATE:








60-55N



① Rev. (Add 2 Curb Inlets) 7-11-80

SWS #167 sheet 3 of 10

 $\frac{7}{9}$



B.M. = 145.52 iron @ MUIRFIELD & DOUGLAS
 B.M. = 141.103 WOODCHUCK & MAPLE, City Sid 52'S & 32'W of
 @ Both
 B.M. = 144.963 Ridge Rd. & 2nd ST. N., City Sid. 39.50' N. & 48' W
 of @ Both

