STATE OF KANSAS

STATE HIGHWAY COMMISSION

PROJECT 35W-87I-35W-1(25)50

INDEX OF SHEETS
See Sheet No 2

Br. No. 35W-87-18.31

Br. No. 35W-87-18.18

Br. No. 35W-87-18.09

Br. No. 35W-87-17.79

PLAN AND PROFILE OF PROPOSED

STATE HIGHWAY

FEDERAL AID PROJECT

SEDGWICK COUNTY
INTERSTATE 35W
ACCESS CONTROL

TRAFFIC CENSUS 2[illegible] VEHICLES PER DAY [illegible]

35W-87-25.62

35W-87-25.66

BEGIN Proj. 35W-87I-35W-1(25)50 PART II

PRELIMINARY DRAWING

Br. No. 35W-87-25.92

Br. No. 35W-87-25.87

END Proj. 35W-87I-35W-1(25) 50 PART II

END Proj. 35W-87I-35W-1(25)50 PART I

BEGIN Proj. 35W-87I-35W-1(25)50 PART II

Br. No. 35W-87-18.11

Br. No. 35W-87-19.80

WILSON & COMPANY ENGINEERS

CONVENTIONAL SIGNS

COUNTY LINE	RETAINING WALL		
CITY, VILLAGE OR BOROUGH	BASE OR SURVEY LINE		
STATE OR NATIONAL LINE	LEVEE		
TOWNSHIP LINE	CULVERTS		
SECTION LINE	DROP INLETS		
GRANT LINE	TROLLEY POLE		
FENCE LINE	POWER LINE		
BOARD FENCE	TELEPHONE OR TELEGRAPH LINE		
UNFENCED PROPERTY	MARSH		
RIGHT OF WAY LINE	HEDGE		
TRAVELLED WAY	TREES		
RAILROADS	GRADE ELEVATION		
ACCESS CONTROL	CITY LIMITS		

GROSS LENGTH OF PROJECT

EXCEPTIONS

ADDITIONS

NET LENGTH OF PROJECT [illegible] MILES

NET LENGTH OF BRIDGES [illegible] MILES

NET LENGTH OF ROAD [illegible] MILES

ENGINEER OF DESIGN STATE HIGHWAY COMMISSION	ENGINEER BUREAU OF PUBLIC ROADS DEPARTMENT OF COMMERCE
STATE HIGHWAY ENGINEER STATE HIGHWAY COMMISSION OF KANSAS	DISTRICT ENGINEER BUREAU OF PUBLIC ROADS DEPARTMENT OF COMMERCE

FUR. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-0373(4) - 265 EC	1975	19	19

Sta 5+20 Ramp D Constr
Grate Inlet 80 Ft
D.A. = 1.3 Q= 5 cfs
L.F. = 0.5 H.W. =

Sta 5+20 Ramp D Constr
Grate Inlet 60 Ft
D.A. = 2.5 Q= 7 cfs
L.F. = 0.5 H.W. =

Sta 336+60 Constr.
18'x 14' RCB
D.A. 835 Ac Q_{50} = 1438 cfs
H.W. = 16.3'
See Sheet No

WARNALL AVE.

CHIPP AVE.

DAVIDSON AVE.

CLEVELAND AVE.

Scale: 1"=100'

DERBY

REFINING

COMPANY

TRAFFIC FLOW DIAGRAM
Dec. 1975

Sta 15+80 Ramp B Install
18" x CRP 1 End Sect
D.A. = 4.5 AC Q_{25} ECB
L.F. = 0.6 H.W. = 1.1

Sta 17+30 Ramp C & D Constr.
Dbl. 14'x14' RCB. Bridge
D.A. = 6.66 Ac Q_{50} = 3162 cfs
H.W. = 11.9
See Sheet No

Sta 14+60 Ramp A Install
24" x x CRP 1 End Sect
D.A. = 1.5 Q_{25} = 5 cfs
L.F. = 0.8 H.W. = 1.1

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

FAI 135 W

21ST STREET INTERCHANGE

LAYOUT A

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA, KANSAS

DESIGNED RLD | TRACED DL | CHECKED

P.O.T. Ref. Sta 340+76.14
1.
2. 02.60' S. Spike in 70" Elm.
3. 77.40' S.S.W. Spike in 40" Elm.
4. 47.75' N. Spike in top Fence Post.

Curve Data
Δ = 30° 27' 55"
D_c = 2°00'
L_s = 200'
L_c = 1323.27'
T_t = 880.29'
E_s = 104.92'
X_c = 199.98'
Y_c = 2.33'
θ_s = 1°00'
T.S. = Sta 343+80.07
S.C. = Sta 345+80.07
C.S. = Sta 359+03.34
S.T. = Sta 361+03.34

P.O.S.T. Ref. Sta 346+22.70
1.
2. 28.60' S. Spike in Power Pole.
3. 59.37' N.N.W. Spike in Power Pole.
4. 62.20' S.S.W. Spike in top Fence Post.

P.I. Ref. Sta 352+60.36
1.
2. 68.56' N.W. Spike in Telephone Pole.
3. 07.85' N. to E. Rail
4. 07.80' E. to W. Edge of Tanks.
5. 40.90' N.W. to End of Fence.

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-871-35W -1-22152	1959	7	

Sta. 343+11± END P.I.E. BEGIN Project 35W-871-35W-1(22152)
E.W.T.
Should Limited Access Owned Under Bridge?
Warehouse
Metal Building
Kansas Texas Oil Co.
Tank Storage Area
Engineering Building
Derby Oil Co.
Lumber Yard
Concrete Slab
Drainage Basin
Concrete Foundation
2'x3' Drainage Basin
Industrial Sewer
Conduit Box
Water Meter
Guard Rail
Guard Posts
Guard Roof Sewer Vent
Head Box Curb Inlet
Elev. 1308.9
Elev. 1314.9
Elev. 1319.4
Exist. 2-19" CMP
12"-15"-40' (MINIMUM)
Ohio St. (Construction)
STREET
Bridge
Tank
Stacks
Tank Area
(R/W?)
(R/W-50')
(L.A.=50')
345
350
355
340
SECTION A-A
D: 11.5', n: .013, S: .001'/'
A: 355.6 sq. ft. R: 6.42 ft. V: 10.10'
V: 9.77', Q: 3590 cu. ft. (50%)
BM #23 3/4" Iron Bar Sta 345+20 - 926' Rt. Elev. 1307.49
BM #24 3/4" Iron Bar Sta 348+20 - 225' Lt. Elev. 1310.90

Scale 1" = 50'

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA. 340+00 - STA. 355+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA, KANSAS

DESIGNED | TRACED | CHECKED


P.O.S.T. Ref. Sta 357+05.66
1.
2. 39.63' N. to Spike in Telegraph Pole.
3. 32.57' S.W. to Spike in Telegraph Pole.
4. 55.31' W. to top of Fence Corner.

P.O.T. Ref. Sta. 365+27.98 ℄ Dike
1. 3/8" Iron Bar
2. 17.15' N.W. to S.E. Cor. of Bldg.
3. 30.22' N. to T-Rail.

Curve Data
Δ = 5°21'49"
D_c = 1°00'
T = 268.38'
L = 536.36'
E = 6.28'
P.C. = Sta 367+12.13
P.T. = Sta 372+48.49

P.I. Ref. Sta 369+80.51
1. 3/8" Iron Bar
2. 22.62' W. Spike in Power Pole.
3. 40.19' N.N.W. Spike in 30" Tree.
4. 76.35' E. Spike in Telegraph Pole.

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-677-35W -1-1(29)30	1959	9	



BM # 25 3/4" Iron Bar
Sta 364+07 - 164' L.T.
Elev. 1311.52

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA. 355+00 - STA. 370+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA, KANSAS

DESIGNED | TRACED | CHECKED

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	95W-157-35K J-165-55	1953	11	

P.O.T. Ref. Sta 373+72.98 ℄ 25th St.
1. 3/8" Iron Bar
2. 46.65' SE. Spike in top of Fence Post.
3. 40.40' SW. Spike in Power Pole.
4. 37.82' NW. Spike in Power Pole.

CRI&P RR.

ST.

6" Industrial Sewer

Wooden Bridge & Fence Opening

North Wichita Drainage Canal

S.L. & S.F. Ry.

WASHINGTON AVE.

Industrial Sewer

MH

3" Abandoned G

Oil

House

Proposed Install 36" x [illegible] CMP Culvert

D.A. 8.2 Sq. Mi.
C.F. 0.5
H.W. 2.5

Irrigation Pipe Line

25TH ST.

24"x30" CMP

WABASH AVE.

Street

Church

Sewer Pipeline Co.

Drain

Switch Box

Concrete Bldg.

Culvert box

CRI&P RR.

OHIO AVE.

26TH ST.

PRELIMINARY DRAWING

NO	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA 370+00 - STA. 385+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA KANSAS

DESIGNED | TRACED | CHECKED

KD-278

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-81F-33K (-1651-50)	1959	20	27

Sta 4+60 25th St Const
50' Bottom Paved Ditch 2:1 SS
Under Bridge
D.A.: 852 Ac. Q=1030 cfs
L.F. 1.0 H.W.: 3.5

Sta 5+50 Ramp C Const
24' Bottom Pave'd Ditch 2:1 SS
Under Bridge
D.A.: 852 Ac. Q=1030 cfs
L.F. 1.0 H.W.: 3.5

Sta 4+60 25th St Const
5'x4' RCB
D.A.: 32 Ac Q=70 cfs
L.F. 1.0 H.W.: 3.0

Sta 10+50 Ramp D Const
Paved Ditch 2:1 SS
Under Bridge
D.A.: 4.5 cfs
L.F. = H.W.: 4.0

Sta 10+50 Ramp D Const
10' Bottom Paved Ditch
2:1 SS
D.A.: 284 Ac. - 260 cfs
L.F. 1.0 H.W. 3.8

"50' Bottom Ditch
2:1 SS
S= 0.0025'

Mainline Curve Data
Δ: 5°21'28.86"
D: 1°00'
T: 268.38
L: 536.36
E: 6.28
Rc: 5729.12.18
R: 5721.55.95

Sta 7+50 Ramp B Install
30'x ' x CRP & end Sect
'L'
D.A.: 6 Ac Q= 69 cfs
L.F.: 0.8 H.W.: 2.4

Sta 7+50 Ramp B Install
30'x ' x CRP & end Sect
'L'

Sta 10+50 Const
6'-10'x4' RCB
D.A. 40 Ac Q 576 cfs
L.F. 1.0 H.W.: 4.7

Sta 16+00 Frontage Road Install
36" x CRP & End Sect.

Mainline Curve Data (℄)
Δ: 46° 33' 22.37"
D: 5°00'
Ls: 300'
Lc: 1251.88'
Ts: 972.54'
Rc: 1145.91'
Ys: 26.21'
θs: 8° 30'
T.S.: 378+91.79
S.C.: 382+91.79
C.S.: 395+43.67
S.T.: 398+43.67
S.E.: 0.0774 ft/ft

Note: All turns are AASHO C-03

PRELIMINARY DRAFTING

NO	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PRELIMINARY LAYOUT SKETCH

25TH STREET INTERCHANGE

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA, KANSAS

DESIGNED LCT | TRACED LCT | CHECKED

P.I. Ref. Sta 389+64.34
1. 3/8" Iron Bar
2. 54.00' S.E. to N.W. Cor. of House.
3. 36.65' N. to S.E. Cor. of Hog House.
4. 15.50' S.W. to Cor. of Shed.

Curve Data
$\Delta = 46°33'23"$
$D_c = 3°00'$
$L_1 = 300'$
$L_c = 1251.88'$
$T_c = 972.54'$
$E_s = 171.40'$
$X_c = 299.81'$
$Y_c = 7.85'$
$\theta_s = 4°30'$
T.S. = Sta 379+91.79
S.C. = Sta 382+91.79
C.S. = Sta 395+43.67
S.T. = Sta 398+43.67

P.O.S.T. Ref. Sta 395+41.03
1. 1/2" Iron Bar
2. 69.00' N.W. to top of Cor. Post. (Steel)
3. 63.00' S.W. to top of Cor. Post. (Steel)
4. 53.15' S.S.E. to Spike in Power Pole.

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-87-35W 1-1-1251-30	1959	13	

S.L. & S.F. R'Y

Wabash Bridge Co.

Cultivated

Frontage Road & 115' R/W

ERW 165'

WABASH

OHIO

PRELIMINARY DRAWING

BM #26 3/4" Iron Bar
Sta 391+38-540' Lt.
Elev. 1315.26

BM #30 3/4" Iron Bar
Sta 391+45-280' Rt.
Elev. 1312.87

Large Trees to be Grubbed
Sta 385+00 to Sta 400+00
4-40", 1-60"
All trees to be Grubbed
are Marked Thus ✲
Total 5

Scale 1"=50'

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA 385+00 - STA 400+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA KANSAS

DESIGNED | TRACED | CHECKED

HOLLINGSWORTH - TENNILL, INC. — ATLANTA — WEST IMPERIAL CLOTH

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-87-1, 35W-11-22) 50	1959	15	

P.O.T. Ref. Sta. 406+05.73
1. 3/8" Iron Bar
2. 64.32' W. Spike in top of Fence Post.
3. 98.10' E. Spike in top of Fence Post.
4. 52.12' S. Spike in Telephone Pole.

T.S. Ref. Sta. 408+27.69
1. 3/8" Iron Bar 12" Deep.

Sta. 48+70 29th St. Install
48" x 136" CMP Rdwy. 43° 22'
2 End Sections
51' Lt 135' Rt
D. A. 25 Ac Q. 76 cfs
L.F. = 1.0 H.W. 4.0

Myrtle S. Lee

Bridge No. 35W-87-1311
Sta. Sheet No.

TWENTY-NINTH

T.S. Sta. 408+27.69

S.T.S. Sta. 410+27.69

R/W

O.B.L. & E.E.

Frontage Road & 115' R/W

165' R/W

150' Rt

+60 155'

E.I.B.L. E.E.
Cultivated

City Service

STREET

Guard Rail

Gas Valves

+30 150'

Oakland Inc.

PRELIMINARY DRAWING

BM #31 3/4" Iron Bar
Sta 410+70 - 434' Rt.
Elev. 1317.91

Scale : 1" = 50'

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA 400 + 00 - STA 415 + 00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA KANSAS

DESIGNED | TRACED | CHECKED

FED. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-87(25M)-1(65)20	1959	12	37

PLAN

PROFILE

Sta 14+00 BEGIN Constr.

Sta 50+00 Constr.
Bridge No. 35W-87-18.71
58'-100'-100'-58' Cont. Reinf. Conc.
Box Girder Spans 28' Roadway
See Sheet No.

Sta 50+00 29th St
= Sta 405+64.46 Ahd

Sta 54+00 29th St 40' Lt
Install 24"x38' SRP
Rotate 30° Lt

Sta 56+00 29th St Constr.
3-6'x5'x53' RCB
D.A. = 375 Ac Q = 360 cfs
C.F. = 0.8 H.W. = 4.8
See Sheet No

Sta 570+00 END Constr.

PRELIMINARY DRAWING

Wheat

Cultivated Field

House

OHIO

29TH ST.

City Service

Gas Meters
Guard Rail

Cattle Guard

Fence

Center Line

W & C-E

E/W

136° 38' 05"

Top Of Rt

3' Of Lt

3' Of Rt

PT = 00
El 1332.275

900' V.C.
NPSD 350'

300' V.C.

200' V.C.

+4.95%

-5.65%

0.00%

+0.2% Lt

+0.20% Rt

-0.15% Lt

Existing Ground Line

El Lt 12.5

El Lt 14.0

El Rt 12.35

El Rt 13.23

Sl = 1355

PC +50
El 1315.15

PT +50
El 1318.95

PC +50

PT

PVC

PRC

PT +50

PRT +50

Cr. Gr. El Lt 1321.55
El Rt 1318.06

1330
1320
1310

41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57

1315.15 1318.95 1323.58 1327.53 1330.00 1332.33 1336.10 1338.69 1340.11 1340.35 1339.41 1337.29 1336.00 1329.53 1326.85 1324.98 1321.20

PLATE 1 PLAN PROFILE D.P. A. & B. E.
CHARLES BROWNE COMPANY, INC.

POST. Ref. Sta 418+63.45
1.
2. 36.50' N. to S.W. Cor. of Bldg. Remains.
3. 50.00' N.W. to 6" Hackberry Tree.
4. 09.55' N. to S. Edge of Foundation.

Curve Data PI Sta 423+05.95
$\Delta = 61°05'36"$
$D_c = 2°30'$ R = 2292.01'
$L_s = 250'$
$L_c = 2193.73'$
$T_c = 1478.26'$
$E_s = 370.67'$
$X_c = 249.93'$
$Y_c = 4.54'$
$\theta_s = 3°07'30"$
T.S. = Sta 408+27.69
SC = Sta 410+77.69
CS = Sta 432+71.42
ST = Sta 435+21.42
SE = 0.06'/ft

P.I. Ref. Sta 423+05.95
1. 3/8" Iron Bar
2. 96.10' S.E. to Telegraph Pole.
3. 64.85' N.W. Spike in Telephone Pole.
4. 109.65' S.W. Spike in Telephone Pole.

P.O.S.T. Ref. Sta. 423+86.67
1. 3/8" Iron Bar
2. 26.05' S. Spike in Hedge Stump.
3. 03.00' E. to N-S. Hedge.
4. 19.98' N. to Spike in 12" Hedge.

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-871-35W -1-1051-00	1959	17	

Sta 415+50 Const
Type II Inlet on ℄
Install 18' x 72" C.R.P.
See Sheets No

Sta 422+00 Const
Type II Inlet on ℄
Install 18' x 72" C.R.P.
See Sheets No.

Sta 428+50 Const
Type II Inlet on ℄
Install 18' x 72" C.R.P.
See Sheets No.

Cultivated

Clark Land Inc

Cultivated

F.L. Outlet
1314.55

F.L. Outlet
1315.66

F.L. Outlet
1316.76

Invert El
1315.14

Invert El
1316.44

Invert El
1317.58

415 16 7 8 9 420 1 3 4 425 6 7 8 9 430

N.W. 143.57 ℄

Cultivated

R/W = 15' from ℄

City Services

10"

40'

Nat. Gas Boost Sta.

HYDRAULIC

AVE.

PI Sta 423+05.95 Back
= Sta 420+43.16 Ahead

BM #27 3/4" Iron Bar
Sta 418+04 - 99' Rt.
Elev. 1319.64

BM #32 3/4" Iron Bar
Sta 422+85 216' Rt.
Elev. 1319.70

Scale 1" = 50'

NO.	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA. 415+00 - STA. 430+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA KANSAS

DESIGNED | TRACED | CHECKED


PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	KANSAS	35W-81(-35)-1-125,30	1959	19	

S.T. Ref. Sta 435+21.42
1. 3/8" Iron Bar
2. 56.65' S.S.W. Spike in top Fence Post.
3. 27.80' N.N.E. Spike in top Fence Post.
4. 61.90' N.W. Spike in Hedge Tree.

P.O.T. Ref. Sta 435+64.35
1. 3/8" Iron Bar
2. 31.88' W. Spike in Hedge Tree
3. 27.05' E.N.E. Spike in top Fence Post.
4. 34.15' E.S.E. Spike in top Fence Post.

Curve Data
Δ = 9°44'27"
D = 1°00'
T = 488.23'
L = 974.09'
E = 20.76'
P.C. = Sta 439+06.60
P.T. = Sta 448+80.69
R = 5729.65
S.E. 0.02'/ft.

P.I. Ref. Sta 443+94.83
3/8" Iron Bar 12" Deep



BM = 33 3/4" Iron Bar
Sta 435+46 - 66' Rt.
Elev. 1322.57

Large Trees to be Grubbed
Sta 430+00 to Sta 445+00
1-40"
All Trees to be Grubbed are Marked Thus ☒
Total 1

Scale 1"=50'

NO	DATE	REVISIONS	BY	APP'D
3				
2				
1				

STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA. 430+00 - STA. 445+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA, KANSAS

DESIGNED | TRACED | CHECKED

PUB. ROAD DIV. NO.	STATE	PROJECT NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
	KANSAS				

POT Ref Sta 453+86.43
1. 3/8" Iron Bar
2. 6.0' N. to E.W. Hedge
3. 18.05' N.W. Spike in Hedge Tree.
4. 25.20' N.E. Spike in Hedge Tree.

Sta 444+20 Ramp D Install
80' x 70' x CMP Cemt Sect
32 Lf 33 Rt
D.A.= 3.Ac Q= 13 cfs
L.F. 0.3 H.W.= 2.0

Sta 9+00 Ramp C Install
66" x 54" x CMP Cemt Sects.
57.6 Lf 18.6 Rt
D.A.= 3.15c Q= 13 cfs
L.F. = 0.8 H.W.= 1.0

Sta 5+50 Ramp B Install
24" x 80' x CMP Cemt Sects.
31 Lf 49' Rt
D.A.= 3.Ac Q= 13 cfs
L.F. = 0.8 H.W.= 1.5

Myra S. Lee

Myra S Lee

Sta 443+70 Const
Type III Inlet 17' Rt ℄
Install 1.5'-8' x 60' CRP(MAC)
See Sheets 11-5

FL Inlet 1321.72

FL Outlet 1320.55

+80.69 RW = 150' E

+25 RW = 165' E

+50 RW = 150' E

+50 RW = 190' E

+20 RW = 190' E

+25 RW = 190' E

N.T. Sta. 448+80.69

Ramp C

Ramp D

Ramp B

PRELIMINARY DRAWING NOT FOR CONSTRUCTION

B.M. #34 3/4" Iron Bar
Sta 449+25 - 266 Rt
Elev. 1322.96

Large Trees to be Grubbed
Sta 445+20 to Sta 460+00
28-42"; 18-50"; 4-60"; 5-70"; 4-80"; 1-90" & 1-130"
All Trees to be Grubbed are Marked Thus ✱
Total 55

NO	DATE	REVISIONS	BY	APP'D


STATE HIGHWAY COMMISSION OF KANSAS

PLAN

STA. 445+00 - STA. 460+00

WILSON & COMPANY
ENGINEERS & ARCHITECTS
SALINA KANSAS

DESIGNED	TRACED	CHECKED


Existing 22nd St
Main Access
Mesh alignment (Revised) Fig. 39 of
Aldrich Estates 89-101
Sheet 61

Traffic flow diagram
DHV 1975
3262
1212
5240