B. M. 97.18 "G" in Globe 1.1' E. of E. L. Magnolia N. curb 27th.

B. M. 98.15 "G" in Globe 1.8' E of E. L. Osage S. curb 27th

B. M. 101.67 S.E. cor. conc. porch on N.W. cor. Osage & 29th St.

NOTE:
Bid price of Pavement removed and replaced shall include saw joint.

NOTE TO CONTRACTOR:
Contractor shall excavate exist. sewer prior to construction so that Field Engr. may verify elev.

Sta. 3+15.0 Const. Std. M. H. Type A.

Sta. 6+32.62 Const. Std. M. H. Type "A". Install 6" stub S.W. For Bldg. 3.

NOTE: Replace Pavement and walk.

Exist. M.H. 98.58 C. Rim 90.61 F.In

27TH ST. SO.

Exist. Pavement

8" gas line

705.31

Exist. 8' Southwestern Bell Telephone Easement.

96.19'

Sta. 0+00.0 Const. Std. M. H. Typ. "A" over Exist. 12" San. Sewer.

94.6' T.V.E.

23.5'

Exist. M.H. 99.08 R. Rim 90.85 F.In

OSAGE

LOT 1, KINGSTON COVE SECOND ADDITION

Plan Scale 1" = 10'
Profile Scale 1" = 10' Horiz. 1" = 1' Vert.

NOTE TO CONTRACTOR:
Call Mr. Edwards for location of gas service leads south from 2" gas main in 27th St. So. PH: FO 3-7511 Ext. 268.

NOTE: Replace Pavement and walk

Sta. 0+00.0 Const. Std. M. H. Type "A" over Exist. 12" S. S.

Natural ground

Exist. S. ch. 27th St. So.

Sta. 3+15.0 Const. Std. M. H. Type "A".

Natural ground

Sta. 6+32.62 Const. Std. M. H. Type "A". Install 6" Stub S.W. For Bldg. 3.

8" V.C.P. @ 0.10% 8" V.C.P. @ 0.10%

90.37 Calc. F/o. Exist. 12" 90.12 F/I

90.82 90.92 91.02 91.04 F/I 91.12 91.22 91.32 91.35 F/o out 91.45 F/I in

632.62 lin. ft. of 8" V.C.P. @ 0.10% grade.

100 90

0 1 2 3 4 5 6

JAMES H. TANDY 2032 REGISTERED ENGINEER

B. E. SMITH 1969 REGISTERED ENGINEER

LAT. 15, SUBMAIN 4, S. S. NO. 22
CITY OF WICHITA, KANSAS
B. E. SMITH CITY ENGINEER
MAY 1969 PROJECT NO. C29-3

1 of 2

27TH. ST. SO.

Exist. Pavement

Fence

8" gas line

Sta. 6+32.63

Sta. 8+20.0 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg. D.

Sta. 10+98.58 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg. C.

Sta. 13+26.61 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg.

Sta. 14+71.63 Const. Sta. M.H. Type "A" Install 6" Stub SW For Bldg. A.

BLDG. B

Lowest Fl. Elev. 96.0

BLDG. D

Lowest Fl. Elev. 95.5

BLDG. C

Lowest Fl. Elev. 95.5

BLDG. A

Lowest Fl. Elev. 97.0

Fl. Elev. 100.0

LOT 2

KINGSTON COVE SECOND ADDITION

VALLEY

MIDLAND

Sta. 6+32.63

Fl. Bldg. "B" Elev. 99.0

Lowest Fl. Bldg. "B" Elev. 96.0

Sta. 8+20.0 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg. D.

Set top of M.H. @ 99.0

Exist. S. ch. 27th St. Co.

Natural ground

Lowest Fl. Elev. Bldg. "D" 95.5

Lowest Fl. Elev. Bldg. "C" 95.5

Sta. 10+98.58 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bld. C.

Set top of M.H. @ 97.0

Natural ground

Sta. 13+26.61 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg.

Set to of S.M.H. @ 96.0

Sta. 14+71.63 Const. Std. M.H. Type "A" Install 6" Stub S.W. For Bldg. "A".

Fl. Elev. Bldg. "A" 100.0

Lowest Fl. Elev. Bldg. "A" 97.00

8" V.C.P. @ 0.10% 8" V.C.P. @ 0.10% 8" V.C.P. @ 0.10% 8" V.C.P. @ 0.10%

91.45 Flo in 91.52 91.62 91.64 Flo 91.72 91.82 91.92 Flo out 98.08 Flo in 98.18 98.22 98.25 Flo out 98.55 Flo in 98.68 98.49 Flo

839.01 Lin. ft. of 8" V.C.P. @ 0.10% grade.

6 7 8 9 10 11 12 13 14

LAT. 15, SUBMAIN 4, S. S. NO. 22

PROJECT NO. C29-3

12