



TRANSITION FROM ROLL CURB TO FULL HEIGHT TO MATCH EXISTING.

CONSTRUCT VALLEY GUTTER PAVEMENT. 7" REINFORCED CONCRETE W/ 5" CRUSHED ROCK BASE AND MONOLITHIC EDGE CURB (3 5/8")

SAWCUT AND REMOVE 62 LF EXISTING CONCRETE CURB AND GUTTER

CONSTRUCT 5" ASPHALT CONCRETE PAVEMENT W/ 5" CRUSHED ROCK BASE

CONSTRUCT COMBINED ROLL TYPE CURB AND GUTTER (3 5/8") BOTH SIDES

CONSTRUCT 33 LF CONCRETE FLUME, W=2, WITH 6"x10" LIGHT STONE RIP RAP (6 S.Y.) SEE DETAIL THIS SHEET.

REMOVE 17 LF EXISTING 15" RCP AND REPLACE WITH 17 LF 24" RCP.

PLACE FILL FROM END OF FLUME TO BREAK LINE OF DITCH. SEE SECTION A-A FOR DETAIL. DO NOT CUT OVER GAS LINE!!

STA. 0+25, 19' RT. INSTALL SNS "Gilda"
Gilda Ct. (---)
*CONTRACTOR TO CALL 268-4276 FOR NUMBERS.

B.G.'S 1ST ADDITION GILDA CT. WICHITA, KANSAS		AML	346DE
Ruggles & Bohm, P.A. Engineering, Surveying, Land Planning		AMC	4
824 North Main Wichita, Kansas 67203 www.rbgkansas.com		AMU	11
(913) 264-6888 (913) 264-4821 fax E-mail: info@rbkansas.com		DATE	Mar. 2, 2010
PROJECT FILE Engineering Base {04 Gilda Ct.}	PROJECT NUMBER 472-64862		