



SCALE: 1" = 60'

REMOVE AND REPLACE 40 L.F. CONCRETE SIDEWALK (APPROXIMATE LENGTH & LOCATION)
 CONSTRUCT 91 S.F. CONCRETE SIDEWALK

REMOVE AND REPLACE 10 L.F. CONCRETE SIDEWALK (APPROXIMATE LENGTH & LOCATION)

STABILIZED CONSTRUCTION ENTRANCE

REMOVE AND REPLACE 40 L.F. CONCRETE SIDEWALK (APPROXIMATE LENGTH & LOCATION)

NOTE: IT IS THE CONTRACTOR'S RESPONSIBILITY TO MAINTAIN BMP'S ON SITE.

- LEGEND
- - - DITCH CHECK
 - - - CURB INLET PROTECTION
 - STRAW BALE BARRIER
 - - - SILT FENCE
 - - - CONSTRUCTION LIMITS

NOTE: ALL DISTURBED AREAS TO SEED AND MULCHED PER CITY OF WICHITA SPECIFICATIONS.

Crestlake
Erosion Control Plan
WICHITA, KANSAS



Ruggles & Bohm, P.A.
Engineering, Surveying, Land Planning
824 North Main
Wichita, Kansas 67203
www.rbkansas.com

(316) 284-8008
(316) 284-4621 fax
E-mail: info@rbkansas.com

DESIGN AML
DRAWN MLP
REVIEW
UTILITY
DATE May 24, 2006

DRAWING FILE
SS [EROSION CONTROL PLAN]

PROJECT NUMBER
472-B4406

SHEET
14
OF
40