

|        |             |      |           |              |
|--------|-------------|------|-----------|--------------|
| STATE  | PROJECT NO. | YEAR | SHEET NO. | TOTAL SHEETS |
| KANSAS | 472 84614   | :    | 74        | 534          |

| SEC/COR NO. | QUARTER CORNER LOCATION       | COORDINATES  |              | CORNER DESCRIPTION                    | STATION                            | OFFSET (FT)              | ANGLE                        | TIE | DISTANCE (FT) | DIRECTION    | TIE DESCRIPTION                                     |
|-------------|-------------------------------|--------------|--------------|---------------------------------------|------------------------------------|--------------------------|------------------------------|-----|---------------|--------------|-----------------------------------------------------|
|             |                               | NORTHING     | EASTING      |                                       |                                    |                          |                              |     |               |              |                                                     |
| 205         | S 1/4 Cor. Sec. 22, T27S, R2E | 1683881.7292 | 1689113.0847 | *4 Rebar with Baughman Cap in Thimble | 600+71.73<br>Zelta St.<br>49+70.50 | 29.50 Lt.<br>0.00 Lt.    | 90° 01' 47" NW               | R1  | 84.05         | SW           | Chiseled cross cut on traffic signal base           |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 94.74         | SE           | Chiseled cross cut on traffic signal base           |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 64.10         | NE           | Chiseled cross cut on traffic signal base           |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 66.00         | NW           | Chiseled cross cut on traffic signal base           |
| 206         | SW Cor. Sec. 23, T27S, R2E    | 1683925.0841 | 1691762.3417 | *5 MKEC                               | 627+21.90<br>127th St.<br>50+02.14 | 2.14 Rt.<br>0.00 Lt.     | 90° 24' 00" SE               | R1  | 1.50          | S            | North edge of eastbound shoulder                    |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 83.00         | SW           | Nail in cap in light pole                           |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 88.20         | SW           | Centerline of SBC manhole                           |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 115.20        | SE           | Gas pipeline marker                                 |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 144.30        | NW           | Fence corner post, fence east, northeast, southwest |
|             |                               |              |              |                                       |                                    |                          |                              | R6  | 178.80        | NE           | 3 nails in highline pole                            |
| 207         | S 1/4 Cor. Sec. 23, T27S, R2E | 1683983.9978 | 1694410.8031 | *5 Rebar in Thimble                   | 653+71.02                          | 2.14 Rt.                 | 90° 23' 10" SE               | R1  | --            | N & S        | Tree line                                           |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 110.10        | N            | Nail in washer top of brace post                    |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 111.64        | NNE          | Nail in washer top of brace post                    |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 119.06        | S            | Nail in washer top of brace post                    |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 57.11         | W            | Chiseled cross cut on drop inlet                    |
| 208         | SW Cor. Sec. 24, T27S, R2E    | 1684042.6246 | 1697049.5335 | *4 Baughman Rebar (Set)               | 680+11.13<br>143rd St.<br>50+32.00 | 32.00 Rt.<br>0.00 Lt.    | 90° 04' 25" SE               | R1  | 98.85         | SW           | Chiseled cross on signal pole base                  |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 93.44         | SE           | Chiseled cross on signal pole base                  |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 84.42         | NE           | Chiseled cross on signal pole base                  |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 79.12         | NW           | Chiseled cross on signal pole base                  |
| 209         | S 1/4 Cor. Sec. 24, T27S, R2E | 1684086.1048 | 1699684.0765 | *4 Baughman Rebar (Set)               | 706+46.67<br>(Bk. Tan.)            | 1.92 Lt.                 | 87° 04' 36" NW<br>(Bk. Tan.) | R1  | 97.99         | SSW          | Chiseled cross cut on fence corner base             |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 55.75         | W            | Chiseled cross cut on drop inlet                    |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 71.30         | NNE          | Top of right-of-way monument                        |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 93.69         | NW           | Chiseled cut on high line pole base                 |
| 210         | SW Cor. Sec. 19, T27S, R3E    | 1684130.0028 | 1702321.6939 | *5 Rebar in Thimble                   | 732+84.76<br>159th St.<br>49+89.78 | 10.22 Lt.<br>0.00 Lt.    | 89° 55' 49" NW               | R1  | 97.60         | SE           | Nail and washer in light pole                       |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 98.00         | SW           | Nail and washer in light pole                       |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 99.50         | SW           | Top of right-of-way monument                        |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 85.00         | NE           | USGS Monument                                       |
| 211         | W 1/4 Cor. Sec. 19, T27S, R3E | 1686783.4130 | 1702283.1162 | Concrete Monument                     | 159th St.<br>23+36.09              | 0.00 Lt.                 |                              | R1  | 30.40         | ENE          | Nail in cap in power pole                           |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 35.20         | NW           | PK nail in hedge tree                               |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 47.50         | SW           | PK nail in hedge tree                               |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 30.00         | W            | *5 rebar with yellow cap                            |
| 212         | Center of Sec. 24, T27S, R2E  | 1686738.6964 | 1699645.3190 | *4 Rebar with Baughman Company Cap    |                                    |                          |                              | R1  | 0.50          | WSW          | Steel fence corner post                             |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | --            | N, S, E, & W | Line of tree lines                                  |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 12.15         | S            | 40d nail in 14" Hackberry                           |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 1.90          | N            | Wrought iron fence corner                           |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 14.20         | E            | PK nail in cap in hedge tree                        |
| 213         | W 1/4 Cor. Sec. 24, T27S, R2E | 1686698.8786 | 1697009.1081 | *5 Rebar                              | 680+11.13<br>143rd St.<br>23+75.44 | 2624.56 Lt.<br>0.00 Lt.  | 90° 04' 25" NW               | R1  | 51.15         | W            | 3 nails in brace post                               |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | --            | E & W        | Tree line                                           |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | --            | N & S        | Centerline of road                                  |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 52.00         | ESE          | Mag in power pole                                   |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 56.70         | SE           | Chain link fence corner                             |
|             |                               |              |              |                                       |                                    |                          |                              | R6  | 51.90         | WSW          | Gas test                                            |
| 214         | Center of Sec. 23, T27S, R2E  | 1686640.4253 | 1694369.6915 | Metal Cap LS - 1126                   | 653+71.02                          | 2654.61 Lt.              | 90° 23' 10" NW               | R1  | 21.60         | S            | Chiseled cross cut on retaining wall                |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 47.00         | E            | Chiseled cross cut on RCP                           |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 10.50         | NW           | Shoulder NE bound Turnpike                          |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 67.10         | NNW          | Chiseled cross cut top of centerline of wall        |
| 215         | W 1/4 Cor. Sec. 23, T27S, R2E | 1686582.4754 | 1691721.7917 | 1" Iron Pipe in Thimble               | 627+21.90<br>127th St.<br>23+42.30 | 2655.56 Lt.<br>0.00 Lt.  | 90° 24' 01" NW               | R1  | 60.80         | SE           | 3 nails in top of fence post                        |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 59.10         | NW           | Top of steel fence corner post                      |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 46.10         | SW           | Top of fire hydrant                                 |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 46.40         | NW           | 3 nails in light pole                               |
| 216         | Center of Sec. 22, T27S, R2E  | 1686542.0000 | 1689073.9768 | 100D Spike                            | Zelta St.<br>23+09.94              | 0.00 Lt.                 |                              | R1  | --            | E & W        | Centerline of road                                  |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 34.80         | S            | Bent 60d nail in hedge tree                         |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 29.30         | N            | 3 nails in power pole                               |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 71.35         | NW           | PK nail in guy pole                                 |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 36.00         | SW           | PK nail in light pole                               |
| 225         | Center of Sec. 27, T27S, R2E  | 1681227.8883 | 1689148.3159 | *5 Rebar With MKEC Cap                | 600+71.73<br>Zelta St.<br>76+24.57 | 2,624.57 Rt.<br>0.00 Lt. | 90° 01' 47" SE               | R1  | 4.00          | N            | Chiseled cross cut on curb                          |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 13.90         | S            | Chiseled cross cut on curb                          |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 20.00         | SW           | Chiseled cross cut on curb                          |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 18.30         | SE           | Chiseled cross cut on curb                          |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 33.40         | NE           | Square cut east end headwall RCBC                   |
| 226         | W 1/4 Cor. Sec. 26, T27S, R2E | 1681274.1284 | 1691796.5656 | *4 Rebar                              | 127th St.<br>76+53.32              | 0.00 Lt.                 |                              | R1  | 26.35         | E            | Steel fence corner post                             |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | --            | E            | Line of tree line                                   |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 34.30         | NW           | Chiseled cross on southeast gas meter guard post    |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 37.65         | SE           | PK nail in power pole                               |
|             |                               |              |              |                                       |                                    |                          |                              | R5  | 70.30         | SW           | PK nail in power pole                               |
| 228         | W 1/4 Cor. Sec. 25, T27S, R2E | 1681387.8614 | 1697079.7227 | *4 Rebar                              | 143rd St.<br>76+86.93              | 0.00 Lt.                 |                              | R1  | 38.40         | W            | PK nail in power pole                               |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 33.10         | ESE          | Chiseled cross cut on RCP                           |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 53.90         | NE           | PK nail in power pole                               |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 68.50         | WNW          | South end wrought iron fence                        |
| 229         | Center of Sec. 25, T27S, R2E  | 1681434.7013 | 1699727.6085 | 3/4" Iron Pipe with LS555 Cap         | 706+46.67<br>(Bk. Tan.)            | 2649.84 Rt.              | 87° 04' 36" SE<br>(Bk. Tan.) | R1  | 2.73          | NW           | Mag nail in fence corner                            |
|             |                               |              |              |                                       |                                    |                          |                              | R2  | 80.97         | NE           | Southwest corner of metal building                  |
|             |                               |              |              |                                       |                                    |                          |                              | R3  | 127.23        | SE           | Southeast corner of garage house # 15210            |
|             |                               |              |              |                                       |                                    |                          |                              | R4  | 189.59        | W            | Chiseled cross cut on curb                          |

CITY OF WICHITA

SECTION CORNERS

I:\28.34 AM  
 2/19/2011  
 T:\35766A\Cadd\Sheets\General\K2SECCOR01.dgn  
 SURV. - PLOT CADD DES. - DR. - TR. - CKD. - APP.