

Reference Only
NOT TO SCALE

U.S. Patent No. 6,951,619

Dimensions in inches

Permanent Pool Volume = 800 US gallons

The Hydroguard must be cleaned after the construction period if it is used as a sediment and erosion control measure

The Hydroguard should be inspected once per year for stabilized sites

Inspection will determine the maintenance frequency (annual maintenance or once every two years typical for stabilized sites)

Sites with unstable conditions (exposed soil or materials storage) will require more frequent inspection and maintenance

Hydroworks, LLC

50 S. 21st St., Kenilworth, NJ 07033

Phone: 888-290-7900 Fax: 888-783-7271

Web: www.hydroworks.com


Hydroworks HG5 (60"Ø)

PROJECT:

LOCATION:

REVISION DATE: 02/10/2011



	Site Grading Plan Mid-Continent Airport Addition Lot 1, Block 2	
	<small>Baughman Company, P.A. 315 Ellis St. Wichita, KS 67211 P 316-262-2721 F 316-262-2149 ENGINEERING SURVEYING PLANNING LANDSCAPE ARCHITECTURE</small>	
PROJECT NUMBER 33 PPD (607861)	DESIGN DATE 7/11	DRAWN DATE 7/11
REVISIONS:	APPROVED SCALE No Scale	SHEET 3 OF 9