



Note:
 At all locations where joints are not congruent through pavement sections, Contractor shall drill full pavement depth & seal with Hot Paired Joint Sealant (ASTM D1190). Subsidiary to "Concrete Pavement 9" (NRDJ)."

LEGEND

- * Match Existing
- Longitudinal Joint (L.J.)
- Transverse Contraction Joint (C.J.)
- ∅ Omit Dowels or Tie Bars



13TH STREET JOINT DETAILS		
CITY ENGINEER JAMES L. ARMOUR, P.E., L.S.		
PROJECT NUMBER 472-84817 PHASE I	OCA NUMBER 770005	DATE 11/2011
CITY ENGINEER'S OFFICE CITY HALL - SEVENTH FLOOR 455 NORTH MAIN STREET WICHITA, KANSAS 67202-1620 (316) 268-4501		DESIGN DRAWN SHEET 30 of 113



Plotted on: Monday, November 07, 2011 02:56 PM
 Plot Queue: \\ovpww00\pl\TBWLP
 Plot Scale: 20.000000:000000 Pen Table: \\ovpww00\Jobs\4809\Common\Highway\Library\lob\pen\CC-22x36.pen
 Design Filename: \\ovpww00\Jobs\4809\Detail\13th\Int\Intersection-Joint.dgn

\\ovpww00\Jobs\4809\Detail\13th\Int\Intersection-Joint.dgn