



A SITE ARCHITECTURAL PLAN
 1"=10'-0"
 NORTH

GUARDRAIL NOTES:

1. ALL GUARDRAILS ARE TO BE HOT DIPPED GALVANIZED PER KDOT SPECIFICATION SECTION 1624 (ZINC COATING)
2. GUARDRAILS ARE TO BE A DUPLEX SYSTEM. GALVANIZER SHALL PREPARE GUARDRAILS ACCORDINGLY TO ACCEPT PRIMER AND TOPCOAT.
3. PREPARE GALVANIZED METAL PER SSPC-SPI SOLVENT CLEANING AND SSPC-SP16 BRUSH BLASTING, OR MPI #25 CLEANING, ETCHER FOR GALVANIZED STEEL. PREPARE GALVANIZED SURFACES PER ASTM D6386.
4. PAINTED AEAS SHALL BE COATED WITH PRO-CRYL UNIVERSAL PRIMER (MP1 134)
5. TOP COAT SHALL BE SHER-CRYL HIGH PERFORMANCE ACRYLIC PAINT.
6. FINAL TOP COAT SHALL BE 'RED IRON' OR 'OXIDE RED'. FINAL COLOR TO BE PREPARED AND SUBMITTED FOR APPROVAL PRIOR TO FINAL PAINTING.
7. PROVIDE (1) ONE MOCK-UP OF EACH GUARDRAIL TYPE FOR REVIEW PRIOR TO GALVANIZING.

DOUGLAS AVE.-BNSF
 RAILROAD UNDERPASS
 IMPROVEMENTS
 WICHITA, KS

LKArchitecture
 Architecture • Engineering • Planning • Interior Design • Landscape Architecture

LK Architecture Inc. ©
 345 RIVERVIEW WICHITA, KS 67203
 Phone (316) 268-0230 Fax (316) 268-0205

CONTACT: JEFFREY A. BEST, PLA
 PROJECT NUMBER:

17145

SHEET TITLE:

**SITE ARCHITECTURAL
 PLAN**

SHEET NUMBER:

15