

INLET & MANHOLE DATA																				FOR INFORMATION ONLY						REMARKS									
ROUTING SEQUENCE		LOCATIONS OF INSTALLATIONS			CONSTRUCT OR INSTALL								DIMENSIONS				ELEVATIONS		INFLOW CONDUITS					OUTFLOW CONDUITS			NO STEP	CAST IRON (LBS.)	STRUC. STEEL (LBS.)	REINF. STEEL (LBS.)	CLASS 'A' CONC. (MISC.) (CU. YD.)	CL. III EXC. (CU. YD.)			
FROM	TO	STATION	ROUTE IDENTIFICATION	DISTANCE LEFT/RIGHT	INLET (TY.12) (CURB)	INLET (TY.12) (SPEC)	INLET (TY.22) (CURB)	INLET (TY.1A) (CURB)	DROP INLET (DOUBLE)	M.H. (STD.) (TY.B)	END SECT. *	G & F A (TYPE)	L & F A (TYPE)	L. (FT.)	W. (FT.)	H. (FT.)	HT. (FT.)	TOP	FLOOR	SIZE DIRECTION	FLOWLINE (ELEV.)	SIZE DIRECTION	FLOWLINE (ELEV.)	SIZE DIRECTION	FLOWLINE (ELEV.)								SIZE DIRECTION	FLOWLINE (ELEV.)	
18	19	66+00	WEBB	25.5' LT.				1						11'-4"	4'-4"			222.00	214.00									15'-E.	214.25						
19	21	66+00	WEBB	25.5' RT.				1						11'-4"	4'-4"			202.00	213.50	15"-W.	214.00							15"-S.	213.90						
20	21	61+50	WEBB	25.5' LT.				1						11'-4"	4'-4"			217.09	208.09									15'-E.	208.50						
21	23	61+50	WEBB	25.5' RT.				1						11'-4"	4'-4"			217.09	207.09	15"-W.	208.25	15"-N.	208.25					21"-S.	207.75						
22	23	56+50	WEBB	25.5' LT.				1						11'-4"	4'-4"			210.55	206.05									15'-E.	206.30						
23	26	56+50	WEBB	36.5' RT.				1						11'-4"	5'-4"			210.20		15"-W.	206.00	21"-N.	205.20					24"-S.	204.95						
24	25	51+21.61	WEBB	107.99' LT.					1					4'-0"	2'-0"			204.00										24"-E.	198.50						
25	26	51+23.50	WEBB	42.5' LT.				1						11'-4"	4'-4"			203.92	197.92	24"-W.	198.35							38"x24"-E.	198.25						
26	27	51+23.50	WEBB	42.5' RT.				1						11'-4"	4'-4"			203.92		38"x24"-W.	197.85	24"-N.	198.10					4'x3'-S.	197.85						
27	28	51+13.5	WEBB	44.5' RT.						1								203.92		4'x3'-N.	197.84							4'x3'-SE.	197.84						
28	30	11+13.5	21ST. ST. N.	44.5' RT.						1								205.10		4'x3'-NW.	197.74							4'x3'-E.	197.74						
30	33	12+78.5	21ST. ST. N.	42.5' RT.				1						11'-4"	4'-4"			204.40		30"-N.	197.88	7'x3'-W.	197.59					9'x3'-E.	197.59						
32	33	16+08.5	21ST. ST. N.	25.5' RT.				1						11'-4"	5'-4"			203.58	198.58									15"-N.	198.79						
33		16+08.5	21ST. ST. N.	36.5' LT.										11'-4"	4'-4"			203.24		30"-N.	197.54	15"-S.	198.50	9'x3'-W.	197.25			9'x3'-E.	197.25						
47		19+00.00	21ST. ST. N.	42' LT.					1					4'-0"	2'-0"			201.0																	
48	35	20+42.00	21ST. ST. N.	30' RT.							1																								
49	35	20+58.00	21ST. ST. N.	30.56' RT.							1																								
50	35	20+58.00	21ST. ST. N.	40' LT.							1																								
-	35	20+50.00	21ST. ST. N.	40' LT.						1								202.0																	
		TOTALS						10	2		3	3																							

CONDUIT DATA																												REMARKS										
ROUTING SEQUENCE		LOCATIONS OF INSTALLATIONS			CONSTRUCT OR INSTALL		CONDUIT FLOW LINES		SEWER EXCAVATION		STORM SEWERS (LIN. FT.)										END SECTIONS (EACH)						AASHTO CONC. CLASS			METAL PIPE GAGE								
		STATION	ROUTE IDENTIFICATION	DISTANCE RT./LT.	TYPE OF CONDUIT		LENGTH (FEET)	INFLOW (ELEV.)	OUTFLOW (ELEV.)	ROCK (CU.YDS.)	COMMON (CU.YDS.)	REINF. CONC.										REINF. CONC.			CORR. METAL													
FROM	TO				SIZE	MATERIAL						15"	21"	24"	30"	54"	1.5Sq.Ft	5.0Sq.Ft		4'x3'	7'x3'	9'x3'	15"	18"	48"													
18	19	66+00.00	WEBB	25.5' LT.	15"	RCP	56	214.25	214.00			56																										
19	21	66+00.00	WEBB	25.5' RT.	15"	RCP	450	213.90	208.25			450																										
20	21	61+50.00	WEBB	25.5' LT.	15"	RCP	56	208.50	208.25			56																										
21	23	61+50.00	WEBB	25.5' RT.	21"	RCP	500	207.75	205.20				500																									
22	23	56+50.00	WEBB	25.5' LT.	15"	RCP	67	206.30	206.00			67																										
23	26	56+50.00	WEBB	36.5' RT.	24"	RCP	525	204.95	198.10																													
24	25	51+21.61	WEBB	107.99' LT.	1.5Sq.Ft	RCPHE	60	198.50	198.35							60																						
25	26	51+23.50	WEBB	42.5' LT.	5.0Sq.Ft	RCPHE	91	198.25	197.85								91																					
26	27	51+23.50	WEBB	42.5' RT.	4'x3'	RCB	12	197.85	197.84											12																		
27	28	51+13.50	WEBB	44.5' RT.	4'x3'	RCB	97	197.84	197.74											97																		
28	30	11+13.50	21ST. ST. N.	44.5' LT.	4'x3'	RCB	160	197.74	197.59											160																		
29	30	12+78.50	21ST. ST. N.	70.5' LT.	30"	RCP	24	197.95	197.88						24																							
30	33	12+78.50	21ST. ST. N.	42.5' LT.	7'x3'	RCB	330	197.59	197.25																													
31	33	16+08.50	21ST. ST. N.	59.0' LT.	30"	RCP	6	197.59	197.54					6																								
32	33	16+08.50	21ST. ST. N.	25.5' RT.	15"	RCP	67	198.79	198.50		67																											
33	34	16+08.50	21ST. ST. N.	36.5' LT.	9'x3'	RCB	440	197.25	196.81												440																	
48	35	20+42.00	21ST. ST. N.	30' RT.	15"	RCP	6	196.68	196.62		6											1																
49	35	20+58.00	21ST. ST. N.	30.56' RT.	15"	RCP	6	196.68	196.62		6											1																
50	35	20+58.00	21ST. ST. N.	40' LT.	15"	RCP	6	197.5	197.0		6											1																
TOTAL												714	500	525	30		60	91		269	330	440	3															