




Combined Curb & Gutter (6")




Combined Curb & Gutter (1 1/2")




Combined Curb & Gutter (3 5/8")




Combined Curb & Gutter (1 1/2")




Combined Curb & Gutter (8")



Combined Curb & Gutter (1 1/2")



Combined Curb & Gutter (6 5/8")





Combined Curb & Gutter (1 1/2")


GENERAL NOTES

- Expansion (isolation) joints shall be constructed a maximum of 300' apart and at all Pls, PCs, cul-de-sac quadrants, and ends of returns.
- Contraction joints shall be constructed a minimum of 12' apart.
- Joint sealer shall be required at all joints on arterial and industrial streets and at intersections on residential streets.


T* = Thickness of curb to adjust with pavement thickness



ALT. LONGITUDINAL CONSTRUCTION JOINT



EXPANSION JOINT (E.J.)



PAVING BRICK CROSSWALK DETAIL

Sheet: 06-06-2019, 8:18:05 PM by CP
 Plot Date: 11-07-2019, 1:41:06 PM by CP
 U:\Wichita-Civil\2018\187042-006-12C-COMBINED CURB AND GUTTER DETAILS

CITY OF WICHITA
PUBLIC WORKS & UTILITIES
ENGINEERING DIVISION

CURB & GUTTER DETAILS		
CITY ENGINEER GARY JANZEN, P.E.		
PROJECT NUMBER 472-85496	OCA NUMBER 707150	DATE
CITY ENGINEER'S OFFICE CITY HALL - SEVENTH FLOOR 455 NORTH MAIN STREET WICHITA, KANSAS 67202-1620 (316) 268-4501		SHEET 12 of 48