



- ▬▬ Type 3 Barricades
- X Length to the Nearest Whole Mile
- Channelizing Device
- ▭▭▭ Ahead, 1500 ft, or 1 mile
- ▭▭▭ Ahead, 1000 ft, 1500 ft, or 1/2 mile
- ⊕ Right or Left
- ⊗ Speed to be determined by the Engineer
- Type "A" Low Intensity Warning Light

* For speeds greater than 45 mph use freeway / expressway size signs.

One flagger should be stationed within each multi-lane roadway activity area where work is in a closed lane adjacent to traffic and not separated by a concrete safety barrier system.

Sowed: 06-06-2019 6:23:07 PM by: CP
 Plot Scale: 1:1 07-03-2019 1:45:42 PM by: CP
 U:\Vchile-Civil\2018\187042\006\Drawings\187042-006-48C-48C-1E748

KANSAS DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL CROSSOVER ON UNDIVIDED ROADWAY				
TE748				
NO.	DATE	REVISIONS	BY	APPD
3				
2				
1				
DESIGNED	B.A.H.	DETAILED	B.A.H.	QUANTITIES
DESIGN CK.	DETAIL CK.	QUAN. CK.	TRACE	CK.