

STATE	PROJECT NO.	YEAR	SHEET NO.	TOTAL SHEETS
KANSAS	87 TE-0451-01	2018	127	222

DETAILED SPECIFICATIONS FOR FLAT SHEET SIGNS

ALL NEW FLAT SHEET SIGN BLANKS SHALL BE OF THE ALUMINUM ALLOY AND THICKNESS SHOWN ON THE FLAT SHEET BLANK DETAIL SHEETS.

FLAT SHEET BLANKS SHALL BE USED FOR SIGNS THAT ARE LESS THAN OR EQUAL TO 7'-0" IN LENGTH AND/OR LESS THAN OR EQUAL TO 4'-0" IN HEIGHT. FLAT SHEET BLANKS SHALL ALSO BE USED FOR SIGNS THAT ARE 4'-0" IN LENGTH AND LESS THAN OR EQUAL TO 8'-0" IN HEIGHT.

THE DESIGN DETAILS FOR SIGNS (COLOR, LETTER HEIGHT, AND LETTER SERIES) SHALL BE AS SHOWN IN THE 'STANDARD HIGHWAY SIGNS' MANUAL (2004 EDITION), UNLESS OTHER DETAILS ARE SHOWN IN THE PLANS.

ALL SIGN FACES WITH BLUE, GREEN, RED, YELLOW, FLUORESCENT YELLOW GREEN, BROWN, OR WHITE BACKGROUND SHALL BE COVERED WITH TYPE IV HIGH INTENSITY RETROREFLECTIVE SHEETING.

THE TYPE OF ADHESIVE USED FOR RETROREFLECTIVE SHEETING OR LETTERING FILM SHALL BE HEAT ACTIVATED OR PRESSURE SENSITIVE.

THE SIGN FACES SHALL BE DIRECT SCREEN PROCESS, REVERSE SCREEN PROCESS, OR DIRECT APPLIED LEGEND.

DETAILED SPECIFICATIONS FOR STRUCTURAL EXTRUDED PANEL SIGNS

ALL NEW REINFORCED SIGN PANELS SHALL BE OF THE FABRICATION, ALUMINUM ALLOY, AND THICKNESS SHOWN ON THE REINFORCED PANEL DETAIL SHEETS. IF EXTRUSHEET FABRICATED SIGN PANELS ARE USED, THEY SHALL BE OF THE LENGTH, WIDTH AND IN THE POSITION SHOWN. IF EXTRUSHEET FABRICATED PANEL DIMENSIONS ARE NOT SHOWN, A LINE OF LEGEND SHOULD BE PLACED ENTIRELY ON ONE PANEL. IF EXTRUDED FABRICATED SIGN PANELS ARE USED, EITHER 1'-0" OR 6" PANELS SHALL BE USED. THE 1'-0" PANELS SHALL BE USED ONLY AT THE TOP OR BOTTOM OF SIGNS.

REINFORCED PANELS SHALL BE USED FOR SIGNS THAT ARE GREATER THAN 7'-0" IN LENGTH OR GREATER THAN 4'-0" IN HEIGHT.

ALL SIGN FACES SHALL BE COVERED WITH TYPE IV HIGH INTENSITY RETROREFLECTIVE SHEETING.

THE RETROREFLECTIVE SHEETING USED FOR THE DIRECT APPLIED LEGEND, AND DIRECT APPLIED BORDERS SHALL BE TYPE IV HIGH INTENSITY RETROREFLECTIVE SHEETING.

THE TYPE OF ADHESIVE USED FOR RETROREFLECTIVE SHEETING OR LETTERING FILM SHALL BE HEAT ACTIVATED OR PRESSURE SENSITIVE.

LETTERS AND NUMBERS ON REINFORCED PANEL SIGNS ARE MODIFIED SERIES "E" UNLESS OTHERWISE SHOWN.

SPACING TABLE DIMENSIONS ARE IN INCHES.

Drawn By : \$\$USERNAME\$\$ Plotted : \$\$YTIME\$\$
 File : \$\$DGN\$PEC\$\$ \$KDOTGRP\$\$

1	7/23/10	Changed Notes and Sheeting Type	D.D.G.	D.B.
NO.	DATE	REVISIONS	BY	APPD

KANSAS DEPARTMENT OF TRANSPORTATION
DETAILS SPECIFICATIONS
FOR REINFORCED SIGN PANELS
AND FLAT SHEET SIGNS

~~TE590~~ 7/1/03

FHWA APPROVAL	7/23/2010	APPD	Steven A. Buckley
DESIGNED	D.D.G. DETAILED	K.D.S. QUANTITIES	TRACED
DESIGN CK.	S.A.B. DETAIL CK.	D.D.G. QUAN. CK.	TRACE CK.