



**1 FOUNDATION PLAN**  
 1/8" = 1'-0"

**FOUNDATION PLAN NOTES:**

- TOP OF FOUNDATION 99'-4" UNLESS NOTED OR DETAILED OTHERWISE.
- SEE SHEET S0.1, S0.2 AND S0.3 FOR GENERAL STRUCTURAL NOTES AND SHEET S0.4 FOR SPECIAL INSPECTION REQUIREMENTS.
- CENTER ALL COLUMN FOOTINGS BELOW GRID LINE INTERSECTIONS UNLESS SHOWN OR NOTED OTHERWISE.
- SEE DETAILS 1/S5.1 FOR TYPICAL SLAB JOINT DETAILS AND 2/S5.1 FOR CORNER BAR DETAIL.
- SEE DETAIL 3/S5.1 FOR THICKENED FOOTING DETAIL WHEN SUBGRADE PLUMBING FLOWLINE IS LESS THAN 2'-0" BELOW BOTTOM OF THE GRADE BEAM, TYP.
- PROVIDE 1/2" E.J. MATERIAL BETWEEN EXTERIOR CONCRETE AND THE BUILDING, TYPICAL.
- SEE DETAIL 6/S5.1 FOR TYPICAL SLAB OPENINGS.
- SEE DETAIL 5/S5.1 FOR TYPICAL ISOLATION JOINT AT EACH STEEL COLUMN.
- REFERENCE MECHANICAL FOR MISCELLANEOUS FLOOR DRAINS AND OTHER SLAB PENETRATIONS.
- REFERENCE ARCHITECTURAL DRAWINGS FOR NON-LOAD-BEARING WALLS.
- PROVIDE (2) #4X4'-0" @ ALL RE-ENTRANT CORNERS WHERE SLAB JOINTS DO NOT TERMINATE AT CORNER.

**FOUNDATION PLAN NOTES:**

- TOP OF FOUNDATION 99'-4" UNLESS NOTED OR DETAILED OTHERWISE.
- REFERENCE SHEET S-001 AND S-002 FOR GENERAL STRUCTURAL NOTES AND S-003 FOR SPECIAL INSPECTION REQUIREMENTS.
- CENTER ALL COLUMN FOOTINGS BELOW GRID LINE INTERSECTIONS UNLESS SHOWN OR NOTED OTHERWISE.
- REFERENCE 1 AND 2/S-501 FOR TYPICAL SLAB JOINT DETAILS AND CORNER BAR DETAILS.
- REFERENCE 3/S-501 FOR THICKENED FOOTING DETAIL WHEN SUBGRADE PLUMBING FLOWLINE IS LESS THAN 2'-0" BELOW BOTTOM OF THE GRADE BEAM, TYP.
- PROVIDE 1/2" E.J. MATERIAL BETWEEN EXTERIOR CONCRETE AND THE BUILDING, TYPICAL.
- REFERENCE 4/S-501 FOR TYPICAL SLAB OPENINGS.
- REFERENCE ARCHITECTURAL DRAWINGS FOR NON-LOAD-BEARING WALLS.
- PROVIDE (2) #4X4'-0" @ ALL RE-ENTRANT CORNERS WHERE SLAB JOINTS DO NOT TERMINATE AT CORNER.

**PLAN MARKS:**

- C#** COLUMN MARK, REFERENCE SHEET S-601
- F#** FOOTING MARK, REFERENCE SHEET S-601
- LENGTH** SHEAR WALLS, REFERENCE SHEAR WALL SCHEDULE ON SHEET S-601

