FHWA REGION NO.	STATE	PROJECT NO.	YEAR	SHEET NO.	TOTAL SHEETS
7	KANSAS	87N-0061-01	1998	28	91

SCHEDULE OF INLETS AND MANHOLES

STATION	SIDE	(RC) MAN-HOLES	TYPE12 CURB INLETS	TYPE10 CURB INLETS	SEWER DATA INFLOW PIPES SIZE	INFLOW PIPES ℄ ELEV.	INFLOW PIPES SIZE	INFLOW PIPES ℄ ELEV.	INFLOW PIPES SIZE	INFLOW PIPES ℄ ELEV.	OUTFLOW PIPES SIZE	OUTFLOW PIPES ℄ ELEV.	OUTFLOW PIPES GRADE	ELEVATIONS TOP	ELEVATIONS FLOOR	DIMENSIONS L (mm)	DIMENSIONS W (mm)	DIMENSIONS H (mm)	STORM SEWER (RCP) (m) 300 mm	375 mm	450 mm	600 mm	FOR INFORMATION ONLY SEWER EXC. (m^3) COMM.	ROCK	HT. FILL (m)	CONC. AASHTO CL. NO.	PIPE THICK. (mm) STEEL	FOR INFORMATION ONLY CL. III EXC. (m^3)	CAST IRON (kg)	STRUC. STEEL (kg)	REINF. STEEL (kg)	CLASS A CONC. (m^3)	STEPS	REMARKS
22+662.445	RT.	1			375	394.071	375	394.071			375	394.041	0.40%	394.988	393.768	1370	1370	1370		10.1			5.1					5.384	148		119	1.346		
22+666.446	LT.		1								375	394.199	0.90%	395.009	394.089	910	1980	1070		14.2			4.9					4.213	53	69	82	0.917		
22+676.000	RT.		1		375	394.132	375	394.132			375	394.102	0.20%	394.978	393.908	910	1980	1220		15.4			5.8					4.817	53	69	92	1.040		
22+676.000	LT.		1								375	394.198	0.40%	395.058	393.988	910	1980	1220		16.5			6.1					4.817	53	69	92	1.040		
22+720.000	RT.		1		375	394.249					375	394.219	0.20%	395.049	394.129	910	1980	1070		43.4			15.5					4.213	53	69	82	0.917		
22+720.000	LT.		1		375	394.312					375	394.282	0.20%	395.109	394.189	910	1980	1070		16.5			5.9					4.213	53	69	82	0.917		
22+752.000	LT.		1								375	394.375	0.20%	395.154	394.234	910	1980	1070		31.4			10.4					4.213	53	69	82	0.917		
22+800.164	LT.		1								375	394.479	0.40%	395.198	394.278	910	1980	1070		5.9			1.8					4.213	53	69	82	0.917		
22+806.470	LT.	Exist			375	394.460					375	394.430	0.13%							2.2			0.7											
22+806.477	LT.	1			375	394.427	375	394.455	375	394.455	375	394.425	Exist	395.186	394.266	1370	1370	1070										4.153	53		100	1.127		
22+811.060	LT.		1								375	394.472	0.40%	395.239	394.319	910	1980	1070		4.2			1.4					4.213	53	69	82	0.917		
22+820.000	LT.		1		375	394.516					375	394.486	0.20%	395.232	394.312	910	1980	1070		12.8			4.0					4.213	53	69	82	0.917		
22+820.000	RT.		1								375	394.549	0.20%	395.209	394.289	910	1980	1070		16.5			4.5					4.213	53	69	82	0.917		
22+895.000	LT.		1								375	394.423	0.50%	395.236	394.316	910	1980	1070		16.5			5.7					4.213	53	69	82	0.917		
22+895.000	RT.		1		375	394.340					450	394.265	0.50%	395.236	394.166	910	1980	1220			61.1		30.8					4.817	53	69	92	1.040		
22+941.256	LT.		1								375	394.100	2.16%	395.375	394.025	910	1980	1500		14.7			8.5					6.017	53	69	112	1.284		
22+956.300	LT.	Exist			750	392.297	375	393.783	450	393.693	750	392.297	Exist	395.276																				
22+956.940	RT.	Exist			450	393.959	600	393.172	450	393.698	750	392.338	Exist	393.315																				
22+980.000	RT.		1		375	393.468	450	393.393			600	393.243	0.32%	395.372	393.082	910	1980	2440				22.3	34.2					9.626	91	69	171	2.003	6	
22+980.000	LT.		1								375	393.963	3.00%	395.372	393.842	910	1980	1680		16.5			10.6					6.621	53	69	122	1.399		
22+997.000	RT	1			450	393.475					450	393.445	0.32%	395.175	393.195	1370	1370	2130			16.4		16.8					8.266	148		166	1.903	6	
23+050.000	RT.		1		450	393.672					450	393.642	0.32%	395.515	393.535	910	1980	2130			52.2		54.4					8.425	85	69	151	1.766	5	
23+140.000	RT.		1		450	393.988					450	393.958	0.32%	395.524	393.874	910	1980	1830			89.4		77.1					7.217	78	69	132	1.521	4	
23+160.000	RT.		1		375	394.199	375	394.507			450	394.124	0.70%	395.541	394.011	910	1980	1680			19.4		15.7					6.621	53	69	122	1.399		
23+160.000	LT.		1								375	394.870	2.20%	395.541	394.781	910	1980	910		16.5			4.6					3.609	53	69	71	0.803		
23+185.000	RT.			1	375	394.424					375	394.394	0.80%	395.527	394.177	910	900	1500		24.4			13.3					3.398	0	68	56	0.716		
23+185.000	LT.			1							375	394.672	1.50%	395.527	394.457	910	900	1220		16.5			6.1					2.763	0	68	40	0.590		
23+216.000	RT.			1							300	394.772	0.80%	395.558	394.638	910	900	1070										2.424	0	68	34	0.522		
23+222.500	LT.			1	300	394.630					300	394.600	0.80%	395.533	394.463	910	900	1220	17.8				6.7					2.763	0	68	40	0.590		
23+228.842	LT.		Exist		300	394.537					375	394.511	Exist.	395.530					7.9				3.0											
TOTAL		3	19	4															25.7	294.2	238.5	22.3	353.6					129.655	1 451	1 583	2 450	28.342		

KANSAS DEPARTMENT OF TRANSPORTATION

SCHEDULE
INLETS AND MANHOLES

RD768 SI

FHWA APPROVAL	2-17-95	APP'D. James O. Brewer	
DESIGNED	DETAILED	QUANTITIES	TRACED B.N.B.
DESIGN CK.	DETAIL CK.	QUAN.CK.	TRACE CK. R.J.S.

Drawn By : $$USERNAME$$ Plotted : $$$$SYTIME$$$$$$
File : $$$$$$$