

* Offset dimension for Inlets are measured from the inside face of the box structure nearest the curb to the centerline of the street right of way

* Offset dimension for Inlets are measured from the inside face of the box structure nearest the curb to the centerline of the street right of way

* Offset dimension for Inlets are measured from the inside face of the box structure nearest the curb to the centerline of the street right of way

BL Sta 14+32.88 Lt.
5'ø RCMH
Top=112.72
FL(N)=108.95
FL(S)=108.95
FL(E)=108.20
FL(W)=108.20

Construct 14' Concrete Drive
Approach (See Detail Sheet CV 4.9)
220 S.F. 8" Reinf. Conc.

KGE MH. See note
1 Sheet CV 1.1

BL Sta 15+01.26 38.10' Lt.
Light Fixture

BL Sta 14+76.99 38.1
Light Fixture

BL Sta 14+32.88 Rt.
Type 2 Curb Inlet

Construct 18' Concrete Drive
Approach (See Detail Sheet CV 4.9,
275 S.F. 8" Reinf. Conc.

Sta 13+68.55 40.68' Rt.
Adjust MH Lid
Top=112.57
Replace KGE MH Lid w/
City of Wichita MH Lid

Sta 12+55.53 40.38' Rt.
Adjust MH Lid
Top=112.81
Replace KGE MH Lid w/
City of Wichita MH Lid

BL Sta 12+74.74 Rt.
Type 2 Curb Inlet
Top=112.66
 $FI(N)=109.12$
 $FI\ 4''\ Stub\ (S)=109.66$

Existing conduit to be abandoned by Westar Energy. City of Wichita to assume ownership.

Sta 11+42.74 40' Rt.
Exist. KGE MH to remain
No adjustment required
Replace KGE MH Lid w/
City of Wichita MH Lid

Concrete Intersection Pavement
See Detail Sheet CV 1.7

6" Asphalt Pavement
See Detail Sheet CV 1.7

Remove

Mill and Overlay

Concrete Intersection Pavement
See Detail Sheet CV 1.7

6" Asphalt Pavement
See Detail Sheet CV 1.7

WEST DOUGLAS STREETSCAPE
ARKANSAS RIVER TO SENECA
WICHITA, KANSAS

PROJECT NO. 472 83608 **OCA:** 706846
MVP PROJECT NO. 101008
DATE: August 7, 2002
REVISED: August 30, 2002

SHEET

CV 1.1

kemiller
engineering 



516 S. Market,
Wichita, KS 67202

316/264-0242

PAVING PLAN 1