

an Addition to Wichita, Sedgwick County, Kansas



(A) = Assumed Kansas Zone South Grid Bearing
P = Plotted
M = Measured
C = Calculated
D = Described

1	1/8" REBAR W/SAVOY COMPANY CAP (FOUND)
2	5/8" SMOOTH BAR (FOUND - ORIGIN UNKNOWN)
3	3/4" IRON PIPE (FOUND - ORIGIN UNKNOWN)
4	5/8" REBAR W/CAP (FOUND - ORIGIN UNKNOWN)
5	1/2" REBAR W/SAVOY, RUGLES BOOM CAP (FOUND)
6	5/8" REBAR W/HARMSTRONG SURVEYING CAP (FOUND)
7	1/2" REBAR W/CARVER CAP (SET)

BENCHMARK #1: CHISELED SQUARE ON THE TOP
OF CURB ON THE EAST SIDE OF CRANBROOK, 52
FEET NORTH OF THE CENTERLINE OF PAWNEE,
ELEVATION = 1397.80 (NAVD88)

MANBROOK AND BELAIRE,
EVALUATION = 1374.75 (NAVD88)

BENCHMARK #3: CHISELED SQUARE

CURB ON THE EAST SIDE OF
FORTH CURB RETURN OF THE H

ROUND, ELEVATION = 1361.56 (NAVD88)

MINIMUM BUILDING PAD ELEVATION FOR LOWEST OPENING INTO STRUCTURES		
BLOCK	LOT NO.	ELEVATION (MMVD88)
7	1, 2, 3, 4	1,366.7
7	5, 6, 7, 8, 9, 10, 11, 12	1,362.0
7	15, 16, 17, 18, 19	1,359.3

• BM #

SOUTHWEST CORNER
OF THE SE1/4 OF
SEC. 33, T27S, R2E

SHEET 2 OF 2