

REMOVE CONCRETE DEBRIS PRIOR TO CONSTRUCTION INCIDENTAL TO BID ITEM FOR SITE CLEARING AND RESTORATION

CONSTRUCT STANDARD 29' PAVEMENT SECTION SEE DETAIL, SHEET 3

INSTALL 4" CONCRETE SIDEWALK (4" DEPTH)

STA 9+00.00 MILLRUN SAW CUT EXISTING PAVEMENT TO NEAT LINE AND MATCH EXISTING PAVEMENT REMOVE EXISTING E.O.R. MARKERS

INSTALL SNS "Millrun" "Blade"


BLADE STA 14+40.75 MILLRUN STA 14+53.90

CURVE #4
 L = 102.64'
 R = 100.00'
 Δ = 58°48'36"

CURVE #5
 L = 80.14'
 R = 137.35'
 Δ = 33°25'49"

NOTE: ROLL TYPE CURB AND GUTTER TO BE CONSTRUCTED ALONG PAVEMENT DEPICTED ON THIS SHEET

SAWMILL CREEK ADDITION
 MILLRUN
 WICHITA, KANSAS



Ruggles & Bohm, P.A.
 Engineering, Surveying, Land Planning
 924 North Main
 Wichita, Kansas 67203
 www.rbkansas.com

(316) 284-8008
 (316) 284-4821 fax
 E-mail: info@rbkansas.com

DRAWING FILE: Paving [Spyglass 01]
 PROJECT NUMBER: 472-84123
 DATE: Jan. 17, 2005

DESIGN	AML	SHEET 9 OF 38
DRAWN	AML	
REVIEW		
UTILITY		