Maintain existing construction entrance.

Maintain 3,050 L.F. existing silt fence. Replace if missing or damaged.

Relocate existing construction entrance at intersection of 127th St. N. & 127th St. Ct. as necessary for street construction.

Maintain curb inlet sediment barriers.

Maintain all existing erosion control measures including rip-rap & cutoff trench.

Install 1,390 L.F. Curlex Blanket

Maintain existing sediment barriers.

Maintain 3,050 L.F. existing silt fence. Replace if missing or damaged.

Scale: 1" = 60'

EROSION CONTROL PLAN
LEGEND
(Installation Details Found in the SWPP Plan)

- LIGHT STONE RIP-RAP
- DROP INLET PROTECTION
- CURB INLET PROTECTION
- STRAW BALE BARRIERS
- SILT FENCING
- EARTH DIKES
- CURLEX BLANKET

NO SCALE

NOTE: Contractor shall remove & replace existing erosion control measures as necessary for construction. Contractor shall be required to maintain all on-site erosion control items until final acceptance by the City of Wichita.

Baughman

THE FAIRMONT 3RD ADD. - PH I
Erosion Control Plan
STREET IMPROVEMENTS

Baughman Company, P.A. 315 Ellis St. Wichita, KS 67211 P 316.262.7271 F 316.262.0149
ENGINEERING | SURVEYING | PLANNING | LANDSCAPE ARCHITECTURE

PROJECT NUMBER 472-84136
REVISIONS
DESIGN Staff
DRAWN
APPROVED
DATE 02/05
SCALE NOTED
SHEET 7 OF 15

The Fairmont 3rd\STErosion
04-04-E871