
BENCHMARKS:
BM #1: "X" on the West End of the Steel Casing Pipe at the Railroad Crossing South of 37th Street North Sta. 25+90, 41' Rt.
Elev. = 1336.58 MSL

BM #2: Steel T-Post Driven 4' Deep Sta. 18+00, 25' Rt.
Elev. = 1337.73 MSL

BM #3: "□" in the Concrete Footing of the SBC Pedestal in the South West Corner of 37th Street North and Tyler Road Sta. 8+56, 95' Rt.
Elev. = 1342.17 MSL

BM #4: Railroad Spike in the East Face of the 2nd Power Pole North of 37th Street and West of Tyler Road Sta. 94+24, 48' Lt.
Elev. = 1342.85 MSL

Scale: 1" = 20'
• = Iron



Curve #6
Curve Data Based on Centerline
Rad. = 35' Delta = 90°00'0" Tangent = 35.00'
Arc = 149.23' L.C. = 134.35' Def/Ft. = 18.09286 Min.

Station	Arc	FACE CHORD LENGTHS 8' Lt.	8' Rt.	Defl.	T. Defl.
10+44.45	–	–	–	0°00'00"	0°00'00"
10+50.00	5.55'	4.09'	7.01'	1°40'25"	1°40'25"
10+75.00	25.00'	18.37'	31.49'	7°32'19"	9°12'44"
11+00.00	25.00'	18.37'	31.49'	7°32'19"	16°45'04"
11+25.00	25.00'	18.37'	31.49'	7°32'19"	24°17'23"
11+50.00	25.00'	18.37'	31.49'	7°32'19"	31°49'42"
11+75.00	25.00'	18.37'	31.49'	7°32'19"	39°22'01"
11+93.68	18.68'	13.74'	23.56'	5°37'59"	45°00'00"

Adjust water valve boxes as needed to grade. Incidental to 'Site Clearing and Restoration'.

Contractor to remove existing trees, fence, etc. as needed to complete paving project. Removal shall be incidental to bid item 'Site Clearing and Restoration'.

NOTE: ROLL TYPE CURB & GUTTER TO BE CONSTRUCTED ON THE PAVEMENT SHOWN ON THIS SHEET. TOP OF CURB ELEVATIONS ARE GIVEN FOR FULL HEIGHT CURB.

Baughman

Tyler's Landing 3rd Addition - Phase I
Forest Ridge
STA 8+61.45 TO STA 11+93.68

Baughman Company, P.A. 315 Elle St. Wichita, KS 67211 P 316.262.2221 F 316.262.0149
ENGINEERING | SURVEYING | PLANNING | LANDSCAPE ARCHITECTURE

PROJECT NUMBER 47284262
DESIGN AEG DRAWN JWH/TMS
APPROVED DATE 08/05
REVISIONS:
SCALE Noted
SHEET **8** OF **52**

tylers landing 3rdplat1.dwg 0507-E283